[INCH-POUND]
A-A-58065
11 June 1996

COMMERCIAL ITEM DESCRIPTION

MOUNTER-DEMOUNTER, PNEUMATIC TIRE, STATIONARY

The General Semites Administration has authorized
the use of this commercial item description, for all federal agencies

1. SCOPE. This Commercial Item Description (CID) covers a stationary, hydraulic motor driven mounter-dernounter for tube-type or tubeless tires used on trucks, busses, tractors, and earth moving equipment.

2. SALIENT CHARACTERISTICS

2.1 Sizes. The mounter-demounter shall have the capability of accommodating tube and tubeless tires up to 83 inches in diameter and rims from 15 to 44 inches in diameter to a maximum width up to 40 inches

2.2 Design and construction The mounter-demounter shall be an electro-hydraulic type The mounter-demounter shall be capable of being serviced in the field by personnel of average mechanical skill,

2.3 Features The mounter-demounter shall have an adjustable or mobile control console that allow for one person operation The mounter-demounter shall have an adjustable pressure regulator and gauge to match chuck pressure to rim size A portable ramp or tire lifting device shall be included to maneuver tires on and off the mounter-demounter.

2.4 Jaws The jaws shall rotate clockwise and counter clockwise. The jaws shall not open if hydraulic pressure drops.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to SA-ALC/TIL DD, Kelly AFB, TX 78241-5000. FAX 210-925-0902

Fsc 4910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.5 Clamping chuck The clamping chuck shall be hydraulically controlled and self-centering to the appropriate rim size

2.6 Controls The mounter-demounter shall be capable of having all operations controlled by a single control console The control console shall have a dedicated lever or control device for each power operation and shall be of the "deadman" type

2.7 Noise The mounter-demounter under any operating condition shall be shall not exceed 84 dBA (slow scale) measured not more than four feet from the perimeter of the unit

2.8 Electrical power requirements The power requirements of this mounter-demounter shall be at least 110 volts, single phase, 30 amps. The electrical system shall include a resetable breaker or thermal overload protection device

2.9 Life The operational life of the mounter-demounter shall beat least twenty years

2.1.O Corrosion resistance The mounter-demounter shall be designed to be corrosion resistant

2.11 Maintainability. A minimum number of parts and tools shall be required to maintain the mounter-demounter during its life cycle The electric motor, hydraulic pump, and drive assembly shall be enclosed to prevent environmental contamination. Removable panels shall be a part of the design to afford access to the electric motor and hydraulic pump and drive assembly.

2.1.2 Finish. The mounter-demounter shall be finished to the manufacturers best commercial practice

2.1.3 Accessories The mounter-demounter shall include all the necessary tools, adapters, and attachments Operation and repair parts manuals shall be furnished as specified in the contract

3. REGULATORY REQUIREMENTS

3.1 Safety The mounter-demounter shall comply with Federal OSHA requirements in effect as of the date the proposal is issued The Federal OSHA regulations shall take precedence in the event of conflict with state or local OSHA regulations

4. QUALITY ASSURANCE PROVISIONS

4.1 Product Conformance, The mounter-demounter provided shall meet the salient characteristics of this commercial item description, conform to the producer’s own drawings, specifications, standards, and quality assurance practices, and be the same unit offered for sale in the commercial market The government reserves the right to require proof of such conformance

4.2 Market Accpetability The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

4.2.1 The company producing the item must have been producing a product meeting the requirements of this CID, for at least 2 years

4.2.2 The company must have sold 500 units meeting this CID, in the commercial market place over the past 2 years

4.3 Inspection requirements and testing

4.3.1 Classification of tests. The inspection and testing of the mounter-demounter shall be conducted in accordance with paragraphs 2 1 through 2 7 Classification of the types of failures is described in Appendix A, Bid Sample Evaluation Criteria

4.3.2 Bid sample acceptance Acceptance shall be contingent upon the results of all tests described under paragraph 2

4.3.3 Inspection of unit The bid samples shall be inspected in detail to confirm adherence wit h specified requirements not otherwise tested for This inspection shall be accomplished using a contractor developed check list that identifies specific mounter-demounter attributes for which inspections are made and results obtained.

4.3.4 Tire change test. A truck tire shall be changed in order to ensure that the mounter-demounter complies with paragraphs 21 through 27

4.3.5 Noise test The mounter-demounter shall be tested to demonstrate the noise level of the operating unit meets the noise limit specified by para 27

5. PACKAGING Preservation. packing, and marking shall be as specified in the contract or order

6. NOTES.

6.1 Ordering data Procurement documents must specify the title, number and date of this CID and must specify the size of the mounter-demounter to be procured Other than the size, this CID provides for no ordering options

6.2 Bid samples. The government will request a bid sample from the contractor that wishes to be considered for contract award. A 14 to 30 day evaluation on each bid sample will be made at SA-ALC/LDEE, Building 1562, Kelly AFB, TX 78241 Bid samples should be shipped to this address Contractor shall furnish continuous maintenance support (parts and labor) during the evaluation (see Appendix 4 - Bid sample evaluation criteria)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6.3 Metric products Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard 376 and all other requirements of this commercial item description are met If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should b made to the contracting officer to determine if the product is acceptable, The contracting officer has the option of accepting or rejecting the product

MILITARY INTERESTS
Air Force -99
Army-AL
DLA - CS
Navy -YDl

Preparing Activity
Air Force -82

Agent Activity
Air Force -99

Project Number 4910-0789

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

APPENDIX A

BID SAMPLE EVALUATION CRITERIA

1. If an offeror proposes to modify equipment to be provided under any contract resulting here from (production units) so that the production units are not identical to the bid sample units, the offeror must

a Submit a clear description of the modification with their proposal

b. Mark any descriptive material (e.g. operation and maintenance manuals) to reflect the modifications

c. Propose a unique model and/or part number which will be applicable to the production units

2. A major modification is one which will have significant effect upon the salient characteristics of the mounter-demounters. A minor modification is one which will not affect the salient performance characteristics of the equipment. The government will determine whether a modification is major or minor. No modification will be permitted after the deadline for submission of bid sample. any bid samples which require major modification order to comply with the specification, shall be declared unacceptable and the offeror shall be determined nonresponsive

3. All production equipment must conform in all respects to the bid samples (model and/or part number), as approved by the Government If the approved units identification must be modified in the production units

4. Bid sample failures The Government alone will determine when a failure exists and whether the failure is major or minor

a. Major failure Failure to meet the Air Force's specified parameters due to design limitations or operational inability's of the mounter-demounters Inaccuracies and/or out-of tolerance conditions caused by any internal deficiencies which do not create a critical defect shall be considered a major failure A single major failure will result in disapproval.

b. Minor failure A defect which will not reduce the ability of the mounter-demounter to be used for its intended purpose.

1). The vendor will be permitted to correct one minor failures with the understanding that the production units will not incorporate the minor failures into the production quantities. More than two minor failures will make the bid sample package unacceptable A major failure will also render the package unacceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2). The offeror shall be responsible for providing all components, test units, and personnel necessary to correct the failure Use of Government facilities and/or equipment shall be permitted at the option of the Government but shall be at the risk of the offeror

3). The offeror must submit to the government, with five working days after the failure has been corrected 1) a detailed written description of the corrective action taken, and 2) a written summary describing the impact of such corrective action on any descriptive material (e g, OEM manuals) submitted as part of the technical proposal

5. The bid samples shall be tested in accordance with the tests specified in the CID and shall cerify minimum government requirements defined herein as salient characteristics Bid sample failures will be major or minor The testing shall be in accordance with paragraph 20 and classification of the failures shall be as follows

a. Examination of the mounter-demounter The samples shall be examined in detail to confirm adherence with specified requirements not otherwise tested for A checklist shall identify specific mounter-demounter attributes for which the examination of being made and the results obtained. This includes adequacy of design that conforms to the user's needs and inherent quality and durability of the product when in use The mounter-demounter shall be examined in accordance paragraph 2.1 Failure of the mounter-demounter to meet this requirement is a minor failure

b. Design and construction The mounter-demounter must be capable of performing in accordance with paragraph 2.2 Failure of the mounter-demounter to meet this requirement is a major failure

c. Features The mounter-demounter must have the features as described in paragraph 23 Failure of the mounter-demounter to meet this requirement is a major failure

d. Jaws The mounter-demounter must be capable of operating in accordance with paragraph 24 and have the features described in this paragraph Failure of the mounter-demounter to meet this requirement is a minor failure

e. Clamping chuck The mounter-demounter must be capable of operating in accordance with paragraph 25 and have the features as described m this paragraph Failure of the mounter-demounter to meet this requirement is a major failure

f. Controls The mounter-demounter must be capable of operating in accordance with paragraph 26 and the features as described in this paragraph Failure of the mounter-demounter to meet this requirement is a minor failure

g. Noise The mounter-demounter shall demonstrate that the noise level meets the limit specified by paragraph 27 of the CID Failure of the mounter-demounter(s) to meet this requirement is a minor failure

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.