INCH-POUND
A-A-58065B
26 February 2003
SUPERSEDING
A-A-58065A
26 April 2001

COMMERCIAL ITEM DESCRIPTION

MOUNTER-DEMOUNTER, PNEUMATIC TIRE, STATIONARY

The General Services Administration has authorized the use of this commercial item description, for all federal agencies

1. SCOPE. This Commercial Item Description (CID) covers a stationary, hydraulic motor driven mounter-demounter for tube-type or tubeless tires used on trucks, busses, tractors, and earth moving equipment.

2 CLASSIFICATION.

2.1 Type.

2.1.1 Types I and II. Both types of mounter-demounters shall have a portable ramp that enables the operator to maneuver tires on the moveable four position tool carriage so that no lifting is required. Both types of units shall be provided with a portable remote control panel that allows for operation of all functions and is capable of swinging out of the way for convenience. The hydraulic chuck shall be three jaw, self-centering and have an adjustable clamp to ensure proper wheel mounting. The jaws shall rotate clockwise and counter clockwise. The jaws shall not open if hydraulic pressure drops. Both type units shall meet the requirements of paragraph 3.3 (Electrical power requirements of 110 volts, single phase, 30 amps).

2.1.1.1 Type I. This mounter-demounter shall accommodate tube and tubeless tires up to 76 inches in diameter and rims from 15 to 38 inches in diameter to a maximum width of up to 34 inches maximum. The unit shall have a rotational torque capacity of 2900 foot pounds minimum.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: WR-ALC/TILCC, 420 Second Street, Suite 100, Robins AFB, GA 31098-1640.

AMSC N/A FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.1.1.2 Type II. This mounter-demounter shall accommodate tube and tubeless tires up to 83 inches in diameter and rims from 15 to 44 inches in diameter to a maximum width of up to 40 inches maximum. The unit shall have a rotational torque capacity of 4400 foot pounds minimum.

2.1.2 Type III. This mounter-demounter shall accommodate tube and tubeless tires up to 86.5 inches in diameter and rims from 10 to 17 inches in diameter to a maximum width of up to 19 inches maximum. The unit shall have a portable remote control that operates the chuck rotation, vertical positioning, jaw and side movement of the carriage. It shall be provided with a self-centering chuck pedal-controlled jaw rotation direction, and low deck ramp for one-man operation. The unit shall be provided with a four-jaw, adjustable chuck clamps at the center hole or inside diameter. The jaws shall rotate clockwise and counter clockwise. The jaws shall not open if hydraulic pressure drops. The unit shall have a rotational torque capacity of 3850 foot pounds minimum.

2.1.3 Type IV. This mounter-demounter shall accommodate tube and tubeless tires up to 38 inches in diameter and rims from 10 to 17.5 inches in diameter to a maximum width of up to 19 inches. This type of mouner-demounter shall be air powered with no electrical requirement (para. 3.3 not required). The required air source shall be 110 to 175 PSI, 2 HP compressor, 5 SCFM minimum at 150 PSI. The mount and demount mechanism shall be conducted on a center post on top of the unit, with a centering cone to be used as a wheel clamping method. The bead loosening system control shall be by means of a foot control that loosens the wheel. An inflation gage shall be permanently mounted on the unit.

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The mounter-demounter shall be an electro-hydraulic type. The mounter-demounter shall be designed to be used at depots and tire shops by personnel of average mechanical skill.

3.2 Noise. The mounter-demounter shall not, under any operating condition exceed 84 dBA (slow scale) measured not more than four feet from the perimeter of the unit.

3.3 Electrical power requirements. The power requirements of this mounter-demounter shall be at least 110 volts, single phase, 30 amps. The electrical system shall include a resetable breaker or thermal overload protection device.

3.4 Life. The operational life of the mounter-demounter shall be at least twenty years.

3.5. Corrosion resistance. The mounter-demounter shall be corrosion resistant.

3.6 Maintainability. A minimum number of parts and tools shall be required to maintain the mounter-demounter during its life cycle. The electric motor, hydraulic pump, and drive assembly shall be enclosed to prevent environmental contamination. Removable panels shall be a part of the design to afford access to the electric motor and hydraulic pump and drive assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.7 Finish. The mounter-demounter shall be finished to the manufacturers best commercial practice.

3.8 Accessories. The mounter-demounter shall include all the necessary tools, adapters, and attachments. Operation and repair parts manuals shall be furnished as specified in the contract.

4. REGULATORY REQUIREMENTS

4.1 Safety. The mounter-demounter shall comply with Federal OSHA requirements in effect as of the date of the contractual document. The Federal OSHA regulations shall take precedence in the event of conflict with state or local OSHA regulations.

5. PRODUCT CONFORMANCE PROVISIONS

5.1 Product Conformance. The mounter-demounter provided shall meet the salient characteristics of this CID, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same unit offered for sale in the commercial market. The government reserves the right to require proof of such conformance by requesting contractor data that meets the requirements of this CID. The inspection and test requirements set forth in the contract document shall be applicable to this CID.

5.2 Inspection requirements and testing.

5.2.1 Classification of tests. The inspection and testing of the mounter-demounter shall be conducted in accordance with paragraphs 2.1 through 3.8.

5.2.2 Tire change test. A truck tire shall be changed in order to ensure that the mounter-demounter complies with paragraphs 2.1 through 3.8.

5.2.3 Noise test. The mounter-demounter shall be tested to demonstrate that the noise level of the operating unit meets the noise limit specified by para 3.2.

6. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES.

7.1 Ordering data. Procurement documents must specify the title, number and date of this CID and must specify the type of the mounter-demounter to be procured.

7.2 Part or Identification Number (PIN). The following part or identification numbering procedure is for government purposes only and does not constitute a requirement for the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.



7.3 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest re vision of Federal Standard 376 and all other requirements of this CID are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

7.4 National stock number (NSN), part number and cage number of units that meet the requirements of this CID:

Type I:

NSN 4910-01-330-1479
PN H.I.T. 5000
Cage 57791
PN AG52L
Cage 57791

Type II:

NSN 4910-01-375-2487
PN H.I.T 9000
Cage 57791

Type III:

NSN 4910-01-308-7609
PN H.I.T. 8000A
Cage 57791

Type IV:

NSN 4910-01-237-0292
PN 4050A
Cage 57791

Custodian:
Army - AR
Navy - YD
DLA - CC

Preparing Activity:
Air Force – 84

Agent:
Air Force – 99

(Project No. 4910-0854)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.