[INCH-POUND]
A-A-58067
28 Jun 96

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, DIESEL-ENGINE-DRIVEN, PNEUMATIC-TIRED, 15,000 POUNDS CAPACITY AT 24 INCH LOAD CENTER

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description covers the general requirements for a diesel engine driven, front wheel drive, rear wheel steer, pneumatic tired 15,000 pound at 24 inch load-center capacity, forklift truck. It shall be used for handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces.

2. SALIENT CHARACTERISTICS:

2.1 Safety. The forklift shall comply with ANSI B56.1, UL 558 Type D, and OSHA standards in effect at the time of manufacture. A seatbelt conforming to SAE J386, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be yellow for safe operation in an indoor environment.

2.2 Environmental requirements. The engine shall start without preheating within 5 minutes, and the truck shall operate as specified herein within 15 minutes after engine start, in any ambient temperature from 0 to 120 degrees F. The forklift shall be capable of continuous operation as specified herein at any ambient temperature up to 120 degrees F.

2.3. Engine and exhaust. A diesel engine shall be provided. The exhaust system shall be the overhead type, with provisions to prevent entry of rain water.

2.4 Fuel system. The forklift shall have all necessary filters, water separators, and other necessary components required for diesel fuel operation. It shall have a fuel tank of sufficient capacity to allow at least 8 hours of continuous operation.

2.5 Starting system. The starter motor shall not be capable of energizing while the engine is running.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: WR-ALC/LVRE, 225 Ocmulgee Court, Robins AFB GA 31088-1647

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.6 Transmission. A torque converter and a powershift type of transmission shall be furnished, with at least two (2) speeds forward and two (2) speeds reverse. The transmission shall provide for positive inching control, or declutch control, that permits lifting of rated load at maximum lifting speed while the transmission control is in either forward or reverse direction, without vehicle movement. This control shall also apply the service brakes.

2.7 Hydraulic system. A pressure relief protection device is required along with pump(s), cylinders, control valves, filter(s), reservoir, hoses, and all other components necessary to make a complete hydraulic system.

2.8 Uprights and carriage. With no load on the forks, the seated operator shall be able to see at least one fork tip at all lift heights and fork positions.

2.9 Forks. Fork dimensions shall be 2.56 inches maximum thickness, 8.06 inch maximum width, and 72.0 (+ or - 0.5 inch) long.

2.10 Fork positioner. A hydraulically powered fork positioner shall be furnished. It shall be controlled by the seated operator, with spacing of 18.0 inches (or less), to 60.0 inches (or more). These dimensions shall be measured to the outside edges of the forks.

2.11 Side shift. Hydraulically powered side shifting shall be furnished. It shall be controlled by seated operator, with at least 6.0 inches side shift each side of center (12.0 inches minimum total travel).

2.12 Load backrest. The load backrest, in conjunction with the forks and carriage, shall provide a vertical rear load guard of at least 48 inches high, measured from the load horizontal carrying surfaces of the forks.

2.13 Steering. Power steering shall be furnished.

2.14 Service brakes. Power brakes conforming to ANSI B56.1 shall be furnished.

2.15 Parking brake. Parking brake shall conform to ANSI B56.1.

2.16 Electrical system. Shall be a 12 volt system with battery(ies), alternator, regulator, wiring, fuses or circuit breakers, and all other components necessary to make a complete electrical system.

2.17 Instruments. The following gauges (or warning indicator lights where indicated) shall be mounted on the instrument panel. They shall be illuminated for night time operation, except as noted:

(1) Ammeter or voltmeter (may be warning light).
(2) Engine oil pressure (may be warning light).
(3) Engine coolant temperature.
(4) Transmission fluid temperature.
(5) Hourmeter, capable of totaling at least 9999 hours (not illuminated).
(6) Fuel gauge.
(7) Air brake pressure gauge, if air brakes are furnished.

2.18 External lights. Minimum of three floodlights. Two in front, mounted on the upright, facing forward, and one mounted in the rear, facing rearward.

2.19 Taillight. One combination stoplight and taillight conforming to SAE J585 and J586.

2.20 Horn. Horn button shall be mounted in the center of the steering wheel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.21 Operator's overhead guard. The guard shall be in accordance with ANSI B56.1. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI B56.1.

2.22 Cab. A cab shall be furnished. It shall be either an integral part of, or one that is built around, the overhead guard. The cab shall be insulated, have two opening doors, and at least one fan for ventilation. There shall be sufficient window area to permit at least 250 degrees of horizontal visibility by the seated operator. The height, from the ground to the top of the cab shall be not more than 116 inches.

2.23 Heater. A combination, or separate, heater-defroster with fan shall be provided.

2.24 Windshield wipers. There shall be at least three wipers, one on the front windshield, one on the rear window, and one on the roof window.

2.25 The truck shall be capable of meeting the following performance requirements:

(1) Capability to safely handle a 15,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. It shall be able to handle this load at all lift height and fork side shift that the forklift is capable of attaining.

(2) Load lifting speed: At least 55 feet per minute.

(3) Load lowering speed: Not more than 80 feet per minute and not less than 40 feet per minute with rated load on the forks and with engine at idle speed.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 270 inches.

(5) Travel speed: 12 miles per hour minimum, in both forward and reverse, while carrying rated load on the forks.

(6) Slope ascension: With the truck facing up the slope and with rated load on the forks it shall be able to accelerate up a 20 percent slope from a dead stop.

(7) Upright tilt: With no load on the truck the forks shall have at least 3.0 degrees forward tilt, and at least 6.0 degrees of rear tilt.

(8) Lowest upright height (collapsed mast height): 116.0 inches maximum with no load on the forks.

(9) Maximum fork lift height. At least 210 inches with rated load on forks and forks horizontal.

(10) Drift of load. With hydraulic fluid at ambient temperature, lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1-3/4 inch of vertical drift, and not more than 1.0 degree of rotational drift.

(12) Stability. The forklift shall meet the ANSI B56.1 "forward stacking", "forward travel", "lateral stacking", and "lateral travel" stability requirements.

(13) Noise limits. The maximum allowable at the operator's ear is 95 db(A). If the noise level at the operator's ear exceeds 84 db(A) (85 to 95 db(A)), a warning sign stating that operator’s hearing protection is required shall be installed at the operator’s station. The sign shall be at least 4 inches square, with a yellow background.

2.26 Painting. The forklift shall be primed and painted using standard commercial practices. The final color shall be yellow, unless otherwise specified.

2.27 Walkway coating. Step surfaces shall be covered or coated with a non-slip coating, or shall be furnished with a non-slip metal surface.

2.28 Slinging and tie-down provisions. There shall be permanently installed slinging devices that enable the truck to be lifted in its normal travel position, and tie-downs that that enable the truck to be tied down to the floor of the transportation media. All devices shall be capable of accepting a chain and hook with an outside diameter of 3.0 inches and shall have a structural safety factor of at least 2.3 to 1, based on static load. The notation “LIFT HERE” or “TIE DOWN” shall be stenciled, in black letters, near each lifting and tie-down device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.29 Electromagnetic radiation. The forklift shall not exceed the limits of electromagnetic radiation specified in SAE J551.

2.30 Highway transportability. The truck, when loaded on a semi-trailer, shall be within the highway permit limits for all states.

2.31 An identification plate made of a corrosion resistive material shall be permanently installed at an easily accessible place on the truck. It shall contain the following information:

NOMENCLATURE:
MANUFACTURER'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURE:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER
REGISTRATION NUMBER:

3. REGULATORY REQUIREMENTS

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extend practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or recomponents, pieces, and parts shall not be incorporated in the forklift.

4. QUALITY ASSURANCE PROVISIONS

4.1 Product Conformance. The products provided shall meet the salient characteristics of this Commercial Item Description, conform to the producer's own drawings, specifications, standards and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4.2. Market Acceptability

4.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offerers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.
(2) Total sale of the item to the general public during the three years.
(3) Length of time the item has been sold in the commercial market place.
(4) Other pertinent information necessary to determine that the item is an established commercial item.

5. PACKAGING. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

CUSTODIANS:
Air Force-99
Army-AT
Navy-SA

PREPARING ACTIVITY:
Air Force - 84

AGENT: 99

(Project: 3930-0682)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.