INCH – POUND

A-A-58069A
22 December 2014
SUPERSEDING
A-A-58069
28 June 1996

COMMERCIAL ITEM DESCRIPTION

TRUCK, LIFT, FORK, ELECTRIC, ORDER SELECTOR, HIGH LIFT RIDER, 3000 POUND CAPACITY, 193 INCH MINIMUM LIFT

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-T-83809 (84) for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers the general requirements for a battery powered, order selector, high lift rider (as defined by ANSI/ITSDF B56.1) industrial type, forklift truck. The truck will be Type E, unless otherwise specified as Type EE (see 6.3), in accordance with UL 583. The trucks are intended for stacking, unstacking, and moving cargo in and around commissary warehouses; also for moving cargo in and out of highway trailers and railroad cars.

2. SALIENT CHARACTERISTICS.

2.1 Safety. The operator driven vehicle shall be capable of operation within the accuracies, limits, and specifications herein. The forklift shall comply with ANSI/ITSDF B56.1, OSHA, and all other applicable standards in effect at the time of manufacture. A means for securing the operator, conforming to ANSI/ITSDF B56.1, and restraint devices designed to ensure the operator's upper body remains entirely within the protection of the overhead guard in the event of tip-over shall be provided. Unless otherwise specified in the contract, the final color shall be the manufacturer's standard commercial color for safe operation in an indoor environment.

2.2 Environmental requirements. The forklift shall be capable of continuous operation as specified herein at any ambient temperature from 0 degrees F to 120 degrees F.

2.3 Battery. The battery shall have adequate capacity to provide not less than 8.0 hours of continuous operation under normal industrial use. The battery mounted half connector shall be the "SB" type. When specified (see 6.3), a battery charger shall be shipped with the forklift.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data that may improve this document should be sent to AFLCMC/WNZ, 235 Byron Street, Suite 19A, Robins AFB, GA 31098-1813. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.4 Hydraulic system(s). A pressure relief protection device is required along with pump(s), cylinders, control valves, filter(s), reservoir, hoses, and all other components necessary to make a complete hydraulic system(s).

2.5 Operator's overhead guard. The guard shall be in accordance with ANSI/ITSDF B56.1. It shall also be a falling-object-protective-structure (FOPS) conforming to ANSI/ITSDF B56.1. Overhead guard height from ground to top of guard shall be 95 inches maximum.

2.6 Forks. Fork dimensions shall be 2.06 inches maximum thickness, 5.06 inches maximum width, and 40.0 (+ or - 1.0) inches in length.

2.7 Fork positioner. The forks shall be capable of being laterally positioned manually without the need of tools. With the forks at their widest spacing, they shall spread at least 28 inches, and with the forks at their narrowest spacing, they shall spread not more than 22 inches, measured from the outside of the forks.

2.8 Operator’s platform. The operator’s platform of adequate size to allow safe and efficient operation shall be provided. The platform shall have railings on both sides running from the floor of the platform to approximately half the height of the overhead guard. There shall be a tether safety belt that fastens around the operator’s waist. The operator’s platform shall be capable of lowering to ground level, at a speed of not more than 60 feet per minute, with the operator on the platform and the rated load on the forks in the event of hydraulic, electrical, or some other failure that interferes with the normal operation of the truck.

2.9 Pallet clamp. A mechanically, electrically, or hydraulically operated pallet clamp and guide shall be mounted to the front carriage between the forks, below the integral with the operator’s platform. The pallet clamp shall be capable of clamping to the center stringer of a pallet to prevent shifting or tilting of the pallet.

2.10 Controls. All controls shall be in accordance with ANSI/ITSDF B56.1. All load motion controls shall be self-centering, that is they shall return to the neutral position when released.

2.11 Steering. Power steering shall be furnished.

2.12 Horn. Horn button shall be mounted within reach of the operator.

2.13 Service brakes. Service brakes conforming to ANSI/ITSDF B56.1 shall be furnished.

2.14 Parking brake. Parking brake shall conform to ANSI/ITSDF B56.1.

2.15 Indicators. The truck shall be equipped with a battery discharge indicator and an hour meter, both visible to the operator.

2.16 External lights. There shall be at least two sealed beam, 25 watts minimum, floodlights. One shall be facing forward, mounted on the left side of the mast, and one mounted in the rear, facing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

rearward. The forklift shall be equipped with an amber colored strobe light with an intensity of at least 40 candela.

2.17 Taillight. One combination stoplight and taillight conforming to SAE J585 and J586 shall be installed.

2.18 Painting. The forklift shall be primed and painted using standard commercial practices. The final color shall be the manufacturer's standard commercial color.

2.19 Walkway coating. Floor plates and step surfaces shall be coated with a non-slip coating compound or be furnished with a non-slip metal surface.

2.20 Electromagnetic interference (EMI) suppression. The forklift shall comply with the EMI requirements per MIL-STD-461, RE101 and RE102.

2.21 Performance. The truck shall be capable of meeting the following performance requirements:

(1) Capability to safely handle the rated load, which is defined as 3,000 pound, 48 inch per side cube with the center of gravity at the center of the cube. It shall be able to handle this load at all lift heights that the forklift is capable of attaining.

(2) Load lifting speed: At least 35 feet per minute with rated load on forks.

(3) Load lowering speed: With rated load on forks, not more than 60 feet per minute. With unloaded forks, not less than 25 feet per minute.

(4) Right angle turn: With rated load on the forks and forklift located perpendicular to a wall, and with the front of the load against the wall, the truck shall be able to back up and make a complete right angle turn (ending up parallel to the wall) within 130 inches.

(5) Travel speed: Shall be capable of traveling at least 4 miles per hour, in both forward and reverse directions, while carrying rated load on the forks..

(6) Slope ascension: With rated load on the forks it shall be able to accelerate up a 5 percent slope from a dead stop in both forward and reverse directions.

(7) Lowest upright height (collapsed mast height): 95.0 inches maximum with no load on the forks.

(8) Minimum fork lift height. At least 193 inches with rated load on forks measured from ground to upper surface of forks.

(9) Drift of load. With hydraulic fluid at normal operating temperature, lift assembly shall hold rated load at maximum lift height for at least 10.0 minutes with not more than 1.00 inch of vertical drift.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

(10) Stability. The forklift shall meet the ANSI/ITSDF B56.1 "forward stacking," "forward travel," "lateral stacking," and "lateral travel" stability requirements.

2.22 Identification plate. An identification plate made of a corrosion resistive material shall be permanently installed at an easily accessible location. It shall contain the following information:

NOMENCLATURE:
MANUFACTURE'S NAME:
MANUFACTURER'S ADDRESS:
MANUFACTURER'S SERVICE PHONE NUMBER:
MANUFACTURER'S MODEL NUMBER:
MANUFACTURER'S SERIAL NUMBER:
DATE OF MANUFACTURER:
CONTRACT NUMBER:
NATIONAL STOCK NUMBER:
REGISTRATION NUMBER:

2.23 Manuals.

PSME – Electronic copy of Operators, Parts and Service Manuals formatted in Indexed Portable Document Format (IPDF) to be sent to the following address. Only one electronic copy is required per order regardless of quantity of vehicles.

The contractor shall provide forklift manuals consisting of Operators, Parts, and Service Manuals. The contractor's Parts Manuals shall list the part numbers for contractor-manufactured parts, plus the part numbers for purchased sub-level components and whole components. Manuals shall be provided in accordance with DFARS 252.227-7015 Technical Data - Commercial Items.

If sending via USPS:
Support Equipment & Vehicles Division
Forklift IPT
AFLCMC/WNZEB
235 Byron Street, Suite 19A
Robins AFB, GA 31098-1813

If sending via Fed Ex or UPS:
Support Equipment & Vehicles Division
Forklift IPT
AFLCMC/WNZEB
235 Byron Street, Suite 19A
Bldg 300WW South End
Bay D, Door 27A
Robins AFB, GA 31098-1813

3. REGULATORY REQUIREMENTS

3.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). However, used, rebuilt, or remanufactured components, pieces, and parts shall not be incorporated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

3.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired: a) competitively within a reasonable timeframe; b) meet appropriate performance standards, or c) at a reasonable price. The prime contractor is responsible for ensuring that all subcontractors comply with this requirement.

4. PRODUCT CONFORMANCE PROVISIONS

4.1 Product conformance. The products provided shall conform to the producer's own drawings, specifications, standards, and quality assurance practices and shall be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Market Acceptability. The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

4.2.1 Commercial. The vehicle furnished shall be, as of the date of award, the latest model (with minor modifications, as that term is defined in DoD FAR Supplement 252.211-7012, Paragraph K-85 of the solicitation) of an established product previously produced and sold in substantial commercial quantities (exceeding the criteria at FAR 15.804-3(f)(2)(ii)(A)) for at least three years. The vehicle furnished, or earlier models of it, absent minor modifications, shall have routinely been supported with spare/repair parts which were produced or sold in the normal course of business. At the time of delivery, the contractor shall furnish the Administrative Contracting Officer with verification of compliance with these requirements. Offers shall provide, as part of their proposals, the following information on the vehicle (or its earlier models) being offered as a commercial item:

(1) Total sales to the U.S. Government or to contractors for U.S. Government use during the three years.

(2) Total sales of the item to the general public during the three years.

(3) Length of time the item has been sold in the commercial market place.

5. PACKAGING

5.1 Packaging. Preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The vehicle is intended for use in handling cargo in and around warehouses, loading platforms, and docks; on paved or other hard surfaces.

6.2 Source of documents.

6.2.1 Military Specifications, Standards, and Handbooks referenced herein may be obtained online at http:/quicksearch.dla.mil or from the Standardization Document Order Desk, Building 4, Section D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

6.2.2 The Society of Automotive Engineers (SAE) documents may be obtained online at http://www.sae.org/ or from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

6.2.3 Occupational Safety and Health Association (OSHA) documents may be obtained online at http://www.osha.gov/ .

6.2.4 FAR and DFARS may be obtained from the Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954. Electronic copies of the FAR may be obtained from https://www.acquisition.gov/far/ . Electronic copies of the DFARS may be obtained from http://www.acq.osd.mil/dpap/dars/dfars/index.htm .

6.2.5 ANSI standards may be obtained at http://www.ansi.org or available from the Electronics American National Standards Institute, 1899 L Street, NW, 11th Floor, Washington, DC, 20036.

6.2.6 Industrial Truck Standards Development Foundation (ITSDF) standards may be obtained from Suite 460, 1750 K Street NW, Washington, DC 20006. Electronic copies may be obtained from http://www.itsdf.org/

6.2.7 Underwriters Laboratories (UL) copies may be obtained online at http://www.ul.com/ or from: 333 Pfingsten Road, Northbrook, IL 60062-2096.

6.3 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Type of forklift, if different (see 1.1)
c. Battery charger, if required (see 2.3)

6.4 Key Words.

Battery powered
Hour meter
Yellow

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

MILITARY INTERESTS:

Custodians:
Army - AT
Navy - SA
Air Force - 84

Preparing Activity:
Air Force – 84

Reviewers:
Air Force – 99
DLA - IS

Agent:
Air Force – 99

(Project 3930-2013-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.