INCH-POUND
A-A-58070 (USAF)
1 July 96

COMMERCIAL ITEM DESCRIPTION

GAGE, INDICATOR BORE

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-G-26762B for all federal agencies.

1. SCOPE

1.1 This commercial item description (CID) covers several types, styles, and classes of bore gages with dial or digital indicators normally used to inspect, measure, or test the accuracy of inside diameters within a specified range.

2. CLASSIFICATION

2.1 Bore gages shall be of the following types, styles, classes, and sizes as specified (see 7.1).

2.1.1 Types and styles. Types of gaging heads and style of contact points.

Type I - Plug
  Style A - Thru-hole
  Style B - Blind hole

Type II - Centralizing plunger

Type III - Retracting Contacts
  Style C - Two point
  Style D - Three point

Type IV - Pin
Type V - Split ball
Type VI - Blind hole
Type VII - Conical-ball
Type VIII - Referencing contact
Type IX - Interchangeable anvil
Type X - Micrometer head

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: WR-ALC/LKJE, 460 Second Street, STE 221 Robins AFB GA 31098-1640

AMSC N/A FSC 5210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

2.1.2 Classification.

Class 1 - Digital indicator; 0.00005 in graduation
Class 2 - Dial indicator; 0.0001 in graduation
Class 3 - Dial indicator; 0.0005 in graduation
Class 4 - Dial indicator; 0.001 in graduation

2.1.3 Sizes. Sizes for each type and style of bore gage, consisting of bore size, gaging depth, and contact distance to head, shall be as specified (see 7.1).

3. SALIENT CHARACTERISTICS

3.1 General Requirements. The bore gage shall be hand held and shall include easy means of interchanging components for quick changeover of gaging head assemblies. Interchangeable gaging head assemblies, contact points, extension rods/tubes, spacers, adapters, and the like, shall be provided as required to obtain the length or depth of gaging in hole as specified (see 7.1). The bore gage shall include an indicator, and may include optional items such as setting masters or rings, stop collars, and protective storage cases as specified (see 7.1).

3.2 Construction. The bore gage and associated components identified herein shall be constructed of materials that will withstand normal shop usage, and all components shall meet acceptable industry standards of workmanship and materials for commercial items of this type. Construction features shall include a means of assembling and adjusting components to meet the requirements of Table I and sizes as specified (see 7.1), with the use of a single indicator. The contact point material shall be as specified (see 7.1).

3.2.1 Indicators. The bore gage indicator shall be of a dial or digital electronic design. Adapter kits shall be furnished when necessary to secure gaging head assembly to indicator. Cables for digital indicators shall be provided when digital output is specified (see 7.1).

3.2.2 Handles and housings. Removable handles, when applicable, shall be of the in-line style unless otherwise specified (see 7.1). For indicators with digital output, pistol-grip handles may be provided in lieu of the in-line style. Removable indicator housings shall be provided when specified (see 7.1).

3.3 Capacities and ranges. The capacities and ranges of the bore gage shall be as specified in Table I. Ranges may depend upon the use of one or more interchangeable gaging head assemblies, adapters and/or extensions of various lengths.

TABLE I. Capacities and Ranges

TYPES AND STYLES	BORE SIZE RANGE (ID.in.)	GAGING DEPTH RANGE (IN.) (If applicable)	CONTACT TO HEAD RANGE (IN) (If applicable)
Plug			
Thru-hole	0.217 - 4.50	1.000 - 1.509	0.250 - 0.748
Blind-hole	0.217 - 4.50	1.000 - 1.509	0.031 - 0.157
Centralizing plunger			
Two point	0.25 - 24.00	2.25 - 9.37	0.140 - 0.375
Three point	0.25 - 24.00	2.25 - 9.37	0.140 - 0.375

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

TABLE I. Capacities and Ranges - Continued.

TYPES AND STYLES	BORE SIZE RANGE (ID.in.)	GAGING DEPTH RANGE (IN.) (If applicable)	CONTACT TO HEAD RANGE (IN) (If applicable)
Retracting contact	0.670 - 15.825	6.0 - 12.0	0.437 - 1.620
Pin	6.0 - 24.0		
Split ball	0.0185 - 1.6000	0.8125 - 2.5000	
Blind hole	0.057 - 1.600		
Conical-ball	0.063 - 0.255	0.375 - 1.000	0.022 - 0.064
Referencing contact	0.5 - 8.0		
Interchangeable anvil	0.275 - 6.0	6.0	
Micrometer head	1.40 - 32.0	6.0 - 10.0	

4. REGULATORY REQUIREMENTS

4.1 Recycled, recovered, or environmentally preferable materials. Recycled, recovered, or environmentally preferable materials should be used to the maximum extent possible provided that the material meets or exceeds the operational and maintenance requirement, and promotes economically advantageous life cycle costs.

4.2 Environmental protection. The bore gage shall meet all applicable Environmental Protection Agency restrictions in effect on the date of the contract. These regulations apply to the emission of materials hazardous to the environment or the operator's health and shall be met during the manufacturing, service, transportation, storage, and operation of the gage.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description , conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6. PACKAGING

6.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be as specified in the contract or purchase order (See 7.1).

7. NOTES

7.1 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this document
b. Type, style, class, and size of bore gage required (see 2.1)
c. Setting masters or rings, stop collars, protective storage cases, if required (see 3.1)
d. Contact points material (see 3.2)
e. Digital output cables, if required (see 3.2.1)
f. Handle style and indicator housings, if required (3.2.2)
g. Packaging requirements, if required (see 6.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

7.2 National Stock Numbers (NSNs). The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

5210-00-516-9031
5210-00-540-3406
5210-00-540-3407
5210-00-540-3408
5210-00-540-3409
5210-00-540-3805
5210-00-542-4392
5210-00-554-7339
5210-00-554-7341
5210-00-554-7342
5210-00-554-7340

7.3 Known sources. The following is a list of sources known to meet the requirements of this CID. The list may not be indicative of all possible sources.

FEDERAL PRODUCTS
FOWLER PRECISION TOOLS
MITUTOYO MEASURING INSTRUMENTS
STANDARD GAGES
STARRETT TOOLS

7.4 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

This example describes a part number system for CID A-A-XXX.

AAXXX - H 0 A 0.500-0.625 Example of reference part number: AAXXX-H0A0.500-0.625

Size: As specified

Class:	A	-	Class 1 - Digital indicator; 0.00005 in grad
	B	-	Class 2 - Dial indicator; 0.0001 in graduation
	C	-	Class 3 - Dial indicator; 0.0005 in graduation
	D	-	Class 4 - Dial indicator; 0.001 in graduation
Style:	0	-	None
	1	-	Style A- Thru-hole
	2	-	Style B - Blind hole
	3	-	Style C - Two point
	4	-	Style D - Three point
Type:	A	-	Type I - Plug
	B	-	Type II - Centralizing plunger
	C	-	Type III - Retracting contact
	D	-	Type IV - Pin
	E	-	Type V - Split ball
	F	-	Type VI - Blind hole
	G	-	Type VII - Conical-ball

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.

H - Type VIII - Referencing contact
I - Type IX - Interchangeable anvil
J - Type X - Micrometer head

MILITARY INTERESTS:

Custodians
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:
Air Force - 84

Agent Activity:
Air Force - 99

(Project 5210-F287)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:00Z
Check the source to verify that this is the current version before use.