MIL-G-15840C
15 MARCH 1963
SUPERSEDING
MIL-G-15840B
17 APRIL 1957
MIL-G-26777 (USAF)
16 SEPTEMBER 1955
MIL-G-22058 (SHIPS)
AMENDMENT 1
27 OCTOBER 1959

MILITARY SPECIFICATION

GARBAGE DISPOSAL MACHINES, COMMERCIAL AND HOUSEHOLD

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 Scope. This specification covers commercial and household garbage disposal machines for automatic grinding and disposal of food scraps. The machines can be installed in a sink, scrap table, or soiled dish counter.

1.2 Classification. Garbage disposal machines shall be of the following types, classes and capacities, as specified (see 6.2).

Type I — Commercial.

Class 1 — With pre-rinse assembly and tableware trap.

Class 2 — Without pre-rinse assembly and with scrap block.

Capacity — Horsepower (Minimum).

100 pounds per hr — ½
200 pounds per hr — ½
400 pounds per hr — ¾
1,000 pounds per hr — 1¼
1,600 pounds per hr — 3

Type II — Household.

Capacity — Horsepower (Minimum).

50 pounds per hr — ¼
75 pounds per hr — ¼

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-636	— Motors, Fractional Horsepower (Alternating Current).
CC-M-641	— Motor, Alternating Current (Integral Horsepower).
PPP-B-601	— Boxes, Wood, Cleated-Plywood.
PPP-B-621	— Boxes, Wood, Nailed and Lock Corner.

MILITARY

MIL-V-3	— Valves, Fittings and Flanges (Except for Systems Indicated Herein); Packaging.

FSC 4540

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

JAN-P-100 — Packaging and Packing for Overseas Shipment, General Specification.

MIL-P-116 — Preservation, Method of.

MIL-P-15024 — Plates, Identification —Information and Marking for Identification of Electrical, Electronic and Mechanical Equipment.

MIL-M-15071 — Manual, Technical, for Mechanical and Electrical Equipment (Less Electronics).

MIL-H-15424 —Hand Tools, Packaging of.

MIL-P-16298 — Preservation, Packaging, Packing and Marking of Electric Machines having Rotating Parts and Associated Repair Parts.

MIL-E-17555 — Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of.

STANDARDS

FEDERAL

FED-STD 66 — Steel, Chemical Composition and Hardenability.

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 — Marking for Shipment and Storage.

MIL-STD-130 — Identification Marking of U.S. Military Property.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procurement activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

OFFICIAL CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York 16, New York.)

NATIONAL BOARD OF FIRE UNDERWRITERS

National Electrical Code.

(Application for copies should be addressed to the National Board of Fire Underwriters, 85 John Street, New York 7, New York; 222 West Adams Street, Chicago 6, Illinois; Merchants Exchange Building, San Francisco 4, California.)

3. REQUIREMENTS

3.1 Preproduction Model. The preproduction model is defined as a production line model of the product which the manufacturer will subsequently produce in fulfillment of the contract unless otherwise specified in the contract or order, as soon as practicable after award of the contract or order and prior to submission of any complete units for final acceptance, the contractor shall furnish one complete preproduction model for preproduction inspection to determine conformance with this specification (see 4.2). Approval of the preproduction model by the activity concerned shall not relieve the contractor of his obligation to supply equipment conforming to this specification. Any changes or deviations from the preproduction model shall be subjected to the approval of the contracting officer. The approved preproduction model will be used as a guide in the inspection of production machines, and shall be presented as

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

part of the contract after successful testing has been accomplished as specified in 4.5.

3.1.1 When a contractor has been the supplier of identical equipment on a recent contract or order, and the preproduction model was actually tested under Government supervision and met all requirements, examinations and test specified herein, the requirements for test of a preproduction model may be waived by the contracting officer provided full information is furnished regarding the test location, date, and activity concerned.

3.2 **Material.** Material shall be as specified herein. Material not definitely specified shall be of a good commercial quality for this type of equipment.

3.2.1 *Corrosion resisting steel.* The cone-hoppers for type 1 machines, the cover and the tableware trap for type I, class 1 machines, and perforated sleeve for type I, class 2 machines, shall be fabricated of corrosion-resisting steel conforming to the chemical requirements of Federal Standard No. 66, type numbers 201, 202, 302, or 304.

3.3 **Design.** The design of the machine shall be in accordance with the best engineering practice. The machine designed shall permit accessibility for maintenance and service where installed without it being necessary to break electrical or plumbing connections. The machine shall be designed to grind garbage and wash it down the drain. Ground garbage shall not pack or adhere to any parts of the machine when water is flowing. Garbage shall be ground to a finely divided mash or pulp, 100 percent of which shall pass through a number 8 sieve. Sieve shall be U. S. standard sieve series and percentage shall be based on drained weights. The machine shall not jam when operated at full capacity.

3.3.1 *Rotor.* The rotor and all rotating parts shall be accurately balanced to insure a quiet running machine at the required speed.

3.3.2 *Grinding mechanism.* The grinding mechanism shall be alloy steel. Carburizing, cemented carbides and weld-on hard facing alloys may be used. The hardness of the grinding surface shall not be less than 58 nor more than 62 on the Rockwell "C" scale. On other surfaces, the Rockwell "C" scale shall indicate a hardness of not less than 38.

3.3.2.1 *Impeller.* The hardness of the face of the impeller or impellers shall be not less than 38 Rockwell "C" scale.

3.3.2.2 *Cutting ring.* The hardness of the cutting ring shall be not less than 58 nor more than 62 on the Rockwell "C" scale.

3.4 **Construction.** Machines shall be free from objectionable vibration and quiet in operation. All machines shall be provided with means of supporting the unit from the floor. Each machine shall consist essentially of a grinding chamber containing the cutting edges, a rotor or impeller, and the electric driving motor. The grinder chamber shall be designed to prevent garbage or water being thrown back out of the machine.

3.4.1 *Rotation direction.* The designed direction of rotation shall be clearly indicated by means of a circular arrow cast or permanently attached on the grinder housing. Machines which may be operated in either direction need not be marked.

3.4.2 *Shaft seal.* The grinder shaft shall be provided with a positive water seal between the motor and the grinder chamber. The seal shall be protected against the entry of grit or dirt.

3.5 **Bearings.** All bearings for rotating elements shall be permanently lubricated anti-friction type.

3.6 **Discharge.** The discharge outlet of each machine shall be such that it can be connected to standard pipe of not less than 1½ inch size.

3.7 **Flow interlock.** A flow interlock shall be provided with each machine for installation by others.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

3.8 **Garbage feed chute.** A plain cone hopper without side water inlet shall be provided with type I machines. The cone hopper shall be 15 to 18 inches in diameter at the top, with a flange for welding flush with the surface of a sink or table. The flange shall have an outside diameter of not less than one inch greater than the inside of the cone hopper at the top. The cone hopper shall have pitch so as to minimize lodgement of garbage. The bottom of the cone hopper opening shall be round and of the same diameter as the opening in the garbage grinder and shall be flange connected thereto in such a manner that garbage cannot lodge on the flange. Unless otherwise specified in the contract or order type I machines over 400 lbs per hr capacity shall be furnished without cone hopper.

3.9 **Safety.** All rotating parts and parts subject to high temperatures that are of such nature or so located as to become a hazard to operating personnel, shall be insulated, fully enclosed, or properly guarded.

3.10 **Class 1 machines.** The machines shall be equipped with a prerinse assembly. A mixing valve with automatic temperature and volume control which mounts to the grinder or the table shall be provided. A flexible metal encased rubber, synthetic rubber, or plastic (nonwater absorbing and heat resistant hose shall hang vertically from the standpipe (if the pipe has a gooseneck) or shall be connected to a vertical standpipe and supported by a corrosion-resistant, kinkproof spring. The spray shall be controlled by a manually operated valve and by an adjustable means in the spray head. The valve shall have a means of locking in the "on" position. The bottom of the spray head shall be approximately 9 inches from the top of the cone-hopper and shall be in line with the center of the scraphole of the cover.

3.10.1 *Cover.* The machine shall be provided with a corrosion-resisting steel cover, 0.0625 inch in thickness (U. S. Standard gage No. 16), designed to fit over the opening of the cone-hopper. The cover shall prevent garbage from being thrown back by the grinder and shall have a circular, oval, or rectangular opening with an area of not less than 18 square inches, with the shorter side of the rectangle or the short diameter of the oval being not less than 4 inches.

3.10.2 *Tableware trap.* A removable corrosion-resisting steel trap for the proper trapping of tableware and other material other than garbage shall be provided directly below the opening in the cover.

3.11 **Class 2 machines.** The machines without prerinse assembly shall have a cylindrical perforated sleeve fabricated from corrosion-resisting steel 0.0625 or 0.0500 inch in thickness (U. S. Standard gage No. 16 or No. 18). The bottom of the sleeve shall be flared inward around its entire perimeter in such a manner as to provide a positive fit to the bottom inside diameter of the cone-hopper. The sleeve shall have eight to ten ¾ inch holes equally spread around its perimeter or other shaped perforations with equal free area. The diameter at the top of the sleeve shall be such that it will receive a scrap block (see 3.11.1). The height of the sleeve shall be such that, when the scrap block is in place, the top of the scrap block will be approximately ¼ inch below the top of the cone-hopper.

3.11.1 *Scrap block.* A molded rubber, synthetic rubber, or plastic scrap block shall be furnished with each machine. The block shall fit in the perforated sleeve specified in 3.11.

3.12 **Type II.** Household. The machines shall be designed to fit without disassembly a sink with 3½ inch drain opening and shall be suitable for either right or left hand "S" trap or "P" trap waste installation.

3.12.1 *Mounting.* Type II machines having vertically mounted motors shall be designed for mounting and fastening to the sink. Machines having horizontally mounted motors shall be floor-mounted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

3.12.2 Type II machines shall be provided with hopper-opening covers which will also serve as sink-stoppers.

3.12.3 *Wiring connections.* All wiring connections between disposers shall be made prior to shipment.

3.13 Electrical Requirements.

3.13.1 *Motors.* Motors shall be alternating current (ac) or direct current (dc) as specified in the contract or order. They shall conform to the requirements of Specification CC–M–636 or CC–M–641 and shall have the following characteristics:

Ambient temperature	40° C
Enclosure	Dripproof
Duty	Continuous
Horsepower	As necessary for satisfactory operation of machine
Voltage	As specified in the contract or order
Bearings	Ball
Insulation	Class A or B

3.13.2 *Starting controls and wiring.* Starting controls and wiring shall be in accordance with National Electrical Code.

3.13.3 *Motor control.* Machines shall be provided with an across-the-line type magnetic starter with overload and low voltage protection.

3.14 Finishing and Painting. The equipment shall be finished and painted in accordance with the manufacturer's standard practice for this type of equipment.

3.15 Technical Manual. Each machine shall be furnished with a type IV technical manual, in accordance with Specification MIL–M–15071. Information concerning the motor winding data shall be included in the final manual.

3.16 Repair parts and maintenance tools. Required repair parts or maintenance tools shall be as specified in the contract or order as selected from the recommended by the manufacturer to maintain operation on the unit for one year.

3.17 Items to be furnished with machines. No shipment of machines shall be made unless all specified repair parts and maintenance tools are included with the shipment or unless written approval for shipment of the machines without such items has been received from the agency concerned.

3.18 Identification marking. Each machine shall be identified in accordance with Standard MIL–STD–130.

3.19 Instruction plates. Each unit of equipment shall be equipped with instruction plates conforming to Specification MIL–P–15024, type A or B, including warnings and cautions suitably located describing any special or important procedure to be followed operating and servicing the equipment. Plates of phenolic compounds are not acceptable.

3.20 Drawings. The manufacturers' standard commercial outline drawing with parts lists of the equipment shall be provided.

3.21 Workmanship. The workmanship shall be first class in every respect.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

4.2 Preproduction inspection. Unless otherwise specified in the contract or order, examination and testing of the preproduction model will be made at the place of manufacture. The preproduction model shall be examined as specified in 4.4 and tested as specified in 4.5.

4.3 Sampling.

4.3.1 *Lot.* All machines of the same type and capacity offered for delivery at one time shall be considered a lot for purposes of sampling and inspection.

4.3.2 *Sampling for examination.* Sample machines shall be selected at random in accordance with Standard MIL–STD–105 at inspection level III for the examination specified in 4.4. The AQL shall be 1.5 percent defective.

4.3.3 *Sampling for group A tests.* The machines selected in accordance with 4.3.2 (or an equal random sample) shall be selected for the following tests:

a. No-load power input 4.5.1

b. No-load speed (dc motor) 4.5.1

c. Insulation resistance 4.5.2

4.3.4 *Sampling for performance test.* Sample machines shall be selected from each lot in accordance with inspection level L–5 of the appendix to Standard MIL–STD–105 for the test specified in 4.5.3. If any machine fails in the performance test, four additional machines shall be subjected to the same test. All machines shall be tested for the defect which causes failure.

4.4 Examination. The machines shall be examined for conformance to all of the requirements of this specification which do not involve tests.

4.5 Test procedures.

4.5.1 *No-load test.* Prior to shipment, each machine shall be operated in accordance with standard commercial test procedures to insure that all parts are properly assembled and in satisfactory working condition.

4.5.2 *Insulation resistance.* The insulation resistance of each motor and controller and connecting cable shall be measured by an approved instrument. Any machine showing a low value shall be rejected.

4.5.3 *Performance test.* When testing of a preproduction sample is stipulated (see 6.2), the machine shall be operated to verify compliance with the requirements of this specification. The duration of the test and the total weight of the solids handled shall be as specified in the ordering data (see 6.2). The composition of the test specimens shall be as specified in 4.5.3.1.

4.5.3.1 *Test specimens.* The test specimen shall consist of the following mixture (percentages based on drained weight):

20 percent uncooked beef or pork bones (not over 1½ inches in diameter or width).
20 percent uncooked poultry bones.
15 percent grapefruit rinds cut in half and inserted in such a manner that they could float.
40 percent raw vegetables and trimmings including lettuce, cabbage leaves, turnip tops, carrot tops, celery stalks, onion skins, and so forth.
5 percent paper and cellophane, including milk cartons (8-ounce size).

4.5.3.2 *Fineness test.* The ground garbage resulting from the full capacity test run specified in 4.5.3.1 shall be screened to determine its fineness conformance to the requirements of 3.3. Ground garbage may be washed through the sieves, but care shall be exercised to refrain from forcing the particles through the perforations with excess pressure.

4.6 Inspection of preparation for delivery. Sample machines and packages shall be selected and inspected in accordance with Specification MIL–P–116 to verify conformance to the requirements of section 5 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B or C as specified.

5.1.1 *Level A.*

5.1.1.1 *Machines.* Each complete machine shall be preserved in accordance with Specification MIL–P–116, Method IA, submethod as applicable. The breaking, pulverizing, and expelling section of the machine shall be coated with type P–3 preservative.

5.1.1.2 *Repair parts, tools, and accessories.* The repair parts, tools, and accessories shall be preserved and packaged in accordance with Specification MIL–V–3, MIL–P–116, MIL–H–15424, MIL–P–16298, and MIL–E–17555, as applicable.

5.1.1.3 *Technical publications.* The technical publications shall be preserved in accordance with Specification MIL–P–116, Method IC-1.

5.1.2 *Level B.*

5.1.2.1 *Machines.* Each complete machine shall be preserved in accordance with Specification MIL–P–116, method III.

5.1.2.2 *Repair parts, tools, accessories, and technical publications.* The repair parts, tools, accessories, and technical publications shall be preserved and packaged as specified for Level A.

5.1.3 *Level C.* Machines shall be preserved and packaged in accordance with the manufacturer's commercial practice.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 *Level A.* Each complete machine with repair parts, tools, accessories, and technical publications shall be packed in a nailed, wood, or wood-cleated plywood boxes conforming to Specification PPP–B–621 (class 2) or PPP–B–601 (overseas type) respectively, at the option of the contractor. Boxes shall be closed and strapped in accordance with the applicable box specification.

5.2.2 *Level B.* Machines packaged as specified shall be individually packed in nailed, wood or wood-cleated plywood boxes conforming to Specification PPP–B–621 (class 1) or PPP–B–60 (domestic type) respectively, at the option of the contractor. Box closure shall be as specified in the applicable box specification.

5.2.3 *Level C.* Machines, repair parts, tools, accessories, and technical publications shall be packed in a manner which will insure acceptance by common carrier and safe delivery at destination Shipping containers shall comply to the uniform freight classification rules or other regulations as applicable to the mode of transportation.

5.3 Anchoring, blocking and cushioning shall be in accordance with Specification JAN–P–100.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Standard MIL–STD–129.

6. NOTES

6.1 Intended use. The machines are intended for shredding food waste into fine particles which are washed into a drain pipe.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.

(b) Type, class and capacity required (see 1.2).

(c) Whether a preproduction model is not required (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

(d) Voltage, current ac or dc, number of phrases and frequency if other than as specified in 3.13.1.

(e) Technical publication required (see 3.15).

(f) Applicable list of spare parts and maintenance tools required (see 3.16).

(g) Where preproduction model will be examined and tested if elsewhere than as indicated in 4.2.

(h) Selection of applicable levels of preservation, packaging and packing required (see 5.1 and 5.2).

(1) Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it is determined that the machines will be held in covered storage for approximately 1 year from date of initial preservation and packaging or the machines are destined for controlled humidity storage.

Notice. When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodians:

Army—CE
Navy—Docks
Air Force—MOA

Preparing activity:

Air Force—MOA
Project No. 4540–0005

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

FOLD

ASD (ASNXS)
WRIGHT-PATTERSON AFB, OHIO

POSTAGE AND FEES PAID

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

Commander
Aeronautical Systems Division
ATTN: ASNXS
Wright-Patterson AFB, Ohio

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET	Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use of the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION
MIL-G-15840C, Garbage Disposal Machines, Household and Commercial

ORGANIZATION	CITY AND STATE
MOAMA	Mobile, Alabama

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A
☐ Direct Government Contract ☐ Subcontract

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD Form 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:05Z
Check the source to verify that this is the current version before use.