[INCH-POUND]
A-A-55571/7C
October 17, 2007
SUPERSEDING
A-A-55571/7B
January 9, 2006

COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

CIRCUIT BREAKER, 28 VOLTS (V) DC, AUTOMATIC RESET, NONWATERPROOF, 35 AMPERES (A) TO 150 A

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring the circuit breakers described herein shall consist of this document and the issue in effect of CID A-A-55571.

CLASSIFICATION/PART OR IDENTIFICATION NUMBER (PIN). This commercial item description CID specification sheet uses a classification system which is included in the PIN as shown in the following example (see NOTES).

AA55571	/07	-	001
CID number	Applicable CID specification sheet (two digits)		Dash number

SALIENT CHARACTERISTICS.


Interface and physical dimensions. Circuit breakers supplied to this CID specification sheet shall be as specified herein (see figure 1).

Ampere rating. The ampere rating shall be as specified in table I.

Voltage rating. The voltage rating shall be 28 V dc maximum.

Endurance. The minimum expected cycling life shall be 2,000 cycles at 200 percent of rated current.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:54Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.005	0.13	1.06	26.92
.015	0.38	1.203	30.56
.027	0.68	1.25	31.75
.250	6.35	1.58	40.13
.500	12.70	1.88	47.75
.531	13.49	2.406	61.11
.940	23.88	3.16	80.26

NOTES:

1. Dimensions are in inches.
2. Tolerance is ±.005 inch (0.13 mm), unless otherwise specified.

FIGURE 1. Configuration and dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:54Z
Check the source to verify that this is the current version before use.

TABLE I. Characteristics.

CID dash number AA55571/07-	Ampere rating	CID dash number AA55571/07-	Ampere rating
001	35	007	80
002	40	008	90
003	45	009	105
004	50	010	120
005	60	011	135
006	70	012	150

Speed of operation at 25°C (77°F) at 200 percent rated current. Circuit breakers supplied to this CID specification sheet shall meet the minimum and maximum opening time requirements as specified in table II.

TABLE II. Speed of operation at 77°F (25°C).

200 percent of rated current	Opening time in seconds	
	Maximum	Maximum
	8	100

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See classification information for PIN format example.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

MFR's CAGE	MFR's name and address
4G0W8	Sensata Technologies, Incorporated Precision Products Division P.O. Box 2964 Attleboro, MA 02703-0964 Phone number (508) 236-3528 Facsimile number (508) 236-1598 E-mail: mailto:customerservice@sensata.com Uniform Resource Locator (URL): http://www.sensata.com

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:54Z
Check the source to verify that this is the current version before use.

Part number (P/N) supersession data. These CID specification sheet PINs supersede the following MFR's P/N's as shown. This information is being provided to assist in reducing proliferation in the Government inventory system.

TABLE III. P/N supersession data.

Dash number (see table I) AA55571/07-	MFR's CAGE 82647 MFR's P/N 1/	CID dash number (se table I) AA55571/07-	MFR's CAGE 82647 MFR's P/N 1/
001	PDLA-35	007	PDLA-80
002	PDLA-40	008	PDLA-90
003	PDLA-45	009	PDLA-105
004	PDLA-50	010	PDLA-120
005	PDLA-60	011	PDLA-135
006	PDLA-70	012	PDLA-150

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID P/N shown. For actual part marking requirements, see the marking paragraph of A-A-55571.

National stock number (NSN). The following is a list of NSN's assigned which correspond to this CID specification sheet. The list is for information only and may not be indicative of all possible NSN's associated with the CID specification sheet. For up to date information on assigned NSN's, please contact the aforementioned DSCC office listed in A-A-55571.

TABLE IV. NSN's.

Dash number (see table I) AA55571/07-	NSN	Dash number (see table I) AA55571/07-	NSN
001	5925-01-265-7692	007	5925-01-430-4757
002	5925-00-420-8561	008	5925-01-092-9694
003	5925-00-520-4666	009	5925-00-295-5460
004	5925-00-708-8769	010	5925-00-709-9437
005	5925-00-247-2076	011	5925-00-173-7634
006	5925-00-350-4480	012	5925-01-429-4554

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:54Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Navy - EC
DLA - CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

DLA-CC

Project 5925-2007-024

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:54Z
Check the source to verify that this is the current version before use.