INCH-POUND

MIL-M-28787/116A
AMENDMENT 2
31 December 1992
SUPERSEDING
AMENDMENT 1
14 November 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE BDC

This amendment forms a part of Military Specification MIL-M-28787/116A(EC), dated 18 February 1982, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 3

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through R shall be performed in any order with the following exceptions. Test conditions A, B, C, D1, and G are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D1, or G are part of a sequence of tests, the order of testing shall be as follows: D1, A, B, C, and G where applicable, followed by the remaining tests in the sequence."

*4.5.1, line 5: Delete "E through J" and substitute "E, F, H, J".

*4.5.3, line 3: Delete "E through J" and substitute "E, F, H, J".

*4.5.3, line 5: Delete "E through R" and substitute "E, F, and H through R".

6.3: Delete and substitute the following:

"6.3 Cross reference of classification. Military Specification MIL-M-28787/116 supersedes Department of the Navy, Naval Ordnance Systems Command Drawing No. 10001-2658636. Part number M28787/116-1 supersedes part numbers 2658636 and M28787/116."

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:06Z
Check the source to verify that this is the current version before use.

PAGE 5

*TABLE I, Test conditions G1-G4, Test type column: Delete "X" and substitute "S".

PAGE 14

FIGURE 5: Delete and substitute new figure 5 as printed on page 3 of this amendment.

PAGE 18

FIGURE 7: Delete and substitute new figure 7 as printed on page 4 of this amendment.

PAGE 24

FIGURE 9: Delete and substitute new figure 9 as printed on page 5 of this amendment.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.


Custodians:
Army - ER
Navy - SH
Air Force - 85

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Preparing activity:
Navy - NW

(Project 5963-0130)


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:06Z
Check the source to verify that this is the current version before use.



CAUTION: If these tests are successively repeated, a time interval of 10 seconds minimum between tests shall be allowed to preclude detrimental effects due to module heating.

FIGURE 5 Zener applied potential test circuit for table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:06Z
Check the source to verify that this is the current version before use.




CAUTION: If these tests are successively repeated, the time interval between execution should be a minimum of 10 seconds in order to preclude detrimental effects due to module heating.

NOTES: 1. R1 = 261 Ω ± 1%, 1/2 W.
2. After point A has been connected to the appropriate module pin, the output shall be monitored for a minimum of 10 seconds before taking the measurement

FIGURE 7 VOUT (low loaded) test circuit for table IV

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:06Z
Check the source to verify that this is the current version before use.



NOTES:
1. R1 = 127 Ω ± 1%, 1/8 W.
2. R2 = 348 Ω ± 1%, 1/8 W.
3. R3 = 61.9 kΩ ± 1%, 1/8 W.
4. Use appropriate VIN for specified test condition and temperature listed below:

Test condition	Temperature (°C)	VIN (volts)
E1-E32	0	1.20
	25	1.10
	60	0.95
	80	0.80
F1-F4	0	2.0
	25	1.9
	60	1.8
	80	1.8

0°, 60°, and 80°C refer to operating temperatures (module frame); 25°C refers to ambient temperature. For 80°C use the 0° to 60°C end-of-life limits

FIGURE 9. Output voltage (high-level and low-level) test circuit for table VI.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:06Z
Check the source to verify that this is the current version before use.