INCH-POUND

MIL-M-28787/118B(SH)
AMENDMENT 1
19 June 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIVIBRATOR, MONOSTABLE, DIGITAL, KEY CODE BDE

This amendment forms a part of Military Specification MIL-M-28787/118B(EC), dated 31 August 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 4

TABLE I, Test conditions B1, B2, Test type column Delete "X" and substitute "S"

TABLE I, Test conditions D1-D4, Test type column Delete "X" and substitute "S"

PAGE 6

TABLE I, Test type column Delete "1/,2/" and substitute "1/,3/"

TABLE I, Test conditions N1-N12, Test type column Delete "S" and substitute "Q"

TABLE I: Add a new footnote 3/ as follows "3/ "Q" parameters shall be tested during qualification testing only."

PAGE 7

4 4 2 Delete and substitute the following

"4.4.2 Order of testing. Test conditions A through Q shall be performed in any order with the following exceptions Test conditions B, D, P and Q are stress tests and shall be performed only at 25 ± 5°C. If test conditions B, D, P and Q are part of a sequence of tests, the order of testing shall be as follows. B, D, P and Q where applicable, followed by the remaining tests in the sequence "

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:07Z
Check the source to verify that this is the current version before use.

4.5.1, fifth and sixth lines: Delete "A, C through F16, F29 through F36, F53 through F56, G5, G7, H2, H6, L1 through L4 and M" and substitute "A, C and E through M".

4.5.3, third line Delete "A through Q" and substitute "A, C and E through M"

4.5.3, sixth line Delete "A through N" and substitute "A, C and E through M"

PAGE 20

FIGURE 8, NOTE 2, last line Delete "PRP = 40ns ± 10%." and substitute "PRP = 40µs ± 10% "

PAGE 36

FIGURE 12, NOTE 4b Delete "(1 5V level)" and substitute "(1.6V level)"

FIGURE 12, NOTE 5b Delete "(1 5V level)" and substitute "(2 5V level)"

FIGURE 12, NOTE 6b Delete "(1.5V level)" and substitute "(0 475V level)".

Preparing activity:
Navy - SH

(Project 5963-N818)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:07Z
Check the source to verify that this is the current version before use.