INCH-POUND

MIL-M-28787/121B(SH)
AMENDMENT 1
8 March 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIVIBRATOR, MONOSTABLE, DIGITAL, KEY CODE CDD

This amendment forms a part of Military Specification MIL-M-28787/121B (EC), dated 7 September 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

TABLE I, Test conditions P1-P12, Test type column Delete "S" and substitute "Q"

PAGE 7

4 4.2· Delete and substitute the following

"4 4.2 Order of testing Test conditions A through R shall be performed in any order with the following exceptions Test conditions B, Q and R are stress tests and shall be performed only at 25 ± 5°C If test conditions B, Q or R are part of a sequence of tests, the order of testing shall be as follows B, Q and R where applicable, followed by the remaining tests in the sequence "

4.5 3, sixth line Delete "A through P" and substitute "A and C through N".

PAGE 8

6.4· Add "Propagation delay time 170 ns".

6 4· Delete and substitute the following·

Input current	
Low level	3 2 mA maximum

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:08Z
Check the source to verify that this is the current version before use.

FIGURE 10, delete "3 0V ± 5%E " (two places) and substitute "3.2V ± 5%" (two places)

FIGURE 10, delete "1.2V ± 5%E" (two places) and substitute "1.5 ± 5%" (two places)

FIGURE 10, delete "1 0V ± 5%E" (two places) and substitute "1.2V ± 5%" (two places)

FIGURE 10, Q and $\overline{Q}$ output pulses, delete the "E" reference (two places)

Add Note 1 as follows: Note 1. Voltage levels are referenced to "O V REF"

Preparing activity
Navy - SH

(Project 5963-N752)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:08Z
Check the source to verify that this is the current version before use.