INCH-POUND

MIL-M-28787/122B(SH)
AMENDMENT 2
7 June 1991
SUPERSEDING
AMENDMENT 1
17 June 1986

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIVIBRATOR, MONOSTABLE, DIGITAL, KEY CODE CDE

This amendment forms a part of Military Specification MIL-M-28787/122B (EC), dated 31 August 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense

PAGE 4

* TABLE I: Delete and substitute new table I as printed on page 2 of this amendment.

PAGE 7

* 4 4 2 Delete and substitute the following

"4 4.2 Order of testing Test conditions A through R shall be performed in any order with the following exceptions Test conditions B, D1-D4, Q, and R are stress tests and shall be performed only at 25 ± 5°C If test conditions B, D1-D4, Q, or R are part of a sequence of tests, the order of testing shall be as follows B, D1-D4, Q, and R where applicable, followed by the remaining tests in the sequence "

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.

TABLE I Module electrical requirements

Test condition	Parameter	Ref test table	Test type 1/-2/	Acceptance requirements 25 ± 5°C ambient temperature				Operating temperature 0° to 60°C				Unit
				Initial		End-of-life		Initial		End-of-life		
				Min	Max	Min	Max	Min	Max	Min	Max	
A1-A7	Continuity	II	X	0	1	0	1	0	1	0	1	Ω
A8	Continuity	II	S	0	1	0	1	0	1	0	1	Ω
B1	Isolation, frame	II	S	10	∞	10	∞	10	∞	10	∞	MΩ
B2	Isolation, used to unused	II	X	10	∞	10	∞	10	∞	10	∞	MΩ
C1,C4, C5,C8	Output voltage, low level	III	X	0 0	0 4	0 00	0 45	0.0	0 4	0 00	0.45	V
C2, C3, C6, C7	Output voltage, high level	III	X	3 8	5 5	3 5	5.5	3 8	5 5	3 5	5.5	V
D1-D4	Output short circuit current	IV	S	16	65	16	65	16	65	16	65	mA
D5,D7	Input current, high level	IV	X	0	4	0	8	0	6	0	10	uA
D6,D8	Input current, low level	IV	X	0 0	3 2	0 0	3 2	0 0	3 2	0 0	3.2	mA
E1	Power supply current (quiescent)	V	S	0	120	0	120	0	120	0	120	mA
E2	Power supply current (operating)	V	S	0	120	0	120	0	120	0	120	mA
F1-F4	Output pulse width (1,000 uS)	VI	X	930	1,070	910	1,090	900	1,100	880	1,120	uS
F5-F8	Output pulse width (200 uS)	VI	X	186	214	182	218	180	220	176	224	uS
F9-F12	Output pulse width (300 uS)	VI	S	279	321	273	327	270	330	264	336	uS
F13-F16	Output pulse width (400 uS)	VI	X	372	428	364	436	360	440	352	448	uS

See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.

* 4 5 1 Delete and substitute the following

"4.5 1 Operating temperature tests The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through R in table I shall be performed in the order specified in 4.4 2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions A, C, D5-D8, and E through P shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

* 4.5.3 Delete and substitute the following

"4 5 3 Life test The life test shall be conducted in accordance with MIL-M-28787 The module shall be operated as shown on figure 2 Following the life test and while still at the maximum class temperature, electrical tests A, C, D5-D8, and E through P shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I Following the return of the module to 25 ± 5°C, electrical tests A, C, D5-D8, and E through P shall be performed in the order specified in 4 4.2 using the 25 ± 5°C ambient end-of-life requirements in table I "

NOTE The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

Preparing activity.
Navy - SH

(Project 5963-N753)

Agent NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.