MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

FLIP-FLOP, JK, DIGITAL, KEY CODE ADH

This amendment forms a part of Military Specification MIL-M-28787/123A(EC), dated 22 June 1982, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I: Delete and substitute new table I as printed on page 2 of this amendment.

PAGE 23

TABLE V: Delete and substitute new table V as printed on page 3 of this amendment.

PAGE 63

TABLE XIX: Delete and substitute new table XIX as printed on page 4 of this amendment.

PAGE 64

FIGURE 27, ITEM D05: Add "E" next to the arrow on the line from CHAN A of ITEM D05.

FIGURE 27, NOTE 5, second line: Delete "item V03" and substitute "item M02".

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N430)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	Acceptance requirements 25°±5°C ambient temperature				Operating temperature 0° to 60°C				Unit
				Initial		End-of-life		Initial		End-of-life		
				Min	Max	Min	Max	Min	Max	Min	Max	
A1-A25	Zener applied potential, cond A	III	S	3.8	5.5	3.5	5.5	3.8	5.5	3.5	5.5	V
B1-B5	Zener applied potential, cond B	III	S	3.8	5.5	3.5	5.5	3.8	5.5	3.5	5.5	V
C1-C10	V_{OUT} (low loaded)	IV	S	0.0	1.1	0.0	1.1	0.0	1.1	0.0	1.1	V
D	Isolation	V	S	10	∞	1	∞	10	∞	1	∞	MΩ
E	Resistance	V	X	4	5	4	5	4	5	4	5	kΩ
F1	Continuity	V	X	0	1	0	1	0	1	0	1	Ω
F2	Continuity	V	S	0	1	0	1	0	1	0	1	Ω
G1-G5	Input current, reverse clock	VI	X	0	4	0	8	0	6	0	10	μA
H1-H10	Input reverse current, synchronous	VII	X	0	2	0	4	0	3	0	5	μA
J1-J10	Input reverse current, asynchronous	VII	X	0	4	0	8	0	6	0	10	μA
K1-K10	Input forward current	VIII	X	0.20	1.07	0.20	1.07	0.20	1.07	0.20	1.07	mA
L1-L10	Input forward current	VIII	X	0.2	3.2	0.2	3.2	0.2	3.2	0.2	3.2	mA
M1-M10	Input forward current	VIII	X	0.2	3.2	0.2	3.2	0.2	3.2	0.2	3.2	mA

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.

TABLE V. Isolation, resistance, and continuity test.

Test condition	Parameter	Connect				Initial limits 25°±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	Min	Max		
D	Isolation	11	All other pins	Open	Open	10	∞	MΩ	9
E	Resistance	Open	Open	1	32	4	5	kΩ	
F1	Continuity	Open	Open	10	30	0	1	Ω	
F2	Continuity	Open	Open	11	Frame	0	1	Ω	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.

TABLE XIX. Transient immunity (J and K) and minimum pulse sensitivity (J-K) test.

Test condition	Parameter	Connect					Initial limits 25° ±5°C ambient		Unit	Test figure
		A to pin	B to pin	C to pin	D to pin	E to pin	Min	Max		
GG1	1K Transient immunity, J and K	7	4	3	2	Open	0.00	0.40	V	27,28
GG2	2K	19	16	15	14					
GG3	3K	22	25	26	27					
GG4	4K	29	9	28	12					
GG5	5K	35	38	39	40					
GG6	1J	7	8	5	6					
GG7	2J	19	20	17	18					
GG8	3J	22	21	24	23					
GG9	4J	29	31	13	33					
GG10	5J	35	34	37	36					
HH1	1J-1K Minimum pulse sensitivity, J-K	7	8,4	Open	Open	3	1.6	2.4	µs	27,29
HH2	2J-2K	19	20,16			15				
HH3	3J-3K	22	21,25			26				
HH4	4J-4K	29	31, 9			28				
HH5	5J-5K	35	34,38			39				

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:09Z
Check the source to verify that this is the current version before use.