[INCH-POUND]
A-A-59442
22 June 1999
SUPERSEDING
MS35917C
21 March 1975

COMMERCIAL ITEM DESCRIPTION

ELBOWS, TUBE, 90 AND 45 DEGREE, SOLDER-JOINT, REFRIGERATION

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

1. SCOPE. This commercial item description (CID) covers wrought copper and copper alloy solder joint pressure fittings for use with copper water tubes in refrigeration systems.

2. SALIENT CHARACTERISTICS.

2.1 Material and Finish. Fitting material and finishes shall be copper and copper alloy, as specified in ASME/ANSI B16.22.

2.2 Design, Construction, and Performance. Fitting design, construction, and performance shall be in accordance with ASME/ANSI B16.22.

3. REGULATORY REQUIREMENTS.

3.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. QUALITY ASSURANCE PROVISIONS.

4.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5. PACKAGING.

5.1 Preservation, Packing, and Marking. Preservation, packing, and marking shall be as specified in the contract or order.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, Defense Supply Center, Columbus, DSCC-VAI, 3990 East Broad Street, Columbus, OH 43216-5000.

AMSC N/A FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

6. NOTES.

6.1 Part Identification Number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor. Figure 1, Figure 2 and Table 1 are provided for configuration identification.



Figure 1. 90 Degree Elbow



Figure 2. 45 Degree Elbow

TABLE I. Dash Nos.

Dash No.		Std. Refrig. Tube Size, inches
90 Degree Elbow Figure 1	45 Degree Elbow Figure 2	
-2	-2U	1/4
-3	-3U	3/8
-4	-4U	1/2
-5	-5U	5/8
-6	-6U	3/4
-7	-7U	7/8
-9	-9U	1 1/8
-11	-11U	1 3/8
-13	-13U	1 5/8
-17	-17U	2 1/8
-21	-21U	2 5/8
-25	-25U	3 1/8
-29	-29U	3 5/8
-33	-33U	4 1/8

The part number consists of the document identifier and a dash no. (see Table 1). The dash number denotes size in increments of 1/8 inch.

Example: Part Identifying Number “AA59442-2U”:

AA59442 -2U

Dash No. (2U = 45 Degree Elbow, 1/4 inch tube size)
Document Identifier

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

6.2 Cross Reference Data.

MS35917		Tube Size, inches	AA59442	
MS35917-2	MS35917-2U	1/4	AA59442-2	AA59442-2U
MS35917-3	MS35917-3U	3/8	AA59442-3	AA59442-3U
MS35917-4	MS35917-4U	1/2	AA59442-4	AA59442-4U
MS35917-5	MS35917-5U	5/8	AA59442 5	AA59442 5U
MS35917-6	MS35917-6U	3/4	AA59442-6	AA59442-6U
MS35917-7	MS35917-7U	7/8	AA59442-7	AA59442-7U
MS35917-9	MS35917-9U	1 1/8	AA59442-9	AA59442-9U
MS35917-11	MS35917-11U	1 3/8	AA59442-11	AA59442-11U
MS35917-13	MS35917-13U	1 5/8	AA59442-13	AA59442-13U
MS35917-17	MS35917-17U	2 1/8	AA59442-17	AA59442-17U
MS35917-21	MS35917-21U	2 5/8	AA59442-21	AA59442-21U
MS35917-25	MS35917-25U	3 1/8	AA59442-25	AA59442-25U
MS35917-29	MS35917-29U	3 5/8	AA59442-29	AA59442-29U
MS35917-33	MS35917-33U	4 1/8	AA59442-33	AA59442-33U

6.3 National Stock Numbers (NSNs). The following is a list of identified NSNs assigned that correspond to this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	Size	NSN	Size
4730-00-100-2841	-6U	4730-00-254-6424	-6
4730-00-254-6444	-25	4730-00-254-6445	-11
4730-00-254-6447	-7	4730-00-254-6448	-9
4730-00-254-6450	-5	4730-00-254-6449	-4
4730-00-254-6460	-9U	4730-00-254-6462	-4U
4730-00-776-1048	-5U	4730-00-813-4440	-2U
4730-00-813-4441	-3U	4730-00-813-4447	-11U
4730-00-818-5185	-21	4730-00-837-0685	-3
4730-01-303-1226	-2	4730-00-254-6459	-7U

6.4 Sources of Documents.

6.4.1 Copies of ASME/ANSI B16.22 “Wrought Copper and Copper Alloy Solder Joint Pressure Fittings” are available from the American Society of Mechanical Engineers, 3 Park Avenue, New York, NY, 10016-5990.

6.4.2 The Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.

6.5 Ordering Data. Acquisition documents must specify the following

a. Title, number, and date of this commercial item description.
b. Part identification number.
c. Preservation and packing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.

A-A-59442

MILITARY INTERESTS:

Custodians:
Air Force - 99
Army - GL4
Navy - SH
DLA - CC

Review activities:
Army - CE, MD1
Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:
GSA/FSS - 7FXE

Preparing activity:
DLA - CC

(Project 4730-0947-001)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:14Z
Check the source to verify that this is the current version before use.