MIL-A-15344J(NAVY)
AMENDMENT - 1
18 September 1963

MILITARY SPECIFICATION

AMPLIFIER, SYNCHRO SIGNAL

This amendment forms a part of Military Specification MIL-A-15344J(NAVY) and has been concurred in by all interested bureaus of the Department of the Navy.

Page 4, paragraph 3.7.2, last line: Delete "or 7".

Pages 6 and 7, paragraph 3.7.15, seventh sentence: Delete and substitute: "A single dial index shall be used. Either the dial index shall permit adjustment of approximately 3 degrees in either direction, or the dial shall permit such adjustment."

Page 7, paragraph 3.8.2, last sentence: Delete and substitute: "When specified (see 6.2), a different complement of output synchros made up from those specified in 3.8.1, but limited to the following guidelines, shall be supplied in production synchro amplifiers in lieu of the complement specified in 1.2:

(a) No more than two 60-cycle synchros and no more than two 400-cycle synchros shall be installed in any one synchro amplifier.
(b) Only synchro transmitters or synchro differential transmitters, not both, shall comprise the output synchro complement of any one synchro amplifier."

Page 7, table V, columns headed "7G" and "7DG": Delete.

Page 10, paragraph 4.7.1.1, line 3: Delete "type 5CT" and substitute "synchro"; lines 4, 6, 7, 9, 12, and 15 delete "5CT"; line 22 delete "5CT" and substitute "60-cycle control transformer".

Page 10, paragraph 4.7.1.1.1, line 4: Delete "5CT".

Page 10, paragraph 4.7.1.1.2, line 10: Delete "5CT".

Page 11, table VIII, column 2 for types E and F: Delete "7G" and substitute "6G"; column 6 for types E and F: Delete "14-37TR6" and substitute "9-37TR6".

Preparing activity:
Navy - Ships
(Project 5990-N005(NAVY))

FSC 5990

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:06Z
Check the source to verify that this is the current version before use.