
INCH-POUND
MIL-DTL-15291/12E
21 August 2026
SUPERSEDING
MIL-DTL-15291/12D
21 January 2022

DETAIL SPECIFICATION SHEET

SWITCHES, ROTARY, SNAP ACTION CLASS 20SR FRONT MOUNTED, SIDE CONNECTED

This specification is approved for use by all Departments and Agencies of the Department of Defense.


The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-DTL-15291.



NOTES
1. Dimensions are in inches.
2. Unless otherwise specified, tolerance is plus or minus 0.015.

FIGURE 1 Class 20SR switch

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.



PIN M15291/12-100

FIGURE 2 Handle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.

TABLE I. Type and switching characteristics.

M15291/11 DASH NO. TYPE DESIGNATION	DETAIL REF / TORQUE IN-LBS	DIM "X" / DIM "Y"	HANDLE OR SHAFT POSITION	CIRCUIT AND SPACER CONFIGURATION ROTOR POSITION, SPACER LOCATIONS, TERMINAL MARKING AND LOCATIONS									NOTES
				NO 1	NO 2	NO 3	NO 4	NO 5	NO 6	NO 7	NO 8	NO 9	
-001 20SR2A2	FIG 1 72	4.812 .437	OFF ON 1 ON 2 OFF		1 2	3 4							
-002 20SR3A2	FIG 1 72	5.687 .437	OFF ON 1 ON 2 OFF		1 2	3 4	5 6						
-003 20SR2B2	FIG 1 72	6.562 .437	OFF ON 2 ON 1 OFF		1 3	2 3	4 4	5 6					
-004 20SR3B2	FIG 1 72	8.312 .437	OFF ON 2 ON 1 OFF		1 3	2 3	4 4	5 6	7 7	8 9			
-005 20SR2E2	FIG 1 72	6.562 .437	OFF ON 3 ON 1 ON 2		1 4	2 3	7 7	5 8					
-006 20SR3E2	FIG 1 72	8.312 .437	OFF ON 3 ON 1 ON 2		1 4	2 3	5 8	6 7	9 9	10 12 11			
-007 20SR4F2	FIG 1 72	7.437 .437	1&2 1 2 OFF			1 2	4 3	5 6	8 7				
-008 20SR6F2	FIG 1 80	9.187 .437	1&2 1 2 OFF			1 2	4 3	5 6	8 7	9 10	12 11		
-009 20SR2S2	FIG 1 72	4.812 .312	ON 1 OFF ON 2 OFF		B1 L1 A1	A2 L2 B2							
-010 20SR3S2	FIG 1 72	5.687 .312	ON 1 OFF ON 2 OFF		B1 L1 A1	A2 L2 B2	B3 L3 A3						

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Applicable specification: MIL-DTL-15291

Dimensions and mounting: See figure 1

Switching characteristics: See table I

Angle of throw: 90 degrees

Switching action: Snap action, reciprocating

Electrical and endurance ratings: See table II

Stop strength (applicable to switches with stops): 100 inch-pounds

Vibration: 50 Hz, MIL-STD-167-1

Shock (high impact): High impact, MIL-DTL-901

Contact resistance: 1.5 milliohms maximum

Dielectric withstanding voltage: 2,000 Vrms

Insulation resistance: 200 megohms minimum

Mounting bolts: (4) ½ diameter, length, and headstyle to suit application. Bolts not furnished.

TABLE II Electrical and endurance ratings.

Tests	Current (amperes)	Voltage (volts)	Electrical Operations (number of operations)	Test rate (operations per minute)	De-energized operations (number of operations)
Alternating current (rms)	200	500	6,000	8	4,000
Direct current	200	250	4,000	3	--

Terminal marking: Terminal markings shown in table I locate terminals as viewed from the front of the switch (handle end) Markings shall be stamped in rear surfaces of terminals.

GENERAL INFORMATION:

Switches not covered by Specification sheets: Switches which are fabricated from standard parts, as used in qualified switches, but which do not comply with switches detailed herein with respect to circuit characteristics, switching action, mounting arrangement, and handle details may be acquired under this specification from contractors having qualification approval under this specification.

Extended ratings: Switches detailed herein have been tested and found satisfactory at the extended ratings listed in table III. Reduced life expectancy must be anticipated for switches used at these increased voltage or current levels. Tests under the conditions of table III are not required for qualification acceptance and they are not repeated routinely as for maintenance of qualification. Supplemental evaluations and tests applicable to particular circuit requirements are recommended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.

TABLE III. Extended ratings.

Switching characteristics	AC 60 or 400 Hz											
	125 volts				250 volts				500 volts			
	Resistive or lamp load		Inductive load 0.75 p.f.		Resistive or lamp load		Inductive load 0.75 p.f.		Resistive or lamp load		Inductive load 0.75 p.f.	
	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations
All	200	6,000	200	6,000	200	6,000	200	6,000	200	6,000	200	6,000
	DC											
	120 volts				250 volts				350 volts			
	Resistive or Lamp load		Inductive load[1]		Resistive or Lamp load		Inductive load[1]		Resistive or Lamp load		Inductive load[1]	
	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations	Amp.	Operations
All	200	4,000	--	--	200	4,000	200	4,000	--	--	--	--

[1]0.025 henry for inductive circuit

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.

APPLICATION AND ACQUISITION GUIDE: PIN and type designation cross reference shall be as shown in table IV

TABLE IV. Application and acquisition guide.

M15291/12 Dash No.	Type Designation	For new or Existing design	For replacement	Circuit Configuration
-001	20SR2A2	X		A (off-on-off-on)
-002	20SR3A2	X		A (off-on-off-on)
-003	20SR2B2	X		B (off-on-1-off-on 2)
-004	20SR3B2	X		B (off-on-1-off-on 2)
-005	20SR2E2	X		E (off-on-1-on 2-on 3)
-006	20SR3E2	X		E (off-on-1-on 2-on 3)
-007	20SR4F2	X		F (off-on 1-on 1 & 2-on 2)
-008	20SR6F2	X		F (off-on 1-on 1 & 2-on 2)
-009	20SR2S2	X		S (on 1-on 2-off-off)
-010	20SR3S2	X		S (on 1-on 2-off-off)

Referenced Documents:
- MIL-DTL-15291
- MIL-DTL-901
- MIL-STD-167-1

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Navy - SH
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2026-063)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:01Z
Check the source to verify that this is the current version before use.