| INCH-POUND |

MIL-S-15297H
30 April 1993
SUPERSEDING
MIL-S-15297G
9 December 1971

MILITARY SPECIFICATION

SPRAY OUTFITS, PAINT, PORTABLE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of portable paint spray outfits.

1.2 Classification. The paint spray outfits shall be of the following types, as specified (see 6.2):

Type A - Standard.
Type B - Lightweight.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, 621 Pleasant Valley Road, Port Hueneme, CA 93043-4300, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-C-3925 - Compressors, Reciprocating, Rotary and Diaphragm Power Driven, Air, (Paint Spray Type).
MIL-S-12928 - Separators, Oil and Water, Compressed Air.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents which are current on the date of the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

B1.1 - Screw Threads (UN and UNR Thread Form) Unified Inch.
B40.1 - Gauges - Pressure Indicating Dial Type - Elastic Element.
C2 - National Electrical Safety Code.

(Application for copies should be addressed to the American National Standards Institute, Inc., 11 West 42nd Street, New York, NY 10036.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

ASME Boiler and Pressure Vessel Code.
ASME Performance Test Code for Displacement Compressors, Vacuum Pumps and Blowers.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

ASTM

A580 - Stainless and Heat-Resisting Steel Wire.
B16 - Free Cutting Brass Rod, Bar and Shapes for Use in Screw Machines.
B21 - Naval Brass Rod, Bar, and Shapes.
B85 - Aluminum Alloy Die Castings.
B86 - Zinc-Alloy Die Castings.

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

MG-1 - Motors and Generators.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

UNDERWRITERS LABORATORIES INC. (UL)

UL-498 - Attachment Plugs and Receptacles.
UL-817 - Cord Sets and Power Supply Cords.

(Application for copies should be addressed to the Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard commercial product. The spray outfits shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features which are not specifically prohibited by this specification but which are a part of the manufacturer's standard commercial product, shall be included in the spray outfits being furnished.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.2.1, 6.2 and 6.3).

3.3 Initial production. When specified (see 6.2), the supplier shall furnish to the Government one or more sprayers for the inspections specified in 4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

3.4 Materials. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or of the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this specification are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification unless otherwise specified.

3.4.1 Neutral reaction. Parts subject to contact with spray materials (see 3.7.1), their solvents or thinners, shall be neutral to chemical reaction with these materials.

3.4.2 Protective finishes. Exposed metal and working surfaces, except those parts inherently corrosion-resistant, shall be electrochemically plated with cadmium, chrome or nickel. The finish shall provide protection against corrosion caused by environmental or atmospheric conditions, compressed air, or spraying fluid during use or periods between service use.

3.5 Design. The design of the paint spray outfits shall be in accordance with current engineering practice. Parts of the paint spray outfits shall be the supplier's current design. All parts shall be of such size, material and strength as to sustain the maximum loads imposed with an adequate factor of safety, work efficiency, and with minimum wear during operation. The outfits and accessories supplied shall be designed for minimum maintenance with a minimum of special tools for maintenance operations. The design shall permit ready access for repair and service.

3.6 Construction. Construction shall be free of any characteristics or defects that will prevent the paint spray outfits from passing any of the examinations and tests specified in Section 4. The paint spray outfits shall be complete so that when connected to the specified source of power, they can be used for any operation for which they were designed.

3.6.1 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which reduces the casting's ability to perform its intended function.

3.6.2 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

3.6.3 Surfaces. All castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free of sand, dirt, fins, sprues, scale, flux, and other extraneous materials. External surfaces shall be smoothed and all edges shall be rounded or leveled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

3.6.4 Interchangeability. All spray outfits of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to ensure interchangeability of component parts, assemblies, accessories, and spare parts.

3.6.5 Fastening devices. All screws, pins, bolts, and similar devices shall be tight and installed with means to prevent loss of tightness or adjustment. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked or otherwise permanently deformed.

3.6.5.1 Threads. All threaded fasteners shall be in the inch system and shall comply with ANSI B1.1.

3.6.6 Hose connections, gun. Unless otherwise specified (see 6.2), air and material hose connections shall be male straight pipe thread with 60-degree bevel taper seat, or adapters shall be furnished for these sizes. The air hose connection shall be 1/4-inch NPS. The material hose connection shall be 3/8-inch NPS. The air hose connection shall be detachable, fabricated from drawn brass rod conforming to ASTM B16 (half-hard), or from corrosion-resistant steel. The connection shall be in the butt of the grip, and shall be removable for replacement, or be of the permanently inserted type.

3.6.7 Hose couplings. The hose couplings shall be made of nonferrous metal. They shall be of the swivel joint types; those for the material or fluid hose shall have 3/8-inch female threads, and those for air hose shall have 1/4-inch female threads (see 3.6.6). In instances where more than two lengths of material or fluid hose or air hose are specified, a suitable male threaded connector threaded on both ends shall be furnished for connecting each additional length of hose. All couplings shall be of the reusable type which can be removed from hose on which supplied and replaced on other lengths of hose without special tools or additional parts.

3.6.8 Hoses. Hoses shall be of commercial grade and material acceptable for intended use and as specified herein.

3.7 Gun.

3.7.1 Material. Except as otherwise specified herein, the gun shall be made of heat-treated, lightweight, nonferrous metal such as aluminum, magnesium, or similar metals or their alloys. Fiber packing or washers shall not be used where they will come in contact with the paint compounds.

3.7.2 General design. The guns shall be air pressure spray type and shall be designed to spray vertical, horizontal, overhead, and intermediate surfaces with paint, varnish, enamel, shellac, and other fast drying or setting materials having viscosities of 15 and 30 seconds, using a No. 4 Ford cup at 77 degrees Fahrenheit. The guns shall be as light in weight as practical, consistent with reliability. The design shall be such that paint compounds will not come in contact with the air control parts. The gun shall be easy to clean, simple to adjust, and so designed and constructed as to produce complete atomization and uniform spray of paint compounds. The weight of the gun shall not exceed 2 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

3.7.2.1 Body. The gun body shall be constructed to withstand designed usage while supporting all other parts of the gun. It shall have an integral hand grip designed to fit the operator's hand and maintain balance with the air and material hoses connected. The body shall be in the general shape of a pistol with grip suitable for two or more finger trigger control. A hook shall be provided at the top of the body for hanging the gun when not in use. The body shall have a buffed and polished surface. The gun shall withstand pressure tests specified in 4.5.6.

3.7.2.2 Nozzle. The nozzle assembly shall consist essentially of an air cap, material needle valve and fluid nozzle, and auxiliary parts. The nozzle provided shall be specially designed for use with the gun to be furnished with the type outfit specified. The nozzle assembly and parts, when size permits, shall be permanently and legibly marked with the original manufacturer's size or spray pattern designation.

3.7.3 Performance. When the spray guns and equipment are operated under test conditions specified in Section 4, they shall produce a smooth, continuous, penetrating film of the sprayed material. Spraying shall be effected without an excessive loss of thinners, solvents, or drying agents in off spray or mist.

3.8 Type A, standard.

3.8.1 General. Spray outfits of this type shall consist essentially of a gun, pressure tank, pressure cup, two lengths of air hose, two lengths of material hose, and when specified (see 6.2), a tank truck, extension nozzle, oil and moisture separator, and extension gun or handle shall be furnished (see 3.8.3, 3.8.7, 3.8.8, and 3.11). The outfit shall be designed to withstand a maximum pressure of 100 pounds per square inch (psi) without distortion of any part, except the pressure cup.

3.8.2 Gun. The gun shall be of the general purpose, heavy-duty, siphon-pressure type (see 3.7.1 to 3.7.3 inclusive). The gun shall be suitable in all respects for volume production spraying. It shall be designed and fabricated to withstand without leakage or deformation, an air pressure of 250 psi (see 4.5.6). Guns shall not exceed 6 cubic feet per minute (cfm) air consumption at 30 pounds per square inch gage (psig). Threaded parts of wear-resistant brass, bronze, or aluminum which are subject to frequent attachment and detachment in normal service, shall have strength and abrasion resistance not less than that of brass conforming to ASTM B16 (half-hard). Threaded parts shall be replaceable. All working parts and removable hose connections shall be replaceable by the use of common hand tools. The gun shall consist essentially of a body, a head, the necessary parts for a nozzle assembly, air and material valves, trigger, and hose connection. This gun shall be suitable for operation from quart cup or pressure tank.

3.8.2.1 Body. The gun body shall conform to the requirements of 3.7.2.1.

3.8.2.2 Head. The head of the gun shall be either detachable or form an integral part of the gun body, as specified (see 6.2). If the head is detachable, it shall be accurately machined and designed for positive alignment. Special tools shall not be required for removing or tightening the head. The head, whether integral or detachable, shall provide support and correct

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

alignment for nozzle parts. The exterior surfaces of the head shall be finished with a buffed metallic protective coating.

3.8.2.3 Nozzle. The nozzle shall conform to the requirements of 3.7.2.2.

3.8.2.3.1 Air cap. The air cap shall provide suitable air openings for complete atomization without splattering or splitting the spray pattern (see 4.5.3.1), and shall be held fast to the gun head by means of a retaining ring. The cap shall be fabricated from a brass drop forging or rod conforming to ASTM B21 (C48500), or ASTM B16 (half-hard). It shall be so designed as to provide a uniform spray under all normal working conditions.

3.8.2.3.2 Fluid nozzle. The fluid nozzle shall provide a precision fit with the fluid needle to ensure a positive shutoff, without any leakage of the paint compound when the trigger is released (see 4.5.2.1.1). The nozzle and needle shall be made of corrosion-resisting metals. Interior surfaces affecting material flow such as the fluid orifice, and exterior surfaces affecting air flow, shall be smooth finished and free of imperfections such as burrs or projections, to reduce interference with flow of air and material to a minimum.

3.8.2.3.3 Auxiliary parts. Baffle plates, tension washers, retainer rings, and other auxiliary parts, as required, shall be provided.

3.8.2.4 Material and air valves. The material and air valves shall be operated by the trigger, and shall be held normally, closed by coil springs enclosed within the gun body. Valves shall provide cut-off of paint compound and normal shut-off of air (see 4.5.2.1.1). Valve stems and needles shall be made of steel conforming to ASTM A580 (S420000). Valve packing shall be treated leather, graphite, or other suitable material.

3.8.2.4.1 Material valve. The material valve shall be of the needle type, not less than 1/8-inch in diameter, and shall be made of corrosion-resisting metal. It shall be machined to close fit to preclude binding.

3.8.2.4.2 Air valve. The air valve shall be of the cartridge or of the spring seated type, which shall increase its seating efficiency under pressure.

3.8.2.5 Trigger. The trigger shall be designed for two or more finger control, and shall operate to permit holding fingers in a normal position when spraying and aid in balancing the gun. The trigger control shall be positive and shall operate to permit flow of air before material flow, and shut-off of material before shut-off of air. The trigger shall contain a hardened steel plate at points of contact with valve stems, or it shall be otherwise designed for minimum wear.

3.8.2.6 Connections and fittings. Connections and fittings shall conform to the requirements of 3.6.6. The material hose connection shall be located underneath the head or body, and so positioned as to allow use of a siphon or pressure feed cup or hose connection from pressure feed tank.

3.8.2.7 Air flow control. Suitable means shall be provided in the gun for maintaining adjustment of the spray. Means of adjusting air flow for forcing atomized paint into the spray pattern shall be located in a position convenient to the operator. It shall be possible to adjust this air flow without stopping

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

the spraying operation. The fluid needle and valve seat shall have a Rockwell hardness of 44 to 54 on the Rockwell "C" scale (see 4.5.3.3).

3.8.2.8 Spray pattern control. The gun shall be fitted with an external mix and adjustable nozzle that will deliver a round or fan shaped spray pattern (horizontal or vertical), as required. The gun shall be adjustable to regulate the volume, size, and shape of the spray pattern quickly without disconnecting the gun, exchanging nozzles, or the use of tools. The adjustment of both the nozzle and the gun shall be maintained without chance of accidental change while the gun is in operation.

3.8.3 Nozzle extension. When specified (see 6.2), the nozzle extension shall be not less than 18 inches long, shall be easily attached to the spray gun, and shall be suitable for spraying any materials suitable for use in the gun. The nozzle, internal or external mix, shall produce a standard fan-shaped spray pattern. The extension shall be made of lightweight corrosion-resisting metal, and shall produce results equal to those obtained with the gun alone.

3.8.4 Tank and accessories. The tank and accessories shall be in accordance with the requirements of this specification (see 3.10 to 3.10.5).

3.8.5 Cup. The cup shall be made of nonferrous metal. It shall have a capacity of not less than 1 quart, and shall be of seamless construction. It shall be so designed that it may be attached quickly and securely to the gun in such manner that there will be no possibility of the cup coming loose unintentionally, and that when cup and cover are attached, there shall be formed an air-tight and liquid-tight joint at operating pressures. If a gasket is required between the cup and the cover, a spare gasket shall be furnished. The cup shall be constructed to withstand 50 psig air pressure (see 4.5.6). The cover shall be fitted with a 3/8-inch threaded (see 3.6.6) swivel connection, female, with 60-degree bevel taper seat, for securely attaching cup to material connection of the gun. The cover of the cup shall be fitted with a material tube which shall extend into the cup, just clearing the bottom of the cup when cover is secured in place. This material tube shall be made of brass conforming to ASTM B16 (half-hard or 2S half-hard aluminum tubing), and shall be of adequate size to handle materials specified. If connection is threaded, the cover shall be of sufficient strength to hold the cup, gasket (if used), and cover in positive engagement. The cup opening shall be of sufficient size to permit easy cleaning of the interior, and shall be not less than 2.7 inches in diameter. A safety valve shall be located in the cup cover, or such valve shall be provided elsewhere in the outfit.

3.8.6 Hose.

3.8.6.1 Air hose. The air hose shall have a 5/16-inch diameter bore and shall be furnished in 25-foot lengths. Couplings shall be provided at each end of each length of hose for attaching hose to gun and tank. Hose with couplings attached shall be so constructed as to withstand an air pressure of 150 psi (see 4.5.6).

3.8.6.2 Material or fluid hose. Unless otherwise specified (see 6.2), the material or fluid hose shall be provided with 3/8-inch nominal diameter bore and shall be furnished in 25-foot lengths. Couplings shall be provided at each end of each length of hose for attaching hose to gun and tank. Hose with couplings

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

attached shall be constructed to withstand a working pressure of 100 psi (see 4.5.6).

3.8.7 Oil and moisture separator. When specified (see 6.2), the oil and moisture separator shall conform to the requirements of MIL-S-12928, for class 1 or class 2 regulators, as specified (see 6.2). The separator shall be suitable for removing residual amounts of oil, water, scale, and other foreign matter from the compressed air in the supply line. The separator shall be arranged for mounting on wall, pipe standard, or integral with the paint spray equipment. The body and filter devices shall be corrosion-resisting. Die castings will not be acceptable for the body of the separator but they may be used as top and bottom covers of this unit. The separator shall be so designed that it may be disassembled for periodic cleaning or replacing the filtering device and reassembled for use. The separator shall be so designed that it will not require adjustment of any kind or fail to function in normal use.

3.8.7.1 Regulators. The regulators shall be of the conventional hand screw type for adjusting air pressure from 5 to 90 psi. Capacity of the regulator shall be such that the required volume of air will be delivered at the prescribed regulated pressure. A diaphragm of not less than 2-1/8-inch diameter and a suitable valve mechanism shall be enclosed within the body and operated by a convenient handle for easy adjustment. Material for the body shall be brass conforming to ASTM B21 (C46400), or ASTM B16, having a minimum tensile strength of 30,000 psi. The body material may also be wrought aluminum alloy having high corrosion resistance and a minimum tensile strength of 30,000 psi. Unless otherwise specified (see 6.2), the regulators shall conform to MIL-S-12928.

3.8.7.2 Gages. Gages shall conform to ANSI B40.1. One gage shall be mounted on each regulator to indicate regulated pressure and one gage shall be mounted to indicate main line air pressure. Regulated pressure gage shall indicate 0-100 psig. Main line gage shall indicate 0-200 psig.

3.8.8 Extension guns and handles. When specified (see 6.2), the extension gun or handle for use in painting ceilings, walls, trusswork, and similar surfaces, shall be made of nonferrous metal and shall be light in weight and properly balanced for ease of operation. The parts shall be firmly fastened, making a rigid unit which shall be self-supporting and of sufficient strength for operation without excessive deflection or permanent set. With the extension gun or handle, the operator shall be able to produce results equal in all respects to those obtained when using the gun alone.

3.8.8.1 Extension handle. The extension handle shall consist of two passages, one for air and one for paint, together with trigger actuating mechanism for controlling the action of the trigger of the gun from the operator's end of the extension handle. The gun end of the handle shall be designed for mounting of a standard hand type gun. This end of the handle shall be of such shape that when the gun is attached, the nozzle of the gun shall be tilted not less than 40 degrees nor more than 45 degrees above the horizontal plane when the main body of the handle is held perpendicular to the horizontal plane. The end of the handle to which the gun is attached shall be fitted with nonferrous couplings of the swivel joint type, having 3/8-inch female threads for the material or fluid connection, and 1/4-inch female threads for the air connection (see 3.6.6). The end of the handle to which the hoses are to be attached shall be fitted with 3/8-inch male threaded nipples, or adapters shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

be provided for this size for the material or fluid connection, and 1/4-inch male threaded nipples or adapters shall be provided for this size for the air connection (see 3.6.6). Handles shall be furnished in 3-, 4-, 6-, 8-, or 10-foot lengths, as specified (see 6.2).

3.8.8.2 Extension gun. These guns shall consist essentially of the manufacturer's standard tip and nozzle only, connected to a controlling means by a fluid tube and an air tube. A positive mechanism for controlling the flow of material or fluid and air shall be in close proximity to the hands of the operator. The design of these guns shall be such that extension of control to the nozzle end of the extension is not required. The nozzle shall be mounted at an angle of not less than 40 degrees nor more than 45 degrees above the horizontal plane when the main body of the extension is held perpendicular to the horizontal plane. Extension guns, complete with controlling mechanism and tube, shall be so constructed that rigidity is attained with minimum weight. The end of the extension to which the hoses are to be attached shall be fitted with 3/8-inch male threaded nipples, or adapters shall be provided for this size for the material or fluid connection, and 1/4-inch male threaded nipples or adapters shall be furnished for this size for the air connection (see 3.6.6). Extension guns shall be furnished in 4-, 6-, 8-, or 10-foot lengths, as specified (see 6.2).

3.9 Type B, lightweight.

3.9.1 General. Spray outfits of this type shall consist essentially of a light duty gun, pressure cup, air hose, air compressor, compressor motor, and air pulsation tank or chamber or other means to ensure a smooth flow of air without pulsation. When specified (see 6.2), material hose and material (paint) pressure feed tank shall be included.

3.9.2 Gun. The gun shall be of the pressure type, either internal or external atomizing, and shall be equipped with three interchangeable nozzles, one for round spray pattern, one for fan spray pattern, and one for 45-degree, angular spray pattern. The gun shall consist essentially of a body and necessary parts for a nozzle assembly, air connection, material valve, and a trigger. Air and material passages shall be adequate for the maximum air and material demand required for satisfactory spraying with a minimum drop in pressure. This gun shall be suitable for operation from both a quart cup and a pressure tank.

3.9.2.1 Body. The gun body shall be made of material having a minimum tensile strength of 30,000 psi, and shall conform to ASTM B85 or ASTM B86. It shall be of one-piece construction, accurately machined where required, to ensure support and correct alignment to the fluid nozzle, fluid needle, and air cap parts. The fluid nozzle, fluid needle, and air cap parts shall be of the removable and replaceable type, and shall be precision machined to fit the gun body. They shall be permanently and legibly marked for identification and replacement.

3.9.2.2 Nozzle. The fluid nozzle shall be in accordance with 3.8.2.3.

3.9.2.3 Connections. The gun shall be provided with a 1/4-inch fitting for the air connections, or adapters shall be furnished for this size (see 3.6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

3.9.2.4 Material valve. The material valve shall be operated by the trigger, and shall be held normally closed by a coil spring enclosed within the gun body. The valve shall seat to provide cut-off of liquid (see 4.5.2.1). Valve stem and needle shall be made of corrosion-resistant steel. Valve packing shall be treated leather, graphite, or other suitable material.

3.9.2.5 Trigger. The trigger shall be similar to that of 3.8.2.5. The gun shall be adjustable to regulate the volume of the spray quickly without disconnecting the gun, or the use of any special tools, and adjustment shall be maintained without chance of accidental change while the gun is in operation.

3.9.3 Cup. The cup shall be made of nonferrous metal. It shall have a capacity of not less than one quart, and shall be of the pressure type. It shall be of seamless construction, and shall be so designed that it may be attached quickly and securely to the gun in such manner that there will be no possibility of the cup coming loose unintentionally. The cup shall be constructed to withstand an air pressure of 50 psi. If a gasket is required between the cup and cover, two shall be supplied; one of these to be retained as a maintenance part. The cup and cover shall be so designed and constructed that when attached to each other, an air and liquid-tight joint at operating pressure shall be formed. The cup opening shall be of sufficient size to permit easy cleaning of the interior, and shall be not less than 2-1/4 inches in diameter.

3.9.4 Hose. When the outfit is intended for use with cup only, one 15-foot length of air hose shall be supplied. Where a material pressure feed tank is to be supplied (see 6.2), two 15-foot lengths of air hose and one 15-foot length of material (fluid) hose shall be supplied.

3.9.4.1 Air hose. The air hose shall be 1/4-inch inside diameter. Tube and cover shall be synthetic rubber. Reinforcement shall be single or double braid. Working pressure shall be not less than 200 psig. Burst pressure shall be at least four times the working pressure.

3.9.4.2 Material hose The material or fluid hose shall have a 3/8-inch inside diameter.

3.9.5 Air compressor. Except as otherwise specified herein, the compressor shall be in accordance with MIL-C-3925, type I, style 1, size 1. The compressor, when driven at the manufacturer's recommended revolutions per minute, shall have a displacement of not less than 2.7 cfm, and shall be capable of attaining a pressure of at least 80 psi. The compressor shall produce air at 50 psig. At this pressure, actual delivery shall be not less than 1.5 cfm free air. At 40 psig, the capacity shall be not less than 1.7 cfm free air. This requirement is intended to indicate the required capacity of the compressor and not the pressure at which the paint spray outfit is to be operated. When the paint spray outfit is operated, the compressor shall produce adequate volume and pressure of air for continuous spraying of the materials specified in 3.7.2, with the quality of application specified in 3.7.3 (see 4.5.2.2). The compressor shall be designed and constructed to prevent building up uncontrolled pressure above the structural strength of the outfit. The compressor shall successfully complete the tests specified in 4.5.4.1 to 4.5.4.1.2 inclusive. The compressor crankshaft shall have two main bearings, one on each side of the connecting rod bearing, and shall be of the anti-friction ball or tapered roller type. One of the bearings shall support the outer end of the crankshaft. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

requirements and definitions of ASME Rules for Construction of Pressure Vessels shall apply.

3.9.6 Electrical requirements.

3.9.6.1 Electric motor. The motors shall be not less than 1/3 horsepower, designed for operation on the power supply specified (see 6.2), and shall have adequate power to provide the volume and pressure of air specified in 3.9.5 in continuous operation without exceeding the allowable temperature rise of 40 degrees Celsius for an open type, and of 55 degrees Celsius for a totally enclosed explosion-proof type. Motors shall conform to NEMA MG-1. Class and style shall be as specified. Motors shall be equipped with ball bearings.

3.9.6.2 Switch. Each paint spray outfit shall be provided with a start-stop motor control switch. The switch shall be rated to agree with the motor rating as indicated on the identification plate. The switch shall be of the commercial toggle type, if mounted on the motor or some adjacent part other than the cable. When specified (see 6.2), switch enclosures shall be provided for use in hazardous atmosphere, and shall conform to the requirements of ANSI C2 for class I, division 2 locations.

3.9.6.3 Cable assembly. Each unit shall be furnished with a cable assembly as an integral part of the equipment. Cable assembly shall consist of not less than 15 feet of three-conductor commercial SO, ST, SJO, or SJT cable, as required for the motor size furnished, and an attachment plug cap conforming to UL-498 requirement for two-pole, 3-wire ground devices rated 15 amperes, 125 volts.

3.9.7 Receiver of pulsation chamber. Means shall be provided to minimize pressure surges in the discharge from the compressor. This shall consist of an external receiver or moisture separator, or of a built-in pulsation chamber. The receiver, moisture separator, and pulsation chamber shall be designed to withstand 150 psi (see 4.5.4.1). A drain cock and a safety valve set for a maximum pressure of 50 psi shall be provided. A moisture separator in the discharge air line will be satisfactory.

3.9.8 Base. The air compressor, compressor motor, receiver, and pulsation chamber, as applicable, shall be mounted compactly on a common base and shall be provided with a handle or other suitable device for carrying by one person. The base shall be equipped with four cushioned rubber feet constructed to prevent the unit from creeping or scuffing when in operation.

3.9.9 Material (paint) pressure feed tank. When furnished, the material (paint) pressure feed tank shall be in accordance with 3.10 through 3.10.5, except that the agitator and the regulator are not required. Tank without welded chime will be acceptable and fittings may be limited to suitable air intake, air and fluid outlets, safety valve (set for a maximum pressure of 75 psi), and relief valve. The tank shall be 2-gallon size and have a capacity for not less than 1-1/2 gallons of paint material. A "D" shaped handle will be acceptable.

3.10 Material-pressure feed tank. The material-pressure feed tank shall be in accordance with ASME Rules for Construction of Pressure Vessels, designed and constructed to withstand a test pressure of at least 150 psi. The dimensions of

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

the tank shall be such that, with the cover assembly and fittings in place, there will be no tendency toward top-heaviness, even when the tank is empty. The tank shall be made of corrosion-resistant steel, or heavily galvanized inside and outside, or otherwise treated to have equal corrosion resistance. It shall be cylindrical in shape, with welded-in bottom chime, and shall be of the removable paint container type. The paint container shall be easily and quickly lifted out when the cover is removed from the tank. Unless otherwise specified (see 6.2), one container shall be furnished with each tank. The tanks shall be furnished in sizes from 2 to 15 gallons, as specified (see 6.2). The 2-gallon tank shall have not less than 1/2-gallon capacity for paint materials, and the 15-gallon tank shall have not less than 13-gallon capacity for paint materials. Intermediate sizes shall have capacities in direct proportion. All tanks, except the 2-gallon size on which "D" type handle will be acceptable, shall have two metal handles near the top of the tank diametrically opposite each other. The handles and means of attachment shall be of such strength that a capacity fill of paint may be lifted without noticeable deflection or permanent set.

3.10.1 Cover. The tank cover shall be designed to provide a sealed closure for the tank size specified and shall provide for assembly of the agitators and required fittings. The cover shall comply with the ASME Rules for Construction of Pressure Vessels, and shall withstand a test pressure of not less than 150 psi. If made of steel, it shall be heavily galvanized inside and outside or otherwise treated to have equal corrosion resistance. The cover shall be fastened by quick acting clamps, or other equally suitable means for easy and quick installation and removal from the tank. The cover shall incorporate a gasket or other suitable means of providing a leakproof pressure seal.

3.10.2 Agitator. When specified (see 6.2), an air-driven or hand-driven agitator shall be installed as part of the cover assembly. The agitator shall be capable of thorough agitation of the paint materials, preventing any settling of the pigments, solvents, or thinners. Air-motor-driven agitators shall have provision for agitation speed adjustment and for shutting off the air motor.

3.10.3 Filler opening. Covers for 5-gallon or larger capacity tanks may have a filler opening so that painting materials can be added without removal of the tank cover. The filler opening cap on such covers shall be attached with quick acting means, not subject to accidental loosening, which will provide a pressure-tight seal at working pressures. The material filler cap shall have a small hole drilled in the threads to allow slow release of pressure during removal of the cap, to prevent its removal without prior pressure release, as a safety feature.

3.10.4 Tank accessories. The following accessories shall be provided either on the cover of the tank or in some other position readily accessible to the operator:

a. Pressure regulator for governing the atomizing pressure of the gun (0 - 100 psig) (see 3.8.7.1).
b. Pressure regulator for controlling the material through the hose to the gun (0 - 100 psig) (see 3.8.7.1).
c. Gage for indicating the atomizing pressure (see 3.8.7.2).
d. Gage for indicating the pressure in the tank (see 3.8.7.2).
e. Relief valve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

f. Safety valve shall be ASME non-adjustable type, set to automatically blow off when the pressure in the tank reaches a minimum of 100 psig or a maximum of 120 psig.
g. Air and material shut-off valves.
h. Paint strainer on material pick-up tube.

3.10.5 Connections. The connections on the tank to which the hoses are to be connected shall be 3/8-inch male threaded nipples for the fluid or material hoses, and 1/4-inch male threaded nipples for the air hoses, or adapters shall be provided for these sizes (see 3.6.6).

3.11 Tank truck. When specified (see 6.2), a tank truck shall be furnished. The truck, if practical, shall be separate from the tank, but if designed as an integral part of the tank, the truck shall have suitable means of locking when necessary to prevent rolling.

3.12 Electromagnetic interference suppression. When specified (see 6.2), electric motors and related circuit components shall be electromagnetic interference-free, and shall conform to the suppression requirements for type II A equipment of MIL-STD-461. This requirement applies for type B paint spray outfit only.

3.13 Identification marking. Identification shall be permanently and legibly marked directly on the spray outfits or on a corrosion-resisting metal plate in accordance with MIL-STD-130 and securely attached to the spray outfits at the source of manufacture. Identification shall include the manufacturer's model and serial number, name and trademark.

3.13.1 Marking of gun parts. Parts, the size of which permit, shall be marked in a plain and permanent manner with the name of the original manufacturer and the model number, or with the manufacturer's trademark of such known character that the source of manufacture may be readily determined. When parts, the size of which do not permit proper marking, are required as replacements, they shall be enclosed in individual packages marked in accordance with MIL-STD-130.

3.14 Instruction plates. The spray outfits shall be equipped with instruction plates suitably located, describing any special or important procedures to be followed in operating and servicing the equipment. Plates shall be of a material which will last and remain legible for the life of the equipment. Plates shall be securely affixed to the equipment with nonferrous screws or bolts of not less than 1/8-inch diameter.

3.15 Treatment and painting. Unless otherwise specified (see 6.2), the spray outfits shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the spray outfits other than corrosion-resisting steel shall be protected against corrosion and present a neat appearance.

3.16 Workmanship. The workmanship shall be in accordance with the requirements specified herein and shall comply with all quality assurance provisions of Section 4 of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1)
b. Quality conformance inspection (see 4.2.2)
c. Electromagnetic interference tests (see 4.2.3)

4.2.1 First article inspection. The first article inspection shall be performed on spray outfits when a first article is required (see 3.2, 6.2 and 6.3). This inspection shall include the examination of 4.4 and the tests of 4.5. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5, and the packaging inspection of 4.6. This inspection shall be performed on the samples selected in accordance with 4.3.

4.2.3 Prior approval of electromagnetic interference suppression. Prior to authorization for first article, complete electromagnetic interference tests as specified herein shall be performed by the contractor or a commercial test laboratory to determine compliance with the interference suppression requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. The unit of production shall be one spray outfit for each classification. All spray outfits offered for delivery at one time shall be considered a lot for the purpose of inspection. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot is screened, reinspection shall be limited to the defect causing rejection. If the lot is reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each spray outfit shall be examined for defects listed in Table I. Each attribute within each classification of multiple defects shall constitute one defect.

Table I. Classification of defects.

Classification	Defects
Major:	2.5 percent defective
101	Type not as specified
102	Component parts missing, damaged, or not as specified
103	Threaded connections, dimensions not as specified
Minor:	4 percent defective
201	Identification marking not complete

4.4.1 Tests for quality conformance. Each sample selected (see 4.3) shall be tested for compliance with the requirements of this specification. Acceptable Quality Level shall be 2.5 percent defective. Nonconforming outfits shall not be offered for delivery and if the number of defective units exceeds the acceptable number for the samples tested, the lot represented shall be rejected. Quality conformance tests shall consist of the tests specified (see 4.5.1, 4.5.2.1, 4.5.2.2 and 4.5.2.3).

4.5 Tests.

4.5.1 Electromagnetic interference test. The electromagnetic suppression network of the outfit offered shall be tested.

4.5.2 Performance tests.

4.5.2.1 Leakage tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

4.5.2.1.1 Test on guns. This test shall be performed by connecting an air hose first to the fluid inlet and then to the air inlet of the gun (so designed). With the gun used with the type A outfit, air pressure of the pressure used in normal operation) shall be applied and the gun nozzle immersed in water. Leakage beyond 50 bubbles per minute in the test shall be considered excessive and cause for rejection (see 3.8.2.3.2, 3.8.2.4, and 3.9.2.3). The trigger of the gun shall be actuated three times for 1/2-minute cycles to ensure correct reseating performance of the valves.

4.5.2.1.2 Tests on outfits. Each of the connections on the outfits shall be similarly tested by immersion in water in an endeavor to determine that all connections are airtight. Pressure tanks and compressor connections shall be tested by application of a leak test solution or other means to visually indicate the presence of air leakage. Leakage shall be cause for rejection.

4.5.2.2 Operation test. The outfit shall be placed in actual operation to determine the ability of the components to function satisfactorily under all conditions specified in Section 3, when spraying fluid (see 3.7.2). A standard flowmeter shall be used to register the quantity of air consumed for operation (see 3.7.2 and 3.7.3).

4.5.2.3 Dielectric test. Cable assembly tests for dielectric strength shall be tested in accordance with the requirements of UL-817.

4.5.3 Spray gun tests.

4.5.3.1 Siphon-pressure type gun (type A outfit). The gun shall not require more than 12 cubic feet of air per minute at not more than 50 psi pressure (see 4.5.6). The nozzle shall deliver fully atomized patterns ranging from 2 to 3 inches for narrow patterns and 6 to 8 inches for wide patterns, without splitting or spattering the spray pattern (see 3.8.2.3.1) when spraying a pigmented material having a viscosity of 22 seconds, using a number 4 Ford cup at 72 degrees Fahrenheit. The gun shall be held perpendicular to and at a distance of 8 inches from the surface being sprayed.

4.5.3.2 Pressure-constant bleed-type gun (type B outfits). The gun shall not require more than 1.7 cubic feet of air per minute at not more than 40 psi pressure (see 4.5.6). Using the nozzle which produces a flat shaped spray pattern, the spray pattern shall be fully atomized and not less than 6 inches wide when the gun is held 7 inches from and perpendicular to the surface being sprayed. Under these conditions, there shall be no splitting or spattering of the spray pattern when spraying any paint material for which the gun is intended, as specified (see 3.7.2 and 3.7.3).

4.5.3.3 Hardness tests. Needle and valve hardness tests shall be performed to determine conformance (see 3.8.2.7), or the supplier shall provide certification of conformance with the hardness requirements of this specification.

4.5.4 Compressor tests.

4.5.4.1 Compressor (type B outfit). The compressor shall be tested in accordance with the ASME Performance Test Code for Displacement Compressors,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

Vacuum Pumps, and Blowers. Inability of the compressor to deliver the capacity and pressures (see 3.9.5) shall constitute failure of this test.

4.5.4.1.1 Endurance test. After satisfactory completion of the tests (see 4.5.4.1), the compressor shall be subjected to an endurance test of 300 hours of continuous operation (no running period to be less than 8 hours) at capacity of not less than 1.7 cfm, at not less than 40 psi pressure. Failure to supply the specified capacity and pressure for the duration of this test shall constitute test failure. Failure of any part requiring more than 1 hour to remove and replace, or a second failure of any part, shall constitute test failure.

4.5.4.1.2 Final test. After completion of the endurance test, the compressor shall be tested as specified in 4.5.4.1. Failure to meet the test requirements will constitute test failure.

4.5.5 Gages and regulators. Gages and regulators used with the outfits shall be tested to verify accuracy in accordance with the accuracy requirements of MIL-S-12928 and ANSI B40.1, as applicable.

4.5.6 Pressure test. Pressure tests shall be performed to determine the ability of the various components of each outfit to withstand the specified pressures (see 3.8.2, 3.8.6.1, 3.8.6.2, 3.9.3, 3.10, and 3.10.3). Pressure tests shall also be performed on the completely assembled outfits to determine their ability to withstand the specified pressures (see 4.5.3.1 and 4.5.3.2).

4.6 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified (see 6.2), preservation, packing, and marking shall be the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use.

6.1.1 Type A. Type A standard paint spray outfits are intended for general use where a source of compressed air is available.

6.1.2 Type B. Type B lightweight paint spray outfits are intended for miscellaneous work where compressed air is not readily available and where outfits are required to be of such size that they can be readily carried from place to place by one person.

6.2 Acquisition data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type required (see 1.2).
c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When first article inspection is required (see 3.2 and 4.2.1).
e. Number of sample units required for inspections (see 3.3 and 4.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

f. When hose connection threads are to be other than as specified (see 3.6.6).
g. Parts required for type A outfits (see 3.8.1).
h. Whether gun with detachable or integral head is required (see 3.8.2.2).
i. If extension nozzle is required (see 3.8.3).
j. Dimensions of material hose, if other than as specified (see 3.8.6.2).
k. If oil and moisture separators are required (see 3.8.7).
l. When regulators are other than specified (see 3.8.7.1).
m. If extension guns and handles are required (see 3.8.8).
n. Length of extension handle or gun required (see 3.8.8.1 and 3.8.8.2).
o. If material hose and pressure tank are required for type B outfits, and lengths of air and material hose to be supplied (see 3.9.1, 3.9.4, 3.9.4.2 and 3.9.9).
p. Power supply required for electric motor (see 3.9.6.1).
q. When switch enclosure is to be provided for use in a hazardous location (see 3.9.6.2).
r. Size and number of tanks required for type A (see 3.10).
s. Type of agitator, if required (see 3.10.2).
t. If tank truck is required (see 3.11).
u. Electromagnetic interference suppression requirements (see 3.12 and 4.5.1).
v. When spray outfits shall be treated and painted other than as specified (see 3.15).
w. When preservation, packing and marking is other than specified (see 5.1).

6.3 First article. When a first article inspection is required, the item will be tested and should be a first article sample, or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Part or identifying number (PIN). The PIN to be used for spray outfits covered by this specification is created as follows:

M15297 - XX
Military specification designation
Type code number (see 6.4.1)

6.4.1 Types. The types of the spray outfits (see 1.2) are identified by a two-digit number (see Table II).

Table II. Type to code number.

TYPE	CODE
Type A	01
Type B	02

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Air
Air compressor
Gun
Pressure

6.6 Definitions. From "ASME Rules for Construction of Pressure Vessels":

a. Free air. Free air refers to the prevailing atmosphere in the vicinity of a compressor. The free air is expressed in terms of the atmospheric temperature, pressure, and relative humidity at the compressor inlet.
b. Displacement. The displacement of a compressor is the volume displaced per unit time by the piston of a reciprocating type or by vanes, gear teeth and lobes of the rotary types. It is expressed in cfm.
c. Capacity (actual delivery). The capacity of a displacement compressor is the volume rate of flow of gas, compressed and delivered, when volume rate is expressed at conditions of total temperature, static pressure and specific weights prevailing at the compressor inlet.
d. Standard commercial product. A standard commercial product is a product which has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs or brochures, and represents the latest production model.

6.7 Subcontracted material and parts. The preparation for delivery requirements of referenced documents listed in Section 2 do not apply when material and parts are procured by the supplier for incorporation into the equipment and lose their separate identity when the equipment is shipped.

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Navy - YD
Air Force - 99

Review Activities:
Army - AL
DLA - CS

Preparing Activity:
Navy - YD

(Project 4940-N561)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-15297H	930430

3. DOCUMENT TITLE
SPRAY OUTFITS, PAINT, PORTABLE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
ROGER P. KIEFER	805-982-5564	551-5564
c. ADDRESS (Include Zip Code) COMMANDING OFFICER, NCBC CODE 1562W 621 PLEASANT VALLEY ROAD PORT HUENEME, CA 93043-4300	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:02Z
Check the source to verify that this is the current version before use.