MIL-C-46216B (MU)
15 April 1969
SUPERSEDING
MIL-C-46216A (MU)
20 May 1963

MILITARY SPECIFICATION

CARTRIDGE, 105MM, APDS-T, M392A2
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading assembling and packing of one type of armor-piercing, discarding sabot, tracer loaded cartridge, APDS-T, M392A2 for use in 105MM Guns, U.K., TK. L7A1 and U.S., M68.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or requests for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167- Ammunition Data Card
MIL-STD-1168- Lot Numbering of Ammunition
MIL-STD-1235- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

ARMY

8863427 - Cartridge, 105MM, APDS-T, M392A2, Assembly and Marking Diagram.
8835039 - Box, Packing, Ammunition, for Cartridge, 105MM, APDS-T, M392A2 for Gun M68 in Fiber Container M431.
8835040 - Container, Ammunition, Fiber M431, for Cartridge 105MM, APDS-T, M392A2, for Gun M68.

PUBLICATIONS

ARMY

ET-8863427-Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable specifications and drawings.

3.2 Complete round.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 8863427 and with all requirements specified in applicable specifications.

3.3 Propellant weight.-The weight of the propellant shall not differ by more than plus or minus 0.12 ounce avoirdupois from that designated by the loading authorization for the particular lot of propellant used.

3.4 Cartridge case crimp (bullet pull).-The cartridge case shall separate from the shot at a load between 1300 pounds, minimum (min.), and 4,000 pounds, maximum (max.), when tested as specified in 4.3.1.

3.5 Security of sub-projectile.-The sub-projectile shall not rotate in the projectile sabot when subjected to 50 plus or minus 5 inch pounds torque in a counter-clockwise direction when facing nose of projectile.

3.6 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.4.

3.6.1 Muzzle Velocity.-The muzzle velocity of the cartridge when fired at 70°F shall be not more than 50 feet per second (f.p.s.) above nor less than 50 f.p.s. below the muzzle velocity as specified on drawing 8863427 and the standard

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

deviation of the lot shall be not greater than 12 f.p.s. max.

3.6.2 Tracer functioning.-The tracer shall ignite and there shall be visible evidence of the burning of the tracer composition for a distance of 2000 meters.

3.6.3 Safety.-There shall be no hangfires, premature bursts, or indications of metal parts failure in the gun bore or in flight, prior to impact, except as will normally occur with respect to the discarding of the sabot, during any of the proving ground tests conducted.

3.7 Workmanship

3.7.1 General.-The cartridge and all components shall be free of cracks or burrs; and chips, dirt, grease, rust or other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge shall not be damaged in any manner during the loading operation.

3.7.2 The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked, when such paintings and markings have been marred or obliterated. (Bare spots in painting, other than marking, are allowable provided that they total not more than 1/4 square inch in aggregate, and that the maximum dimension of any individual bare spot does not exceed 3/16 inch).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Terms of use: https://assist.dla.mil/online/agreement.htm

quality assurance provisions specified in this specification.

b. Drawing, and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates, unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be contrued to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

Each inspection lot of loaded complete round cartridges shall contain:

a. Cartridge cases from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision; or if resized cases are used, from not more than one lot.

b. Projectiles of one lot interfix number from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision.

c. Propellant of one lot from one manufacturer.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Loaded tracers of one lot interfix number from one manufacturer.

f. Liners of one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Primer, prior to assembly to cartridge case (see dwg. 8839499 covering a detail of dwg. 8863427).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:			
	1. Any flash hole missing.....	Visual	01001
Major:	AQL 0.40 percent		
	101. O-ring missing.....	Visual	01002
Minor: None defined.			

4.2.2.2 Cartridge case primer assembly, prior to loading of propellant (see dwg. 8863427).

Categories	Defects	Method of Inspection	Code No.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T08:42
Check the source to verify that this is the current version before use.

Critical: None defined.

Major: AQL 0.65 percent		
101. Primer fails to withstand disassembly torque	Torque-Test	02001
102. Lower liner loose, missing or obviously mislocated	Visual	02002
103. Upper liner loose, missing or obviously mislocated	Visual	02003
Minor: AQL 1.50 percent		
201. Primer stake missing	Visual	02004
202. Foreign matter in interior of case (see 3.7)	Visual	02005
203. Primer bent or damaged	Visual	02006

4.2.2.3 Shot loading assembly, prior to assembly to cartridge case (see dwg. 8863426 covering a detail of dwg. 8863427).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major: AQL 0.40 percent			
101.	Plug and disc assembly fails to withstand disassembly torque	Torque-Test	03001
102.	Component missing	Visual	03002
Minor: AQL 1.50 percent			
201.	Tracer closing disc missing, damaged or loose	Visual-Manual	03003
202.	Marking misleading or unidentifiable including incorrect color code	Visual	03004
203.	Evidence of poor workmanship (see 3.7)	Visual	03005

4.2.2.4 Complete round assembly (see dwg. 8863427).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Distance from rear face of cartridge case to top of electrode, max	Gage	04001
102.	Assembly damaged	Visual	04002
Minor:	AQL 1.50 percent		
201.	Exterior protective coating with bare spot	Visual	04004
202.	Marking misleading or unidentifiable including incorrect color code	Visual	04005
203.	Evidence of poor workmanship (see 3.7)	Visual	04006

4.2.2.5 Unsealed fiber container (see dwg. 8835040).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Packing component missing	Visual	05001
Minor:	AQL 1.50 percent		
201.	Glue or asphalt on cartridge	Visual	05002
202.	Container assembled improperly	Visual	05003
203.	Cartridge cannot be removed by hand	Manual	05005

4.2.2.6 Sealed fiber container (see dwg. 8835040).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Tape incomplete or badly wrinkled	Visual	06001
102.	Container, cut or damaged through all impregnated layers	Visual-Manual	06002
103.	Metal end loose or distorted	Visual Manual	06003
Minor:	AQL 2.50 percent		
201.	Tear tab length, min	Gage	06004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

202.	Gap exceeding 1/8 inch between cap and body of container	Visual	06005
203.	Marking misleading or unidentifiable	Visual	06006
204.	Cuts, scuffs or gouges in outer layers	Visual	06007
205.	Contents loose	Manual	06008

4.2.2.7 Sealed wood packing box (see dwg. 8835039).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Box damaged exposing contents	Visual	07001
102.	Strapping missing or loose	Visual	07002
103.	Hardware missing, broken or loose	Visual	07003
104.	D.O.D. symbol missing or incorrect	Visual	07004
105.	Board loose or broken	Visual-Manual	07005
Minor:	AQL 2.5 percent		
201.	Car seal missing, unsealed or improperly positioned	Visual	07006
202.	Marking misleading or unidentifiable	Visual	07007
203.	Hardware improperly engaged	Visual-Manual	07008
204.	Strapping improperly assembled	Visual-Manual	07009
205.	Handle missing or insecure	Visual-Manual	07010

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of primers Major defect, Code No. 01003.-If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in the applicable primer specification immediately before the primer lot is assembled into the cartridges (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

4.2.3.2 Primer above flush (see dwg. 8863427) Major defect; Code No. 04013.-The cartridges shall be gaged 100 percent for primer above flush with base of case. Any cartridge which fails to meet the applicable requirement shall be classed defective and be removed from the lot. Equipment shall be in accordance with 4.2.4

4.2.3.3 Propellant weight (see 3.3) Major defect - Code No. 02008.-The propellant shall be weighed and check-weighed 100 percent. The check-weighing shall be accomplished idependently of the original weighing and, if performed manually, shall be performed by another operator. Any propelling charge which fails to comply with the applicable requirement shall be classed defective and removed from the lot subject to correction prior to resubmission. Equipment shall be in accordance with 4.2.4.

4.2.3.4 Electrical resistance (see dwg. 8863427) Major defect Code No. 02009.-The cartridge cases, with primers assembled, shall be tested 100 percent, for resistance. Any case-primer assembly which fails to meet the resistance requirement shall be classed defective and removed from the lot. Testing shall be as specified in 4.3.2, using equipment in accordance with 4.2.4.

4.2.3.5 Profile and alignment (see dwg. 8863427) Major defect - Code No. 04008.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and be removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.6 Cartridge case crimp (bullet pull) (see 3.4 and dwg. 8863427) Major defect - Code No. 04009.

4.2.3.6.1 The sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter F, and AQL 1.5 percent. The test shall be performed as specified in 4.3.1 with equipment in accordance with 4.2.4.

4.2.3.7 Security of sub-projectile (see 3.5).-The cartridges shall be tested 100 percent for loose sub-projectiles. Any cartridge failing to meet the applicable requirements shall be classed defective and removed from the lot. Testing shall be as specified in 4.3.3 with equipment in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

4.2.3.8 Proving ground.-The following tests shall be performed as specified in 4.3.4. These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired in a gun for which the cartridge is standard and observation made for conformance to all applicable requirements.

4.2.3.8.1 Muzzle velocity (see 3.6.1) Major defect - Code No. 04010.

4.2.3.8.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter I and AQL 1.0 percent. In addition, if the standard deviation of the sample cartridge multiplied by the factor 0.75 exceeds the lot requirement, the lot shall be rejected.

4.2.3.8.1.2 After three consecutive lots have met the criteria of 4.2.3.8.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code Letter F, and AQL 1.0 percent. In addition, if the standard deviation of the sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.8.2 Tracer functioning (see 3.6.2), Major defect, Code No. 04011.

4.2.3.8.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.8.1.1) shall be observed for tracer functioning. If three or more sample cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8.2.2 After three consecutive lots have met the criteria of 4.2.3.8.2.1, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.8.1.2) shall be observed for tracer functioning. If two or more sample cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.8.3 Extreme temperature firing (for information only). Code 04014.-Twenty cartridges shall be selected from each of the first three production lots and fired for muzzle velocity, target impact dispersion, and max. chamber pressure information at -40 degrees F (10 rds) and 145 degrees F (10 rds). Tests shall be conducted as specified in 4.3.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

4.2.3.8.4 Safety (see 3.6.3) - Critical defect, Code No. 04012.-All cartridges fired in the proving ground tests shall be observed for premature burst, hangfires or break-up of metal parts. If any cartridge fails to comply with the applicable requirements the lot shall be rejected.

4.2.3.8.5 Target-impact-dispersion (for information only)-The sample cartridges used in the test for muzzle velocity (see 4.2.3.8.1.1 and 4.2.3.8.1.2) shall be observed as specified in 4.3.4.1 for target-impact-dispersion information.

4.2.3.8.6 Retest.-If for any reason the test director considers that the test conditions have detrimentally affected the test results he shall declare the results invalid and perform a new test on additional rounds as required.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-8863427 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation production, and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3 *Test methods and procedures.*

4.3.1 Cartridge case crimp (bullet pull).-The cartridge shall be tested in an appropriate tensile testing machine to determine the security of the crimp of the cartridge case to the projectile. The load shall be applied in the axial direction with the rate of travel of the testing machine head from 0.100 to 0.125 inch per minute.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

4.3.2 Electrical resistance.-The electrical resistance shall be measured between the primer electrode and the cartridge case with a maximum current of 20 milliamperes flowing through the primer.

4.3.3 Security of sub-projectile.-The appropriate fixture shall be assembled to the sub-projectile in a manner such that no rearward pressure is applied to the sub-projectile, and the specified torque applied. Observation shall be made to determine compliance with the applicable requirement.

4.3.4 Proving Ground

4.3.4.1 Muzzle velocity, tracer functioning and target-impact-dispersion.-The sample cartridges shall be fired at 70°F temperature, from a gun for which the cartridge is standard, at a cloth target placed 1000 meters from the muzzle of the gun. Muzzle velocity shall be recorded, tracer functioning shall be observed and the vertical and horizontal target hit pattern results shall be expressed as probable error in mils.

4.3.4.2 Extreme temperature firing.-For this test 10 rounds shall be temperature conditioned at -40 degrees F and 10 rounds shall be conditioned at 145 degrees F for a period of 24 hours prior to firing. The cartridge shall be fired at a cloth target placed 1000 meters from the muzzle of the gun. Muzzle velocity, max. chamber pressure and target-impact-dispersion data shall be recorded.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.-The cartridge shall be preserved and packaged in accordance with dwg. 8835040.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 8835039.

5.3 Marking.-The containers and boxes shall be marked in accordance with dwgs. 8796521 and 8796522.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on the Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment
MU - Army design, mandatory for use

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND12. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.

6.4 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the assemblies or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occured as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Visual examination.-When compliance with the applicable requirements is in doubt, as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

6.6 Submission of test data and ammunition data cards.- In addition to the normal distribution of records, when the cartridge is procured by the Army Munitions Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND2 and SMUPA-DA2, Dover, New Jersey.

6.7 Certain provisions of this specification are the subject of international standardization agreement ABCA-ARMY STD-147. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodian:
ARMY-MU

Preparing Activity:
ARMY-MU

Project Number: 1315-A676

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:14Z
Check the source to verify that this is the current version before use.