MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, M37 ASSEMBLY

This amendment forms a part of Military Specification MIL-C-46221A(MU), dated 6 October 1966, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

In the title of the specification, and wherever it appears in the body of the specification, delete "Aircraft Ejection Seat Catapult" and substitute "Impulse".

PAGE 1

* 2.1 Delete "MIL-E-5272 . . ."
"MIL-STD-639 . . ."
"MIL-STD-1167 . . ."
"Federal Test Method Standard No. 151 . . ." in their entirety.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:15Z
Check the source to verify that this is the current version before use.

PAGE 2

Under DRAWINGS, add:

"C9225381 - Box, Fiberboard (Outer) Alternative, Packing, Ammunition for Cartridge, Impulse, M37."

* Add: "2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018.)

(Nongovernment standards and other publications are normally available from the organization which prepares or which distributes the documents. These documents also may be available in or through libraries or other informational services.)"

3.2 Delete in its entirety.

* 3.3 Delete "MIL-E-5272, Procedure XII . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 . . .".

3.4 Delete in its entirety.

PAGE 3

3.6.2.1 Delete "size 9" and substitute "size 4".

PAGE 4

4.2.1, With Table II, delete in its entirety and substitute:

"4.2.1 Initial production sample. At the beginning of regular production, a sample shall be submitted in accordance with contract requirement and shall consist of 5 cartridges for sealant tests, 21 cartridges for ballistic tests, 12 for vibration tests (to be selected from ballistics sample) and 10 sets of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:15Z
Check the source to verify that this is the current version before use.

unassembled components for dimensional and visual examination and tests. The sample for ballistic tests shall be temperature conditioned and shall conform to the requirements as indicated in Table I. The sample for firing shall consist of the following:

Temperature	Not Vibrated	Vibrated
-65°F to -70°F	3	4
65°F to 75°F	3	4
160°F to 165°F	3	4

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply."

4.2.1.2, With Table III, delete in its entirety.

4.3.2.12 Add:

"4.3.2.12 Box, Fiberboard (Outer) Alternative, Drawing C9225381.

Defect		Method of Inspection
CRITICAL		
None Defined		
MAJOR		
None Defined		
MINOR		
201.	Contents loose	Manual
202.	Box broken or damaged	Visual
203.	Number of units contained incorrect	Visual
204.	Marking missing, incorrect or illegible	Visual
205.	Tape incomplete	Visual"

4.3.1.2, Delete in its entirety and substitute:

"4.3.1.2 Size of lot. An ammunition lot of cartridges shall consist of an identifiable group of cartridge assemblies consisting of:

a. Components produced by a homogeneous process.

b. Propellant from not more than one lot.

c. Igniter from not more than one lot.

d. Primers from not more than one lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:15Z
Check the source to verify that this is the current version before use.

* 4.3.2 Delete "MIL-STD-639" and substitute "ANSI B46.1"

4.3.3.6.1:

a. Delete "Thirty (30)" in first and second line and substitute "Twenty-one (21)".

b. Delete "10 - 10 - 10" under "Sample Size" and substitute "7 - 7 - 7".

* 4.4.1 Delete ". . . MIL-E-5272, Procedure XII" and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I - 3.2.5".

4.4.4 Delete "Federal Test Method Standard No. 151" and substitute "MIL-C-60539".

5.1 Delete in its entirety and substitute:

"5.1 Packing and marking. Packing and marking shall be as specified by the procuring activity.

Level A - Drawings F8797379 and F8797380.
Level B - Drawings F8797379 and C9225381.

5.2 Delete in its entirety.

Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing Activity:
Navy - OS
Project No. 1377-N832

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:15Z
Check the source to verify that this is the current version before use.