INCH-POUND

MIL-DTL-46229D (AR)
28 January 2014
SUPERSEDING
MIL-C-46229C (AR)
29 June 1979

DETAIL SPECIFICATION

CARTRIDGE, 105MM BLANK, M395
LOADING, ASSEMBLING AND PACKING

Inactive for new design after 12 February 1997

This specification is approved for use by the US Army Armaments, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling, and packing for one type of cartridge designed as Cartridge, 105MM, Blank, M395 for Howitzers.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in section 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to the Commander, U.S. Army ARDEC, ATTN: RDAR-QES-E, Picatinny Arsenal, NJ 07806-5000 or emailed to usarmy.picatinny.ardec.list.ardec-stdz-branch@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil

AMSC N/A FSC: 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

2.2 Government documents

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-P-223	-	Powder, Black

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-1168	-	Ammunition Lot Numbering
MIL-STD-1916	-	DoD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at http://quicksearch.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

US ARMY ARMAMENTS, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC) DRAWINGS

7258482	-	Gage, Chamber
7549251	-	Cartridge, 105MM, Blank, M395 Assembly
7549252	-	Wad, Closing
7549253	-	Cup, Closing
7549254	-	Box, Packing, Ammunition for Cartridge 105MM Blank, M395, for Howitzers.
7549255	-	Container, Ammunition, Fiber, M34A1, for Cartridge 105MM, Blank, M395, for Howitzers.
8839474	-	Primer
8845003	-	Case, Cartridge (empty)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

(Copies of these drawings may be requested online at usarmy.picatinny.ardec.list.drawing-request-help-desk@mail.mil or from the U.S. Army ARDEC, ATTN: RDAR-EIS-PE, Picatinny Arsenal, NJ 07806-5000.)

2.2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.1.2 Conformance. A sample shall be subject to conformance inspection in accordance with 4.3.

3.2 Components and assemblies. The components and assemblies shall comply with the requirements specified on drawing 7549251 and subsidiary drawings.

3.3 Ammunition lot number. Ammunition lot number shall be assigned in accordance with MIL-STD-1168.

3.4 Air pressure tests.

3.4.1 Air pressure test of the primer and cartridge case assembly. The cartridge case, with the primer assembled, shall withstand air pressure of not less than 5 psi for not less than 15 seconds without leaking, as evidenced by a drop in gage pressure of not greater than 0.025 psi.

3.4.2 Air pressure test of cartridge assembly. The complete cartridge shall withstand air pressure of not less than 5 psi for not less than 15 seconds without leaking as evidenced by a drop in gauge pressure of not greater than 0.50 psi.

3.5 Functioning (proving ground test).

3.5.1 Safety. There shall be no misfires, hang fires in excess of 1 second or indications of metal parts failure in the gun bore during any of the proving ground tests conducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

3.5.2 Sound level. The cartridge shall function with a sound level of not less than 117 decibels.

3.5.3 Extraction. The cartridge case shall freely extract from the gun after firing.

3.5.4 Fragments. There shall be no case or primer fragments thrown more than 300 feet (92meters) beyond the weapon muzzle. Metal parts separation or breakup is excluded. No metal part failures are acceptable. If any metal part fails, the lot shall be rejected.

3.6 Workmanship.

3.6.1 General. The cartridge and all components shall be free of cracks, burrs which can affect assembly, functioning or prove injurious to personnel handling the item; chips, dirt, grease, rust, corrosions or other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.6.2 Painting and marking. Prior to packaging of cartridges, painting and marking which may have been marred or obliterated during handling shall be restored to meet requirements of applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4 VERIFICATION

TABLE I. Requirement / verification cross-reference matrix.

METHOD OF VERIFICATION 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test						CLASSES OF VERIFICATION A – First Article B - Conformance		
SECTION 3 REQUIREMENTS	DESCRIPTION	VERIFICATION METHOD				VERIFICATION CLASS		SECTION 4 VERIFICATION
		1	2	3	4	A	B	
3.1.1	First article			X	X	X		4.2
3.1.2	Conformance			X	X		X	4.3
3.2	Components and assemblies			X	X	X	X	4.3.2.1 – 4.3.2.13
3.3	Ammunition lot number			X		X	X	4.4
3.4.1	Air pressure test of the primer and cartridge case assembly			X	X	X	X	4.3.2.5
3.4.2	Air pressure test of cartridge assembly			X	X	X	X	4.3.2.8
3.5	Functioning (proving ground test)			X	X	X	X	4.4.2
3.6	Workmanship				X	X	X	4.3.2.1 – 4.3.2.13

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. A sample shall be subjected to first article inspection in accordance with Table II.

4.2.1 First article quantity. First article inspection shall be performed on the quantity of items as indicated in Table II.

4.2.2 First article inspection to be performed. The first article inspection shall be performed in accordance with Table II.

4.2.3 First article rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

TABLE II. First article inspection.

Examination or Test	Number of FAT Samples	Requirement Paragraph	Inspection Method Reference
Cartridge, 105MM, Blank, M395, Assembly (Dwg 7549251)			
Examination for defects	20	3.2	4.3.2.5-4.3.2.8
Proving Ground (1/)	20	3.5	4.3.2.9
Cup, Closing (Dwg 7549253)			
Examination for defects	10	3.2	4.3.2.1
Wad, Closing (Dwg 7549252)			
Examination for defects	10	3.2	4.3.2.2
Case, Cartridge, 105MM, Blank (Dwg 8845003)			
Examination for defects	10	3.2	4.3.2.3
Primer, Percussion (Dwg 8839474)			
Examination for defect	10	3.2	4.3.2.4
Container, Fiber (Dwg 7549255)			
Examination for defect	10	3.2	4.3.2.10, 4.3.2.11
Box, Wood (Dwg 7549254)			
Examination for defect	10	3.2	4.3.2.12, 4.3.2.13

NOTES:
1/ After inspection as per 4.3.2.5 - 4.3.2.8, twenty (20) of the forty-five (45) inspected cartridges shall be selected at random for proving ground tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3 Conformance inspection.

4.3.1 Lot formation. Lot numbering shall be in accordance with the lot formation requirements of MIL-STD-1916 (paragraph on the formation and identification of lots or batches). In addition, each inspection lot of Cartridge 105MM, Blank M395 for Howitzers shall contain:

a. Primer assemblies of one lot interfix number from one manufacturer.

b. Black powder of one lot interfix number from one manufacturer.

c. New or fired cartridge cases modified by one manufacturer, of the same type of metal, from one lot interfix number.

d. Closing cups from one manufacturer in accordance with the same drawing and drawing revision.

e. Closing wads from one manufacturer in accordance with the same drawing and drawing revision.

4.3.2 Classification of characteristics.

a. Sampling requirements. Inspection sampling requirements for critical, major and minor characteristics are defined in MIL-STD-1916. The acceptance criteria for sampling inspection shall be in accordance with the levels provided in the conformance examination/test paragraph and MIL-STD-1916. Unless specified otherwise, Verification Level VII in addition to 100% inspection shall be used for all characteristics defined as critical, Verification Level IV shall be used for all characteristics defined as major and Verification Level II shall be used for all characteristics defined as minor.

b. Conformance inspection. Conformance inspection shall be performed in accordance with paragraph 4.3.2.1 through 4.3.2.13. For all conformance inspection the same sample specimen may be used for all non-destructive examinations or tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.1	Cup, closing.			Drawing Number 7549253 Next Higher Assembly 7549251
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Cup cracked, broken, punctured or malformed	VL-IV	3.2	Visual
Minor				
201	Outside diameter	VL-II	3.2	AIE
202	Hole missing	VL-II	3.2	Visual
203	Evidence of poor workmanship	VL-II	3.6	Visual

4.3.2.2	Wad, closing.			Drawing Number 7549252 Next Higher Assembly 7549251
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major	None defined			
Minor				
201	Outside diameter, min.	VL-II	3.2	AIE
202	Evidence of poor workmanship	VL-II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.3	Case, cartridge (empty).			Drawing Number 8845003 Next Higher Assembly 7549251
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Distance from bottom or primer counter bore to front of seating flange	VL-IV	3.2	AIE
102	Crack or split extending through side wall or bottom	VL-IV	3.2	Visual
Minor				
201	Total length	VL-II	3.2	AIE
202	Incorrect protective finish 1/	VL-II	3.2	Visual
203	Evidence of poor workmanship	VL-II	3.6	Visual
1/ Applicable to steel cases only.				

4.3.2.4	Primer, prior to assembling into case.			Drawing Number 8839474 Next Higher Assembly 7549251
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical				
1	One or more primer flash holes missing	100% + VL-VII	3.2	AAIE
Major				
101	Assembly incomplete or improper	VL-IV	3.2	Visual/manual
102	Primer deterioration	VL-IV	3.2	4.4.3
Minor				
201	Evidence of poor workmanship	VL-II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.5	Cartridge, 105MM Blank M395 Assembly (primer case).			Drawing Number 7549251 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical 1	Primer above flush	100% + VL-VII	3.2	AAIE
Major 101	Primer loose	VL-IV	3.2	Visual/manual
102	Air pressure test of case	VL-IV	3.4	AIE
Minor 201	Foreign matter on interior	VL-II	3.6	Visual

4.3.2.6	Cartridge, 105MM Blank M395 Assembly (prior to inserting closing wad).			Drawing Number 7549251 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major 101	Black powder moisture content (see dwg 7549251)	1/	3.2	4.4.1
102	Black powder missing or inadequate	VL-IV	3.2	Visual
Minor 201	Evidence of poor workmanship	VL-II	3.6	Visual
1/ Select sample in accordance with MIL-P-223. Select one (1) sample randomly from each production shift. Failure to comply with the specified requirement shall be cause for rejection of the production shift represented by the sample.				

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.7	Cartridge, 105MM Blank M395 Assembly (after inserting wad and closing cup).			Drawing Number 7549251 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Seal not continuous or groove not filled with adhesive	VL-IV	3.2	Visual
102	Air escape hole not filled with adhesive	VL-IV	3.2	Visual
Minor				
201	Evidence of poor workmanship	VL-II	3.6	Visual

4.3.2.8	Cartridge, 105MM Blank M395 Assembly.			Drawing Number 7549251 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Air pressure test of cartridge assembly	100%	3.4	AIE
102	Chamber gage failure (profile and alignment)	VL-IV	3.2	Dwg. 7258482
103	Assembly damaged or improper	VL-IV	3.2	Visual
104	Closing cup cracked, loose or damaged	VL-IV	3.2	Visual/Manual
105	Wax Emulsion missing or inadequate	VL-IV	3.2	Visual
Minor				
201	Marking missing, incorrect, or illegible	VL-II	3.2	Visual
202	Adhesive or other foreign material on exterior of cartridge	VL-II	3.2	Visual
203	Evidence of poor workmanship	VL-II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.9	Cartridge, 105MM Blank M395 Assembly (proving ground).			Drawing Number 7549251 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical				
1	Hang fire	\1	3.5.1	4.4.2
2	Fragments	\1	3.5.4	4.4.2
Major				
101	Misfire	\1	3.5.1	4.4.2
102	Sound level	\1	3.5.2	AIE/4.4.2
103	Extraction	\1	3.5.3	Manual/4.4.2
Minor				
201	None defined			
\1 A quantity of 20 shall be fired for first article and 20 from the first three consecutively produced lots. If no failures occur, the sample size shall be reduced to 10 for subsequent lots. If any subsequent lot failures occur, the 20 samples size shall be reinstated until such time as three consecutive acceptable lots are produced. The lot shall be rejected if any major defect occurs.				

4.3.2.10	Fiber container (unsealed).			Drawing Number 7549255 Next Higher Assembly 7549254
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Packing component missing	VL-IV	3.2	Visual
Minor				
201	Round cannot be removed by hand	VL-II	3.2	Manual
202	Round improperly assembled in container	VL-II	3.2	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.11	Fiber container (sealed container).			Drawing Number 7549255 Next Higher Assembly 7549254
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Tape incomplete or inner layer not in contact with the surface of the container for at least ½ inch on each side of joint.	VL-IV	3.2	Visual
102	Metal end loose or distorted	VL-IV	3.2	Manual
103	Container damaged through all impregnated asphalt layers as evidenced by removing each layer of suspected container.	VL-IV	3.2	Visual
104	DODIC marking missing, incorrect or illegible	VL-IV	3.2	Visual
Minor				
201	Length of tear tab, min.	VL-II	3.2	Visual
202	Color of tape incorrect.	VL-II	3.2	Visual
203	Marking misleading or unidentifiable.	VL-II	3.2	Visual
204	Cut, scuffs or gouges in outer layer.	VL-II	3.2	Visual
205	Gap between body and cover of container exceeding 1/8 inch.	VL-II	3.2	Visual/AIE
206	Contents loose upon shaking.	VL-II	3.2	Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.12	Wood box (prior to sealing).			Drawing Number 7549254 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Incorrect number of components	VL-IV	3.2	Visual
102	Containers improperly positioned	VL-IV	3.2	Visual
103	Packing material insufficient	VL-IV	3.2	Visual
Minor				
201	Evidence of poor workmanship	VL-II	3.6	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.3.2.13	Wood box (sealed packing box).			Drawing Number 7549254 Next Higher Assembly
Classification	Examination or Test	Conformance Criteria	Requirement Paragraph	Inspection Method Reference
Critical	None defined			
Major				
101	Strapping missing or loose	VL-IV	3.2	Visual/manual
102	Hardware missing or loose	VL-IV	3.2	Visual/manual
103	Contents of box exposed	VL-IV	3.2	Visual
104	NSN and DODIC marking missing, incorrect or illegible	VL-IV	3.2	Visual
105	Board broken or split	VL-IV	3.2	Visual
106	Metallic seal missing or broken	VL-IV	3.2	Visual
Minor			3.2	
201	Hasp improperly engaged	VL-II	3.2	Visual/manual
202	Strapping improperly assembled	VL-II	3.2	Visual/manual
203	Marking missing, incorrect or illegible	VL-II	3.2	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

4.4 Methods of inspection

4.4.1 Moisture content of black powder. The moisture content of the black powder shall be determined in accordance with the procedure specified in specification MIL-P-223.

4.4.2 Ballistic test.

4.4.2.1 First article and initial production. The test shall be conducted in accordance with 4.4.2.3. Beginning with the first lot produced and continuing until three consecutive lots have complied with all the acceptance criteria contained herein, 20 sample cartridges shall be selected at random from each lot for this test. The 20 sample cartridges shall be conditioned and fired at 70°F±2.5° (21°C±1.5°). Items shall be temperature conditioned for a minimum of 24 hours. If any cartridge fails to comply with the requirements of 3.5, the lot shall be rejected.

4.4.2.2 Production lot samples. After three consecutive lots have complied with 4.4.2.1, 10 sample cartridges shall be selected at random for this test. The 10 sample cartridges shall be conditioned and fired at 70°F±2.5° (21°C±1.5°). Items shall be temperature conditioned for a minimum of 24 hours. If any cartridge fails to comply with the requirements of 3.5, the lot shall be rejected. In the event that a lot fails to meet all the requirements of this paragraph, the provisions of 4.4.2.1 shall again apply until three successive lots meet the requirements specified therein.

4.4.2.3 Functioning. This test shall be conducted at a proving ground. The cartridge shall be fired in accordance with the applicable test procedure. The cartridge shall be fired in an M137A1 cannon or equivalent. The cartridge test rounds shall be uniformly temperature conditioned at 70°F±2.5° (21°C±1.5°) for a minimum of 24 hours prior to testing. When measuring sound level, the pick-up microphone shall be located 100 feet (30.48 meters) from the gun muzzle on a line perpendicular to the axis of the tube. Firing shall be made to an asphalt pad or equivalent. Observation shall be made for compliance with 3.5.

4.4.3 Check test for possible deterioration of primers (see applicable primer specification). If the total elapsed time between the original acceptance of any primer lot and the assembly of the lot into complete cartridges exceeds three years or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and shall satisfactorily pass the check test specified in the applicable primer loading specification immediately before the primer lot is assembled into cartridges (see 6.4).

4.4 Ammunition lot number. Visually verify that an ammunition lot number has been applied to each lost as described in MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contract the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Case, Cartridge, 105MM Blank, M395 Assembly is intended for use in the family of 105MM artillery weapons.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Characteristic code number.
c. Packaging requirements (see 5).
d. Requirements for submission of first article sample (see 6.8).
e. Requirement for submission of acceptance inspection equipment (see 6.3).
f. Certificate of conformance for each lot or shipment of product.
g. Applicable stock number.
h. Sample requirements for check test for deterioration of primer, percussion M61 assembly (see 6.4).
i. Data cards should be prepared for each lot in accordance with the information specified in Standard MIL-STD-1168.

6.3 Submission of contractor acceptance inspection equipment (AIE) designs for approval. Submit copies of designs as required to: Commander, U.S. Army Armaments, Research, Development and Engineering Center (ARDEC), ATTN: RDAR-QEM-A, Picatinny Arsenal, New Jersey 07806-5000. This address should be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Cost of primer check test (see 4.4.3). The contracting officer should arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test should be conducted at Government expense without cost to the contractor who loaded the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

primers or the contractor assembling the cartridge, and should not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic in question may be measured or gaged to determine acceptability.

6.6 Alternative testing procedures. Alternative testing procedures may be used by the contractor. The contractor should describe these alternative procedures in a written proposal and should demonstrate for the approval of the responsible Government technical agency that their effectiveness is equal to, or better than the quality assurance provisions specified herein.

6.7 Proving ground test summary.

Test	Sample Size	Temperature
First Article	20	70°±2.5°F (21°±1.5°C)
First Three Lots	20	70°±2.5°F (21°±1.5°C)
Subsequent Lots	10	70°±2.5°F (21°±1.5°C)

6.8 Submission of ballistic test data and ammunition data cards. In addition to the normal distribution of records for items procured by the Department of the Army one copy of all ballistic test data and ammunition data cards should be forwarded to Commander, ARDEC, ATTN: RDAR-QEM-A, and RDAR-MEM-C, Picatinny, NJ 07806-5000. Test records should show test results for individual items.

6.9 Critical classification notes.

6.9.1 One or more primer flash holes missing (see 4.3.2.4). Flash holes missing may cause improper functioning of the primer. The primer may become detached from the cartridge case, leaving material debris in the gun tube. Flash holes missing may also result in improper initiation of the propellant resulting in high or low pressure. This is likely to cause primer to act as a projectile which may result in injury or potential death of troops.

6.9.2 Primer above flush (see 4.3.2.5). Primer above flush may cause functioning of the primer upon closing of the breech or mishandling of the round leading to inadvertent injury or potential death of troops.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

6.9.3 Hangfire (see 4.3.2.9). The primer should function without hang fire in excess of 1 second. During firing, a hang-fire malfunction may occur leading to inadvertent injury or potential death of troops from unexpected recoil of breech.

6.9.4 Fragments (see 4.3.2.9). Fragmentation of case or primer exiting the gun in excess of 300 feet of the muzzle may lead to inadvertent injury or potential death of troops.

6.10 Supersession data. This specification supersedes MIL-C-46229C (AR) dated 29 June 1979 and amendment 3 of MIL-C-46229C (AR) dated 17 January 2001.

6.11 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

6.12 Definitions.

a. Acceptance Inspection Equipment (AIE). Any measuring device that is traceable to the national or international standard which is used to assure conformance of material to the contract requirements.

b. Automated Acceptance Inspection Equipment (AAIE). Equipment for which no, or minimal, human involvement is required in the acceptance determination. This includes equipment employing probes/sensors/transducers that are automatically manipulated to perform measuring and detection functions.

c. Hangfire. A hangfire is a delay in the functioning of a propelling charge at the time of firing or lanyard pull.

d. Misfire. A misfire is a complete failure to fire and may be due to a faulty firing mechanism or faulty element in the propelling charge explosive train.

6.13 Subject term (key word) listing.

Cup, closing
Wad, closing
Primer
Gage, Chamber
Flash holes
Air pressure
Sound level

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

Custodian:
Army- AR

Preparing Activity:
Army- AR
(Project 1315-2013-011)

Note: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.