MILITARY SPECIFICATION

DETONATOR, ELECTRIC, T44
METAL PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of detonator designated as Detonator, Electric, T44.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification, to the extent specified herein.

SPECIFICATIONS

FEDERAL

UU-T-111 - Tape, Paper, Gummed, (Sealing and Securing).
LLL-B-631 - Boxes; Fiber Corrugated (For Domestic Shipment).

MILITARY

JAN-P-120 - Packaging and Packing for Overseas Shipment-Cartons, Folding Paperboard.
MIL-G-2550 - General Specification for Ammunition Except Small Arms Ammunition.
MIL-P-10025 - Packing and Marking for Domestic Shipment of Inert Ammunition Components; General Specification.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Inspection Terms and Definitions

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8838102 - Detonators, Electric, T44 Assembly and Details
PX-89-1394 - Marking Diagram and Label Diagram for Carton for Assemblies of One Kind
PX-89-1395 - Marking Diagram and Label Diagram for Carton for Single Parts of One Kind
PX-89-1396 - Marking Diagram and Label Diagram for Carton for Metal Parts

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedure and Tables for Continuous Sampling by Attributes
IEL-8792763 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Metal parts.-The metal parts shall comply with all requirements specified on Drawing (dwg.) 8792763, and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be free of chips, dirt, rust, grease, and other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. Inspection shall be performed in accordance with this specification and other specifications referenced in any of the contractual documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies procured under this specification and shall perform all inspections required by the system. A current written description of the system shall be submitted to the contracting officer, and meet his approval, prior to initiation of production. It shall include a description covering controls for lot formation and identification, inspections to be performed, inspection stations, sampling procedures, methods of inspection (gages, measuring and testing equipment) and provisions for control and disposition of non-conforming material. The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by the provisions of 4.2.2 and 4.3 and the other documents referenced herein. The contractor shall not be restricted to the inspection station or the method of inspection listed in this specification provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether certain procedures of the contractor's system provide equal assurance, the comparable procedure of this specification shall apply. The contractor shall notify the Government of, and obtain approval for, any change to the written procedure that affects the degree of assurance required by this specification or other documents referenced herein.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

b. Number of units of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of analysis on all material procured directly by the contractor.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification shall consist of: (a) surveillance of contractor operations to determine that the methods and procedures of the written procedure are being properly applied, and (b) Government product inspection. The Government inspector shall also ascertain prior to acceptance that all quality assurance provisions of other specifications referenced in any of the contractual documents have been complied with.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

4.1.3.1 Surveillance.-Surveillance shall include, but is not limited to:

a. Observation of procedures concerning lot formation and identification.

b. Observation of sampling procedures and application of acceptance criteria.

c. Determination that all required examinations and tests are performed in accordance with the prescribed procedures of this specification, or approved equivalents thereto.

d. Review of procedures for control and disposition of non-conforming material.

4.1.3.2 Product inspection.-Physical inspection by the Government of contractor accepted product will be performed to the extent necessary to assure contractor compliance with the requirements of this specification and to determine the reliability of contractor records. Severity of Government inspection of individual characteristics will be directly related to the seriousness classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records, Specification MIL-G-2550 shall apply.

4.1.3.3 Deviation and deficiencies.-Deviations from the prescribed or agreed upon procedures, or instances of poor practice which might have an effect on the quality of the product, shall be called to the attention of the contractor immediately. To avoid interference with operations, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances. Failure of the contractor to promptly correct deficiencies shall be cause for suspension of acceptance until correction has been made or until conformance to prescribed criteria has been demonstrated.

4.2 Inspection provisions.

4.2.1 Lot formation.-A lot shall consist of metal parts produced by one manufacturer in one unchanged process in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification and process changes not affecting performance, safety or fit, as determined by the Government, shall not be cause for changing the lot number.

4.2.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that for critical defects, when listed, inspection shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

4.2.2.1 Cup (see dwg. 8838115).

Categories	Defects	Method of inspection
Critical:		
	1. Split, cut or crack through cup	Visual
Major:	AQL 0.65 percent	
	101. Thickness through bottom	Gage
	102. Inside diameter, minimum (min.)	Gage
	103. Outside diameter, maximum (max.)	Gage
	104. Total length	Gage
	105. Cup dented or distorted	Visual
	106. Deep scratch or groove in cup	Visual
Minor:	AQL 1.50 percent	
	201. Radius missing	Visual
	202. Finish incorrect	Visual
	203. Evidence of poor workmanship (see 3.3)	Visual

4.2.2.2 Ferrule (see dwg. 8838110).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.25 percent	
	101. Outside diameter, max	Gage
Minor:	AQL 1.50 percent	
	201. Inside diameter, min	Gage
	202. Chamfer missing from inside diameter	Visual
	203. Evidence of poor workmanship (see 3.3)	Visual

4.2.2.3 Plug (see dwg. 8838109).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.25 percent	
	101. Inside diameter, min	Gage
Minor:	AQL 1.50 percent	
	201. Taper	Gage
	202. Diameter of chamfer at face	Gage
	203. Evidence of poor workmanship (see 3.3)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

4.2.2.4 Plug assembly (see dwg. 8838112).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.65 percent	
101.	Resistance between plug and pin, min (see 4.3.1).....	Approved test
102.	Push test of pin (see 4.3.2).....	Approved test
103.	Chamfer between pin and plug at bridge end.....	Gage
104.	Length of plug, max.....	Gage
105.	Large outside diameter of plug.....	Gage
106.	Excess bonding material in gap.....	Visual
Minor:	AQL 1.50 percent	
201.	Height of pin.....	Gage
202.	Small outside diameter of plug, max.....	Gage
203.	Evidence of poor workmanship (see 3.3).....	Visual

4.2.2.5 Carton, prior to sealing (see paragraphs 5.1.1.1, 5.1.1.2 and 5.1.1.3).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.25 percent	
101.	Incorrect number of components.....	Balance
Minor:	AQL 0.40 percent	
201.	Incorrect number of cartons.....	Visual

4.2.2.6 Sealed carton (see 5.2).

Categories	Defects	Method of inspection
Critical: None defined		
Major:	AQL 0.25 percent	
101.	Contents loose.....	Manual
102.	Tape incomplete or improperly applied.....	Visual
Minor:	AQL 1.50 percent	
201.	Carton damaged.....	Visual
202.	Flaps loose or insecure.....	Visual
203.	Marking misleading or unidentifiable.....	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment.-For the performance of the examinations and tests specified in 4.2.2 and 4.3, when applicable, the contractor shall have available, and utilize correctly, all necessary gages, measuring and testing equipment identified by Index of Inspection Equipment No. 8792763, or approved equivalents thereto. In inspecting the contractor's inspection equipment, the Government inspector will determine that the contractor has available, and utilizes correctly, gages, measuring and testing equipment of the required accuracy and precision and that the instruments are of the proper type and range to make measurements of the required accuracy. The contractor will have available a set of master gages, standards and appropriate instruments for regularly scheduled calibration of his inspection equipment. Records of such regularly scheduled calibration will be maintained by the contractor and made available for review by the Government. The calibration of gages, standards and instruments will be periodically checked by authorized Government personnel.

4.3 Test methods and procedures.

4.3.1 Resistance between the plug and pin.-A direct current (d.c.) of 325 minus 50 volts shall be applied to the representative plug assemblies selected in accordance with 4.2.2.4, using the test circuit specified in 4.2.3. The electrical resistance shall be measured to determine compliance with the requirement specified.

4.3.2 Push test of pin.-The representative plug assemblies, selected in accordance with 4.2.2.4 shall have the axial force specified on the drawing applied to the contact end of the pin. Observation shall be made to determine that the pin withstands the force without any indication of the pin slipping within the plug.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C.-The inner cartons shall be constructed of 130 pound test paperboard complying with Style III, Type B, Class a, of Specification JAN-P-120. The inside dimensions of the carton shall be 7 1/2 by 7 1/2 by 3 1/4 inches.

5.1.1.1 Cups (8838115).-Ten thousand cups plus overage shall be packaged in a carton constructed as specified in 5.1.1.

5.1.1.2 Plug assemblies (8838112).-Ten thousand plug assemblies plus overage shall be packaged in a carton constructed as specified in 5.1.1.

5.1.1.3 Ferrule (8838110).-Ten thousand ferrules plus overage shall be packaged in a carton constructed as specified in 5.1.1.

5.2 Packing.

5.2.1 Level C.-One carton each, of cups, ferrules, and plug assemblies shall be packed in an RSC Style "B", 275 pound test, double-faced corrugated fiberboard carton constructed as specified in 5.2.2. The inside dimensions of the carton shall be 12 by 6 3/8 by 5 5/8 inches. Interior dunnage shall be used to pack cartons tightly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

5.2.2 Packing requirements.-The construction of the cartons and the material requirements of the carton shall comply with Specification LLL-B-631. When assembled, the corrugations of the carton shall parallel the carton depth. The manufacturer's joint on the carton shall be stapled or stitched. Spacing of staples or stitches shall not average over 1 1/2 inches apart center to center. A manufacturing tolerance of plus or minus 1/16 inch is permissible. Minor modifications of packing material dimensions to provide for a closer pack, as determined to be necessary by examination of sample packs, are permissible.

5.2.3 Sealing.-The carton flaps shall be secured with gummed Kraft paper not less than 1 inch wide complying with Specification UU-T-111 for Class 2 tape. The tape shall be centered the full length of the outer flap seams and extend over each end of the carton at least 3 inches. The flap edge seams shall be similarly sealed with tape extending at least 3 inches along the corners of the carton. Tape shall be properly moistened and sufficiently compressed to insure tight adhesion to the carton.

5.2.4 Marking.-Marking of the cartons shall comply with Specification MIL-P-10025. Printing shall be in Franklin Gothic Type, with black ink on gummed white paper labels approximately 3 by 3 inches in size. See label diagram PX-89-1396 for minimum permissible type sizes.

5.3 Data cards.-Data card information shall be as specified in Specification MIL-G-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing activity:
Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.