MIL-I-46231B (MU)
AMENDMENT I
26 February 1965

MILITARY SPECIFICATION

IGNITER, ROCKET MOTOR, T21E2
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-I-46231B (MU), dated 27 September 1963.

Page 1, paragraph 2.1, delete reference specification MIL-I-45208.- "Inspection Requirements, General Specification for".

Page 3, change paragraph 3.6 to read as follows:

"3.6 Workmanship.-All parts shall be free of surface defects, dirt, grease, and other foreign matter. There shall be no cracks, scratches, burrs, dents, gouges, holes, porous areas, distortions, or other undesirable characteristics which would in any way detract from the useability of the product for its intended purpose. The cleaning method shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required marking shall be neat and sharply defined."

Page 3, delete paragraph 4.1.1 in its entirety.

Page 3, renumber paragraph 4.1.2 and change to read as follows:

"4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specification referenced in any of the contractual documents.

f. Number of items in the lot.

g. Data submitted

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization."

Page 3, renumber paragraph 4.1.3 and change to read as follows:

"4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detailed specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records."

Page 5, paragraph 4.3.2, change Major defect AQL from "0.25 percent" to "0.40 percent" and Minor defect AQL from "0.40 percent" to "0.65 percent".

Page 6, paragraph 4.3.2.1, change Major defect AQL from "0.40 percent" to "0.65 percent".

Page 6, paragraph 4.3.2.2, change Major defect AQL from "0.40 percent" to "1.00 percent".



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

Page 6, paragraph 4.3.2.2, add major defect:
"105. Cutouts do not align.....Visual" 02010

Page 7, paragraph 4.3.2.3, change Major defect AQL from "0.40 percent" to "0.65 percent" and Minor defect AQL from "0.40 percent" to "0.65 percent".

Page 7, paragraph 4.3.2.4, change Major defect AQL from "0.40 percent" to "0.65 percent" and Minor defect AQL from "0.40 percent" to "0.65 percent".

Page 7, paragraph 4.3.2.5, change Major defect AQL from "0.65 percent" to "1.00 percent" and Minor defect AQL from "0.40 percent to "0.65 percent".

Page 12, paragraphs 6.3.2 through 6.3.6, delete in entirety and substitute the following:
"6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designed in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.

supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1340-A182



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:17Z
Check the source to verify that this is the current version before use.