MIL-P-46235A(MU)
1 MARCH 1964

SUPERSEDING
MIL-P-46235(ORD)
20 JUNE 1960

MILITARY SPECIFICATION

PROPELLANT, M26 (T28) FOR USE IN CARTRIDGES M344 AND M346, IN 106MM RIFLES

1. SCOPE

1.1 This specification covers the M26 (T28) propellant for use in propelling charge for 106MM rifle ammunition.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 —Ammunition and Special Weapons; General Specification for

MIL-I-45208 —Inspection Requirements; General Specification for

STANDARDS

MILITARY

MIL-STD-105D —Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-109 —Quality Assurance Terms and Definitions

MIL-STD-414 —Sampling, Procedures and Tables for Inspection by Attributes

MIL-STD-652 —Propellants, Solid for Cannon Requirements and Packing

MIL-STD-1235 —Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

7549097 —Cartridge, 106MM, M344A1, W/Fuze, PI, BD, M509 for 106MM Rifle M40A1, Assembly and Marking Diagram.

8837335 —Cartridge, HEP-T, M346A1 for 106MM Rifle M40A1 Assembly and Marking Diagram.

7549033 —Container, Metal, Universal, M25 for Propellants and Explosives, Assembly and Details.

8858577 —Marking Diagram and Sealing of Container, Metal, Universal, M25 for Shipment of Propellant.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 **Material.** The propellant shall be M26 (T28), Type II, and conforming to the requirement of Standard MIL–STD–652. Test data shall be reported in accordance with 6.5.

3.2 **Ballistics.** The propellant, when fired in the weapon and with the weight of projectile for which it was manufactured, shall comply with the following requirements when tested as specified in 4.3.1.

Weapon	*Round*	*Complete Round Drawing No.*
106MM/M40A1	HEAT–M344A1	7549097
107MM/M40A1	EP–M346	8837335

* feet per second.
** pounds per square inch.

3.2.1 *Velocity and pressure.* At 70° F. the propellant shall be assessed to comply with a prescribed service velocity without exceeding a maximum rated pressure as specified in the following table.

Prescribed Service Velocity	*Maximum Rated Pressure (Piezo Equiv)*
1650 f.p.s.*	11,100 p.s.i**
1650 f.p.s	11,100 p.s.i

3.2.2 *Uniformity of velocity.* The standard deviation in velocity for the lot, at 70 degrees Fahrenheit, shall not exceed 9.40 f.p.s.

3.3 **Workmanship.** The best commercial practices shall be used in the formulation of the propellant furnished under this specification and all other applicable documents. The propellant and its standard ingredients shall be protected from the action of direct sunlight and acid fumes.

4. QUALITY ASSURANCE PROVISIONS

4.1 **General quality assurance provisions.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL–STD–109 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL–I–45208.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
(b) Number of units of product inspected.
(c) Results obtained for all inspection performed.
(d) Drawing, specification number and date, together with an identification and date of changes.
(e) Certificates of analysis on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
(f) Number of items in the lot.
(g) Date submitted.
(h) Eight copies of propellant description sheet, 00 Form 1204, containing the applicable data.

Source: https://assist.dla.mil -- Downloaded: 202640-22T05:18Z
Check the source to verify that this is the current version before use.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL–I–45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 **Inspection provisions.**

4.2.1 *Lot formation.* A lot shall consist of one or more batches of M26 (T28) Propellant produced by one manufacturer, in accordance with the same specification or same specification revision, under one continuous set of operating conditions. Each batch shall consist of that quantity of M26 (T28) Propellant which has been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous. Product shall be submitted for inspection in accordance with Standard MIL–STD–105D (or Standard MIL–STD–1235 when applicable).

4.2.2 *Testing.*

4.2.2.1 *Ballistics* (see 3.2) *Major defect.* A sample of 115 pounds of the propellant shall be randomly selected from the lot for the ballistic test which will be performed at a Government proving ground.

4.2.2.1.1 *Pressure* (see 3.2.1). If the pressure of the test rounds, when calculated and corrected to the corresponding Piezo equivalent at service velocity, exceeds the applicable requirement, the lot shall be rejected.

4.2.2.1.2 *Velocity uniformity* (see 3.2.1). If the product of the factor 0.69 times the velocity standard deviation of the test rounds exceeds the applicable requirement, the lot shall be rejected (see 6.3).

4.2.2.2 *Retest.* If for any reason the proof director considers that the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test on additional charges as required.

4.3 **Test methods and procedures** (see 6.5).

4.3.1 *Ballistic tests.* These tests shall be conducted at a Government proving ground in accordance with the applicable Ordnance Proof Manual and Acceptance Test Procedure. A weight of charge shall be calculated (from closed bomb tests or from charge velocity and charge-pressure curves representing actual rifle firing data) to give prescribed service velocity. A seven round uniformity series shall then be fired and the mean pressure (Piezo Equiv) and velocity variance shall be calculated. When the mean velocity of the uniformity series differs by more than 1.2 percent from the prescribed velocity, re-evaluation of the established charge and a new uniformity series shall be accomplished.

5. PREPARATION FOR DELIVERY

5.1. Packing and marking. The propellant shall be packed and marked in accordance with Standard MIL–STD–652 or dwgs. 7549033 and 8858577.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.

(b) Process. Details of the manufacturing process and the equipment

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.

used by the contractor will be submitted to the procuring activity in writing prior to commencement of manufacture. Any deviation from this manufacturing process must be submitted in writing to the procuring activity prior to being put into effect.

6.2 **Standard deviation.** The standard deviation will be calculated with (N–1) as the divisor in a standard statistical technique to that shown on Standard MIL–STD–414, Section B; Example B–1.

6.3 **Factor 0.69.** The factor 0.69 makes allowance for the probability that a standard deviation from a seven (7) round sample exceeds the true standard deviation by chance alone.

6.4 **Reliability testing.**

6.4.1 For informational purposes only, a seven round uniformity series shall be fired on rounds which were conditioned for a minimum of 24 hours at minus 65° F. before firing.

6.4.2 For informational purposes only, a seven round uniformity series shall be fired on rounds which were conditioned for a minimum of 15 days at 160° F. before firing.

6.5 **Submission of test data.** In addition to the normal distribution of records when the propellant is procured by the Department of the Army, one copy of all test data will be forwarded to the:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA–ND2
Dover, New Jersey

6.6 **Inspection code numbers.** The five digit code numbers assigned to the inspection herein are to facilitate future data collection and analysis by the Government.

Custodian:
Army—MU

Preparing activity:
Army—MU

Project No. 1375–A702

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:18Z
Check the source to verify that this is the current version before use.