The documentation and process conversion measures necessary to comply with this revision shall be completed by 2 October 1999.

INCH-POUND

MIL-PRF-19500/428C
2 July 1999
SUPERSEDING
MIL-S-19500/428B
5 March 1993

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, FIELD-EFFECT TRANSISTOR, N-CHANNEL SILICON,
TYPE 2N4416A
JAN, JANTX, JANTXV AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for N-channel, junction, silicon field-effect transistors. Three levels of product assurance are provided for the device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1.

1.3 Maximum ratings.

Types	P_T 1/ T_A = 25°C	V_{DG} and V_{DS}	V_{GS}	I_G	T_{STG} and T_{OP}
	mW	V dc	V dc	mA dc	°C
2N4416A	300	35	-35	10	-65 to +200

1/ Derate linearly, 1.7 mW/°C for T_A = 25°C.

1.4 Primary electrical characteristics at T_A = 25°C.

Limit	I_{DSS} 1/ V_{DS} = 15 V dc V_{GS} = 0	$V_{GS(off)}$ V_{DS} = 15 V dc I_D = -1.0 nA dc	F	
			V_{DS} = 15 V dc I_D = 5 mA dc R_G = 1 k ohms f = 100 MHz	V_{DS} = 15 V dc I_D = 5 mA dc R_G = 1 k ohms f = 400 MHz
	mA dc	V dc	dB	dB
Minimum	5.0	-2.5		
Maximum	15.0	-6.0	2	4

1/ Pulsed (see 4.4.1)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Defense Supply Center Columbus, ATTN: DSCC-VAT, 3990 East Broad St., Columbus, OH 43216-5000, by using the addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5961
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics at T_A = 25°C - Continued.

Limit	$\|y_{fs}\|$ 2/ V_{DS} = 15 V dc V_{GS} = 0 f = 1 kHz	$\|y_{os}\|$ 2/ V_{DS} = 15 V dc V_{GS} = 0 f = 1 kHz	C_{oss} V_{DS} = 15 V dc V_{GS} = 0 f = 1 MHz	C_{iss} V_{DS} = 15 V dc V_{GS} = 0 f = 1 MHz	C_{rss} V_{DS} = 15 V dc V_{GS} = 0 f = 1 MHz
	ms	µs	pF	pF	pF
Minimum	4.5				---
Maximum	7.5	50	2	4	0.8

2/ Pulsed width = 100 ms; duty cycle = 10 percent.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

STANDARD

MILITARY

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated specifications or specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Associated specification. The individual item requirements shall be in accordance with MIL-PRF-19500, and as specified herein.

3.2 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-19500.


$R_{G'}$ - - - - - - - - - - - - - Transformed equivalent source resistance.

3.3 Interface requirements and physical dimensions. The Interface requirements and physical dimensions shall be as specified in MIL-PRF-19500, MIL-HDBK-6100, and herein.

3.3.1 Lead finish. Lead finish shall be solderable as defined in MIL-PRF-19500, MIL-STD-750, and herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

Ltr	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
HD	.209	.230	5.31	5.84	
CD	.178	.195	4.52	4.95	
CH	.170	.210	4.32	5.33	
LL	.500	.750	12.70	19.05	7
LD	---	.021	---	0.53	2, 7
LU	.016	.019	0.41	0.48	3, 7
TL	.028	.048	0.71	1.22	6
TW	.036	.046	0.91	1.17	



NOTES:
1. Metric equivalents are given for general information only.
2. Measured in the zone beyond .250 (6.35 mm) from the seating plane.
3. Measured in the zone .050 (1.27 mm) and .250 (6.35 mm) from the seating plane.
4. When measured in a gauging plane .054 +.001, - .000 (1.37 +0.03, -0.00 mm) below the seating plane of the transistor, maximum diameter leads shall be within .007 (0.18 mm) of their true location relative to a maximum width tab. Smaller diameter leads shall fall within the outline of the maximum diameter lead tolerance.
5. The gate shall be electrically connected to the case.
6. Measured from the maximum diameter of the actual device.
7. All four leads.
8. Lead 1 = source, lead 2 = drain, lead 3 = gate. lead 4 = case.

FIGURE 1. Physical dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

3.4 Marking. Devices shall be marked in accordance with MIL-PRF-19500. At the option of the manufacturer, the marking of the country of origin may be omitted from the body of the transistor.

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I.

3.7 Qualification. Devices furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.4).

4. VERIFICATION

4.1 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3)

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.3 Screening (JANS, JANTX, AND JANTXV levels only). Screening shall be in accordance with MIL-PRF-19500 (table IV), and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTX and JANTXV levels
9 and 10	Not applicable	Not applicable
11	I_{GSS1}, I_{DSS}, and $\|y_{fs}\|_2$	I_{GSS1}, I_{DSS}, and $\|y_{fs}\|_2$
12	See 4.3.1	See 4.3.1
13	Subgroups 2 and 3 of table I herein; ΔI_{DSS} = 10 percent of initial value. $\Delta\|y_{fs}\|_2$ = 20 percent of initial value.	Subgroup 2 of table I herein; ΔI_{DSS} = 10 percent of initial value. $\Delta\|y_{fs}\|_2$ = 20 percent of initial value.

4.3.1 Power burn-in conditions. Power burn-in conditions are as follows:

MIL-STD-750 method 1039, condition A; T_A = +175°C; V_{GS} = -24 V dc; V_{DS} = 0 V dc.

4.4 Quality conformance inspection. Quality conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. Group A inspection shall be performed on each sublot.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables VIa (JANS) and VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and paragraphs 4.4.2.1 and 4.4.2.2 herein. Electrical measurements (end-points) shall be in accordance with the applicable inspections of table I, group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

4.4.2.1 Group B inspection, table VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	2037	test condition A.
B4	1037	P_T = 300 mW at T_A = +25°C; t_{on} = t_{off} = 3 minutes minimum for 2,000 cycles. No heat sink or forced air cooling shall be permitted.
B5	2037	(Al-Au die interconnects only) is test condition A.
B5	1027	V_{DS} = 15 V dc; I_D = 20 mA dc at T_A = 100°C or adjusted as required by the chosen T_A to achieve an average lot T_J = +275°C.

4.4.2.2 Group B inspection, table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1027	V_{GS} = -24 V dc; V_{DS} = 0; T_A = +175°C ±3°C. No heat sink or forced-air cooling on the devices shall be permitted.
B4	2037	test condition A.
B6	1032	T_A = +200°C.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein. Delta measurements shall be in accordance with table II herein.

Subgroup	Method	Condition
C6	1026	V_{GS} = -24 V dc; V_{DS} = 0; T_A = +175°C ±3°C. No heat sink or forced-air cooling on the devices shall be permitted.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Disposition of case lead during electrical measurements. All electrical measurements and operating life test shall be performed with the case lead connected to the source.

4.5.3 Small-signal common-source short-circuit input, output, or forward transfer conductance and susceptance. These tests shall be conducted with a General Radio transfer function and admittance bridge model 1607A (or suitable equivalent) in accordance with the portion of its accompanying handbook which is applicable to this measurement. A Hewlett-Packard generator model 608D and Nems-Clarke receiver model 1502A (or suitable equivalents) shall be used with the transfer function and admittance bridge.

4.5.4 Spot noise figure tests. These tests shall be conducted using the equipment and circuit shown on figures 3 and 4, or suitable equivalent.

4.5.5 Small-signal common-source insertion power gain. This test shall be conducted using the circuit shown on figure 4, or suitable equivalent.

4.5.6 Small-signal common-source short-circuit output capacitance. This test shall be conducted using the circuit shown on figure 5, or suitable equivalent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Breakdown voltage, gate to source	3401	Bias condition C; I_G = 1 µA dc; V_{DS} = 0	$V_{(BR)GSS}$	-35		V dc
Gate reverse current	3411	Bias condition C; V_{GS} = 20 V dc; V_{DS} = 0	I_{GSS1}		-0.1	nA dc
Drain current	3413	Bias condition C, V_{DS} = 15 V dc; pulsed (see 4.5.1)	I_{DSS}	5	15	mA dc
Gate to source voltage	3403	V_{DS} = 15 V dc; I_D = 0.5 mA dc	V_{GS}	-1	-5.5	V dc
Gate to source cutoff voltage	3403	V_{DS} = 15 V dc; I_D = 1.0 nA dc	$V_{GS(off)}$	-2.5	-6.0	V dc
Gate to source forward voltage	3403	V_{DS} = 0 V dc; I_G = 1.0 mA dc	V_{GSF}		1	V dc
Subgroup 3						
High-temperature operation:		T_A = +150°C				
Gate reverse current	3411	Bias condition C; V_{GS} = 20 V dc;	I_{GSS2}		-0.1	µA dc
Low-temperature operation:		T_A = -55°C				
Magnitude of small-signal, common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0 V dc; f = 1 kHz	$\lvert y_{fs}\rvert_1$		11.25	mS
Subgroup 4						
Magnitude of small-signal, common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0 V dc; f = 1 kHz; pulse width = 100 ms; duty cycle = 10 percent	$\lvert y_{fs}\rvert_2$	4.5	7.5	mS

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Small-signal, common-source short-circuit input capacitance	3431	V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz	C_{iss}		4	pF
Small-signal, common-source short-circuit reverse transfer capacitance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz	C_{rss}		0.8	pF
Small-signal, common-source short-circuit output capacitance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; 100 kHz ≤ f ≤ 1 MHz (see 4.5.6)	C_{oss}		2	pF
Small signal, common-source short-circuit input susceptance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3)	b_{is}			
Test 1 Test 2		f = 100 MHz f = 400 MHz			2.5 10	mS mS
Small signal, common-source short-circuit output susceptance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3)	b_{os}			
Test 1 Test 2		f = 100 MHz f = 400 MHz			1 4	mS mS
Small-signal, common-source short-circuit input conductance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3)	g_{is}			
Test 1 Test 2		f = 100 MHz f = 400 MHz			0.3 3.0	mS mS
Small-signal, common-source short-circuit output conductance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; (see 4.5.3)	g_{os}			
Test 1 Test 2		f = 100 MHz f = 400 MHz			75 400	µS µS

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued						
Small-signal, common-source short-forward transfer capacitance		V_{DS} = 15 V dc; V_{GS} = 0 V dc; f = 400 MHz (see 4.5.3)	g_{fs}	4		mS
Small-signal, common-source-insertion power gain		V_{DS} = 15 V dc; I_D = 5 mA dc; R_G = 1 kΩ (see 4.5.5)	G_{ps}			
Test 1		f = 100 MHz		18		dB
Test 2		f = 400 MHz		10		dB
Common-source spot capacitance		V_{DS} = 15 V dc; I_D = 5 mA dc; R_G = 1 kΩ (see 4.5.4)	F			
Test 1		f = 100 MHz			2	dB
Test 2		f = 400 MHz			4	dB
Subgroup 5						
Not applicable						

1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

TABLE II. Groups A, B, and C delta measurements.

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Magnitude of small-signal, common-source short-circuit forward transfer admittance	3455	V_{DS} = 15 V dc; V_{GS} = 0 V dc; f = 1 kHz; t_p = 100 mS;, duty cycle = 10 percent	$\Delta\lvert y_{fs}\rvert_2$	20 percent change from initial value		
2.	Drain current	3413	Bias condition C; V_{DS} = 15 V dc, pulsed (see 4.5.1)	ΔI_{DSS}	10 percent change from initial value.		

1/ The delta measurements for table VIa (JANS) of MIL-PRF-19500 are as follows:

a. Subgroup 4, see table II herein, step 1.

c. Subgroup 5, see table II herein, steps 1 and 2.


2/ The delta measurements for table VIb (JAN, JANTX, and JANTXV) of MIL-PRF-19500 are as follows:

a. Subgroup 3 and 6, see table II herein, step 1.

3/ The delta measurements for table VII of MIL-PRF-19500 are as follows:

a. Subgroup 6, see table II herein, steps 1 and 2; for JANS level and step 1 for JAN, JANTX, and JANTXV levels.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.



NOTES:
1. The test fixture and procedure shall be in accordance with figure 4.
2. The post amplifier shall contain suitable biasing circuits and shall be constructed utilizing very high frequency design technique. It shall be designed for the test frequency.

FIGURE 2. Block diagram for spot noise figure tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.



Circuit component information (see note)					
	Capacitors			Inductors	
	100 MHz	400 MHz		100 MHz	400 MHz
C_1 C_2	7 pF 0.0015 µF	1.8 pF 0.001 µF	L_1	0.14 µH, 3.5 T, no. 18 enameled copper wire, 3/8" I.D., 1/4" long	.022 µH, 5/8" of no. 16 copper wire formed to 0.5 T, 1/4" I.D.
C_3 C_4 C_5	1-12 pF 1,000 pF 1-12 pF	0.8-8 pF 27 pF 0.8-8 pF	L_2	3 µH, 17 T, no. 28 enameled copper wire, close wound, 9/32" I.D., powered iron slug	0.2 µH, 6 T, no. 24 enameled copper wire, close wound, 7/32" I.D., aluminum slug
C_6 C_7	0.0015 µF 3 pF	0.001 µF 1 pF	L_3	0.25 µH, 4.5 T, no. 18 enameled copper wire, 3/8" I.D., 5/16" long	0.03 µH, 1 1/2" of no. 16 enameled copper wire formed to 1 T, 3/8" I.D.

NOTE: Transformed equivalent source resistance is 1,000Ω at 100 MHz for 100 MHz amplifier, and 1,000Ω at 400 MHz for 400 MHz amplifier.

FIGURE 3. Neutralized small-signal common-source insertion power gain and common-source spot noise figure test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.




FIGURE 4. Small-signal common-source short-circuit output capacitance test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Points' packaging activity within the Military Department or Defense Agency, or within the Military Departments' System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

5.2 Marking. Unless otherwise specified (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Issue of DODISS to be cited in the solicitation.

b. Lead finish as specified (see 3.3.1).

c. Product assurance level and type designation.

6.3 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List QML-19500 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or purchase orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center Columbus, DSCC-VQE, Columbus, OH 43216.

CONCLUDING MATERIAL

Custodians:
Air Force - 11
Navy - EC
DLA - CC

Review activities:
Air Force - 19
Navy - MC

Preparing activity:
DLA - CC

(Project 5961-2118)RP

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-PRF-19500/428C	**2. DOCUMENT DATE** 99/07/02

3. DOCUMENT TITLE SEMICONDUCTOR DEVICE, FIELD-EFFECT TRANSISTOR, N-CHANNEL SILICON, TYPE 2N4416A JAN, JANTX, JANTXV AND JANS

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER		
a. NAME (Last, First, Middle initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) Commercial DSN FAX EMAIL	7. DATE SUBMITTED

8. PREPARING ACTIVITY				
a. Point of Contact Alan Barone	b. TELEPHONE Commercial 614-692-0510	DSN 850-0510	FAX 614-692-6939	EMAIL alan_barone@dscc.dla.mil
c. ADDRESS Defense Supply Center Columbus ATTN: DSCC-VAT Columbus, OH 43216-5000	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC -LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvior, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888			

DD FORM 1426, FEB 99 (EG) PREVIOUS EDITIONS ARE OBSOLETE WHS/DIOR, Feb 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T01:44Z
Check the source to verify that this is the current version before use.