MIL-F-83798/7A
12 January 1977


SUPERSEDING
MIL-F-83798/7
1 AUGUST 1974

MILITARY SPECIFICATION SHEET

FITTINGS, RUBBER HOSE, LIGHTWEIGHT, MEDIUM PRESSURE, SWIVEL FLANGE, STRAIGHT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the fittings described herein shall consist of this document and the latest issue of specification MIL-F-83798.



PART NUMBER	A MAX		WEIGHT MAX	
	IN	MM	LBS	GMS
M83798/7-8	1.82	46.23	0.099	44.91
M83798/7-10	1.87	47.50	0.122	55.34
M83798/7-12	2.29	58.17	0.165	74.84
M83798/7-16	2.60	66.04	0.251	113.85
M83798/7-20	2.82	71.63	0.368	166.92
M83798/7-24	2.74	69.60	0.454	205.93
M83798/7-32	3.08	78.23	0.739	335.20

NOTES:

1. Material: Socket: Aluminum, Per QQ-A-225/6, either SAE 2024-T6 or SAE 2024-T851; or Per QQ-A-225/8, either SAE 6061-T6 or SAE 6061-T651.
   Nipple: Aluminum, SAE 6061-T6 Per QQ-A-225/8 or WW-T-700/6.
   Flange: Aluminum, SAE 2014-T6 Per QQ-A-367.
2. Swivel flange in accordance with MS 20756 and shall mate per MS 33786.
3. This specification sheet takes precedence over documents referenced herein.
4. Referenced documents shall be of the issue in effect on the date of invitation for bid.
5. Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:
Air Force - 99
Army - AV

Review Activities:
Army - AT, ME
Navy - AS
DSA - CS

User Activities:
Air Force - 11
Army - AV
Navy - AS

Preparing Activity:
Air Force - 99

Agent:
DSA - CS

(Project 4730-0588)

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:44Z
Check the source to verify that this is the current version before use.