INCH-POUND

MIL-DTL-83798/7B
18 September 2000
SUPERSEDING
MIL-F-83798/7A
12 January 1977

DETAIL SPECIFICATION SHEET

FITTINGS, RUBBER HOSE, LIGHTWEIGHT, MEDIUM PRESSURE, SWIVEL FLANGE, STRAIGHT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-83798 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.



NOTES:

1. See table I for fitting “A” dimensions and weight.

FIGURE 1. Fitting, swivel flange, straight.

AMSC N/A FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:43Z
Check the source to verify that this is the current version before use.

TABLE I. Fitting “A” dimension and weight.

Dash Number	A (max)		Weight (max)	
	in.	mm	lbs.	gms
-8	1.82	46.23	0.099	44.91
-10	1.87	47.50	0.122	55.34
-12	2.29	58.17	0.165	74.84
-16	2.60	66.04	0.251	113.85
-20	2.82	71.63	0.368	166.92
-24	2.74	69.60	0.454	205.93
-32	3.08	78.23	0.739	335.20

REQUIREMENTS:

1. Material: Socket: Aluminum per SAE AMS-QQ-A-225/6 (2024-T6) or SAE AMS4339 (2024-T851) or aluminum per SAE AMS-QQ-A-225/8 (6061-T6) or SAE AMS4117 (6061-T651).

2. Nipple: Aluminum (6061-T6) per SAE AMS-QQ-A-225/8 or WW-T-700/6.

3. Flange: Aluminum per SAE AMS4133 (2014-T6).

4. The swivel flange shall be in accordance with MS20756 and shall mate with MS33786.

5. This specification sheet takes precedence over documents referenced herein.

6. The Part Identifying Number (PIN) shall be constructed as follows:



M83798/7-10 indicates: 7/8″ fitting, flareless, swivel flange, straight.

Custodians:
Army - AV
Air Force - 99
Navy - AS
DLA - CC

Review activities:
Army - AT
Navy -SA

Preparing activity:
DLA - CC

(Project 4730-0741)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:43Z
Check the source to verify that this is the current version before use.