INCH-POUND

MIL-C-5/14F
AMENDMENT 2
11 October 1989
SUPERSEDING
AMENDMENT 1
25 August 1975

MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, MICA DIELECTRIC,
STYLES CM80, CM81, AND CM83

This amendment forms a part of MIL-C-5/14F, dated 18 October 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

STYLE CM81 (figure): Delete the height dimension "2.00 ±.06" and substitute "2.50 ±.06"; also delete the diameter dimension "2.00 +.03 -.06" and substitute "2.50 +.03 -.06"

PAGE 2

STYLE CM83 (figure): Delete the width dimension of the flange ".50 ±.03" and substitute "2.50 ±.03".

NOTE 6: Delete "CM85" and substitute "CM83".

PAGE 3

* Below requirements add: "Qualification inspection is not required."

Temperature cycling requirement, delete and substitute:

"Thermal shock:

Method 107 of MIL-STD-202, condition A, except the high temperature shall be as follows:

Symbol M: +70°C.

Symbol O: +125°C."

The margin of this amendment is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:51Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Navy - CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1667)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:51Z
Check the source to verify that this is the current version before use.

15 HWT Serial Number HWT Serial No. OPER