# MILITARY SPECIFICATION SHEET

## CAPACITORS, FIXED, MICA DIELECTRIC, STYLES CM04, CM05, CM06, CM07, CM08, CM09, CM10, CM11, CM12, AND CM13

This amendment forms a part of MIL-C-5/18D, dated 21 December 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Temperature cycling, delete and substitute:

"Thermal shock:

Method 107 of MIL-STD-202, condition A, except the high temperature shall be as follows:

Symbol O: +125°C.

Symbol P: +150°C."

PAGE 7

Following footnote 1/, add the following:

* "Supersession data: Capacitors of this specification can be superseded by capacitors of equivalent or better styles, types, capacitance, tolerance, voltage rating, and case size covered under MIL-C-5 or MIL-C-39001 within the interchangeability and substitution guidelines of the Federal Item Identification Guide (FIIG) for Fixed Capacitors-FIIG A010A."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - AS, OS, SH
Air Force - 11, 17
DLA - ES

User activities:
Navy - CG, MC
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1629)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:52Z
Check the source to verify that this is the current version before use.



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.