MIL-R-11F
SUPPLEMENT 1A
17 February 1972
SUPERSEDING
SUPPLEMENT 1
17 April 1967

MILITARY SPECIFICATION

RESISTORS, FIXED, COMPOSITION (INSULATED), GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-R-11F, and is mandatory for use by all Departments and Agencies of the Department of Defense.

DETAIL SPECIFICATIONS

MIL-R-11/1 - Resistor, Fixed, Composition (Insulated), Style RC08.*
MIL-R-11/3 - Resistor, Fixed, Composition (Insulated), Style RC20.
MIL-R-11/4 - Resistor, Fixed, Composition (Insulated), Style RC22.*
MIL-R-11/6 - Resistor, Fixed, Composition (Insulated), Style RC32.
MIL-R-11/7 - Resistor, Fixed, Composition (Insulated), Style RC42.
MIL-R-11/8 - Resistor, Fixed, Composition (Insulated), Style RC07.
MIL-R-11/9 - Resistor, Fixed, Composition (Insulated), Style RC12.*
MIL-R-11/11 - Resistor, Fixed, Composition (Insulated), Style RC05.

* CANCELLED: See Notice 1 dated 30 August 1971.

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5905-0780-2)

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:53Z
Check the source to verify that this is the current version before use.

TABLE I. Performance characteristics.

STYLE			RC20	RC32	RC42	RC07	RC05
Maximum ambient temperature at rated wattage (see 3.1)			70°C	70°C	70°C	70°C	70°C
Maximum ambient temperature at zero wattage derating (see 3.1)			130°C	130°C	130°C	150°C	130°C
Power rating in watts (see 3.5)			1/2	1	2	1/4	1/8
Maximum percent change in resistance ± 1/	Low temperature operation (see 3.12)		3	3	3	3	3
	Temperature cycling (see 3.13)		4	4	4	4	4
	Moisture resistance (see 3.14)	Maximum	15	15	15	15	15
		Average	10	10	10	10	12
	Short time overload (see 3.15)		2.5	2.5	2.5	2.5	2.5
	Life (see 3.16)	Maximum	10	10	10	10	8
		Average	6	6	6	6	6
	Terminal strength (see 3.17)		± (1 percent + .05 ohm)	± (1 percent + .05 ohm)	± (1 percent + .05 ohm)	± (1 percent + .05 ohm)	± (1 percent + .05 ohm)
	Resistance to soldering heat (see 3.18)		± (3 percent + .05 ohm)	± (3 percent + .05 ohm)	± (3 percent + .05 ohm)	± (3 percent + .05 ohm)	± (3 percent + .05 ohm)
	Shock (specified pulse) (see 3.20), and vibration, high frequency (see 3.21)		2	2	2	2	2
	Resistance tolerance (± percent) (see table III)		See 3.1	See 3.1	See 3.1	See 3.1	See 3.1

1/ Where total resistance change is 1 percent or less, it shall be considered as ± (__ percent + 0.05 ohm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:53Z
Check the source to verify that this is the current version before use.