MIL-R-11/8G
24 February 1970
SUPERSEDING
MIL-R-11/8F
12 February 1968

# MILITARY SPECIFICATION

# RESISTOR, FIXED, COMPOSITION (INSULATED),

# STYLE RC07

**INACTIVE FOR DESIGN AFTER 12 FEBRUARY 1968 (SEE 6.2) USE MIL-R-39008/1.**

*This specification is mandatory for use by all Departments and Agencies of the Department of Defense.*

## 1. SCOPE

1.1 This specification covers the detail requirements for style RC07 resistor.

## 2. APPLICABLE DOCUMENTS

2.1 The following document, of the issue in effect on date of invitation for bids or request for proposal, forms a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-R-11 – Resistors, Fixes, Composition (Insulated), General Specification For.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS


3.1 **Requirements.** Requirements shall be in accordance with MIL-R-11, and as specified herein.

3.2 **Design and construction.** The resistor shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 **Power rating.** The power rating shall be 1/4 watt, based on full load operation at an ambient temperature of 70°C. Resistors operated at ambient temperatures in excess of 70°C shall be derated in accordance with figure 2. The rated direct current (dc) or root mean square (rms) continuous working voltage shall not exceed 250 volts.

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 20261O-15T15:54Z
Check the source to verify that this is the current version before use.




| Inches | MM |
|---|---|
| .002 | .05 |
| .008 | .20 |
| .025 | .64 |
| .031 | .79 |
| .090 | 2.29 |
| .125 | 3.18 |
| .250 | 6.35 |
| 1.500 | 38.10 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.

FIGURE 1. Style RC07 resistor.





FIGURE 2. Derating curve for high ambient temperatures.



Source: https://assist.dla.mil -- Downloaded: 202610-15T15:54Z
Check the source to verify that this is the current version before use.

3.4 **Resistance.** Minimum resistance value shall be 2.7 ohms; maximum resistance value shall be 22 megohms.

3.5 **Moisture resistance.** The change in resistance shall not exceed an average of 10 percent for each group of 10 resistors tested, nor a maximum of 15 percent for any individual resistor.

3.6 **Life.** The change in resistance between the initial measurement and each of the succeeding measurements shall not exceed an average of 6 percent for each group of 10 resistors tested, nor a maximum of 10 percent for any individual resistor.

3.7 **Resistance to soldering heat.** The change in resistance shall not exceed ±(3 percent +0.05 ohm).

## 4. QUALITY ASSURANCE PROVISIONS

4.1 **Sampling and inspection.** Sampling and inspection shall be in accordance with MIL-R-11, and as specified herein.

4.2 **Terminal strength.**

4.2.1 *Direct load.* Direct load shall be applied gradually until the load reaches 5 pounds.

4.2 *Twist.* The twist test is applicable to this specification.

4.3 **Resistance to soldering heat.** Temperature of solder in which resistor terminals are immersed, shall be 350° ±10°C.

4.4 **Seal.** The seal test is not applicable to this specification.

## 5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-R-11.

## 6. NOTES

6.1 The notes specified in MIL-R-11 are applicable to this specification.

6.2 **Substitution data.** The resistors specified herein are not for use in design after 12 February 1968. They are suitable for use in design contracts current to that date and to support existing military equipment. Resistors specified in MIL-R-39008/1 are preferred for design and regardless of the failure rate designation can be used as substitutes for the inactivated resistors of the same resistance value and tolerance, of this specification.

• 6.3 **Zero load point.** Resistors furnished under this specification are a substitute for resistors furnished under Revision F regardless of the change in zero load point (150°C). The 130°C zero load point is considered a more accurate definition of RC07 resistor capabilities.



Source: https://assist.dla.mil -- Downloaded: 20261O-15T15:54Z
Check the source to verify that this is the current version before use.

6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army - EL, MU, MI
Navy - EC, AS, OS, SH
Air Force - 11, 17, 85
DSA - ES

User activities:
Army - ME, AT, AV
Navy - MC
Air Force - 19

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5905-0703-3)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:54Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Communications - Electronics Command
ATTN: DRSEL-ED-TO
Fort Monmouth, NJ 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:54Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| | |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |
| | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |
| | |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:54Z
Check the source to verify that this is the current version before use.