GG-P-191F
November 8, 1972
SUPERSEDING
Fed. Spec. GG-P-191E
December 5, 1963

FEDERAL SPECIFICATION

PERFORATOR, PAPER, DESK

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers adjustable and nonadjustable desk type paper perforators.

1.2 Classification.

1.2.1 Types. The perforators covered by this specification shall be of the following types, as specified (see 6.2). Perforator heads for type I perforator may be ordered under this specification (see 6.2).

Type I. - Adjustable.
Type II. - Nonadjustable.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-C-95 - Cards, Guide, File and Card Sets; Guide File.
UU-P-121 - Paper, Bond and Writing, White and Colored.
UU-P-328 - Paper, Manifold.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping Fiberboard.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:49Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

American Society for Testing and Materials:

Standard Methods of Tests.

E 10 - Brinell Hardness of Metallic Materials
E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

(Application for copies should be addressed to the American Society for Testing and Materials 1916 Race Street, Philadelphia, PA 19103.)

3. REQUIREMENTS

3.1 Material and components.

3.1.1 Base. The base shall be made of cast-iron, zinc-base die-casting, cold-rolled steel, or a combination thereof. The thickness shall be as specified in table I.

TABLE I. Base thickness

Material	Thickness (minimum)	
	Type I	Type II
Cast iron	0.125 inch	0.090 inch
Zinc-base die-casting	0.095 inch	0.080 inch
Cold-rolled steel	0.0636 inch	0.0449 inch

3.1.2 Punches. For at least 0.125 inch from the cutting edge, the steel punches shall have a hardness of not less than Rc 50 (see 4.4.2 and 4.4.2.1). If case surface hardened, the depth of the case shall be not less than 0.010 inch, and the hardness shall be not less than R15N 85.5 (see 4.4.2 and 4.4.2.1).

3.1.3 Dies and plates. For at least 0.125 inch from the cutting edges, steel dies forming an integral part of the head, or die inserts or plates shall have a hardness of not less than Rc 25 (see 4.4.2 and 4.4.2.1). If case surface hardened steel die inserts are used, the depth of the case shall be not less than 0.010 inch, and the hardness shall be not less than R15N 72 (see 4.4.2 and 4.4.2.1). Cast iron dies forming an integral part of the head shall have a hardness of not less than BHN 170HB (see 4.4.2 and 4.4.2.2).

3.1.4 Handle. The handle shall be made of cast-iron, aluminum or zinc-base die-casting, or cold rolled steel.

3.1.5 Punch operating shaft. The punch operating shaft, when used, shall be made of steel having a minimum hardness not less than Rc 20 (see 4.4.2 and 4.4.2.1). If case surface hardened die inserts are used the depth shall be not less than 0.010 inch, and the hardness shall be not less than R15N 69 (see 4.4.2 and 4.4.2.1).

3.1.6 Spring. The spring shall be made of suitable steel to assure performance requirements specified in 3.4.

3.1.7 Adjustable extension guide. The extension guide shall be made of suitable steel.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the current version before use.

3.1.8 Adjustable paper stop (type I only). The adjustable paper stop shall be made of suitable metal.

3.1.9 Locking devices. The locking devices for locking adjustable parts and components shall be made of suitable metal.

3.1.10 Receptacle. The removable receptacle, or the stationary receptacle with removable cap shall be made of suitable metal. The cap may be made of suitable plastic.

3.1.11 Protective shoes or covering. The protective shoes shall be made of natural or synthetic rubber, or a suitable combination thereof. The protective covering shall be made of durable rubber or of felt. The shoes or covering shall not produce dark marks or scratches on furniture.

3.2 Type I.

3.2.1 Design and construction. The material and components shall conform to the applicable material requirements stated in 3.1. The perforator shall consist essentially of perforator heads with punch mechanism, base, punch operating shaft, handle, frame or channel for supporting heads, adjustable extension guide, adjustable paper guide, scale, receptacle, and protective feet or covering. All movable or adjustable parts shall fit properly and securely, and operate smoothly and easily.

3.2.1.1 Perforator head and punch mechanism. Each perforator shall have not less than three perforator heads. The punch mechanism shall be contained in the head, and the punch, die or plate, and spring shall conform to the material requirements stated in 3.1.2, 3.1.3, and 3.1.6, respectively. Unless otherwise specified, the punch mechanism shall punch holes 1/4 inch in diameter (see 6.2). The perforator shall be capable of punching holes from 1-3/8 inch center-to-center to not less than 8-1/2 inches center-to-center. The head shall be removeable and replaceable, and shall be provided with a device (see 3.1.9) for locking head in the desired position. The base of the head shall be permanently marked to indicate the center of the punch, and shall be devoid of obstruction when inserting material to be perforated.

3.2.1.2 Base. The base shall conform to the material requirements specified in 3.1.1 and table I. The dimensions of the base parallel to the length of the punch operating shaft shall be not more than 11-1/4 inches. The dimensions perpendicular to the shaft shall be not less than 5-1/4 inches and not more than 7-1/2 inches. The base shall be of such design and construction to assure that the perforator will remain stable, and will not tilt, when tested as specified in 4.4.1.2 and 4.4.1.3. The underside of the base shall be provided with not less than four protective shoes, or covering, as specified in 3.1.11.

3.2.1.3 Handle and punch operating shaft. The handle and punch operating shaft shall conform to the material requirements stated in 3.1.4 and 3.1.5 respectively. The design and construction of the handle and punch operating shaft shall assure that there will be no permanent set or breakdown, when tested as specified in 4.4.1.1. When actuated, the handle and punch operating shaft shall set the punch mechanism into motion.

3.2.1.4 Scale. The top of the base shall be provided with a scale having a useful length of not less than 9 inches. The scale shall be legibly stamped with metal die, etched, or otherwise incised in inches and graduated in increments of 1/16 inch. The scale shall include a mark indicating the center of the base. The scale shall not vary more than plus or minus 1/64 inch, when tested as specified in 4.4.1.4.

3.2.1.5 Adjustable extension guide. The guide shall conform to the material requirements specified in 3.1.7. The guide shall be not less than 0.4375 inch wide. The guide of flat-strip design shall be not less than 0.050 inch thick, and the guide of roll-flanged edge design shall be not less than 0.040 inch thick. The guide shall have not less than 10 inches of useful length, when measured from center of perforator, and shall have a stop for centering material to be perforated. A scale of graduated, measurements shall be stamped with metal die, etched, or otherwise incised into the guide to provide means for centering material to be perforated. The guide shall be provided with a holding device, or shall be of such design to assure that the guide will be held in place at the desired point, when 5 pounds pressure is applied (see 4.4.1.5).

3.2.1.6 Receptacle. The receptacle shall conform to the material requirements specified in 3.1.10. Stationary receptacle with cap shall be securely attached to the underside of the base. Removable receptacle shall not become detached during ordinary usage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the current version before use.

3.3 Type II.

3.3.1 Design and construction. The material and components shall conform to the applicable requirements stated in 3.1. The perforator shall consist essentially of perforator heads or enclosure and punch mechanism, base, handle, adjustable extension guide, and receptacle. All moveable or adjustable parts and components shall fit properly and securely, and operate smoothly and easily.

3.3.1.1 Perforator head or enclosure and punch mechanism. The punch mechanism shall be contained in the perforator head or enclosure. The punch, die or plate, and spring shall conform to the material requirements stated in 3.1.2, 3.1.3, and 3.1.6, respectively. The perforator shall have two punch mechanisms, and unless otherwise specified shall punch holes 1/4 inch in diameter. The center of the perforated holes shall be not less than 7/16 inch and not more than 1/2 inch from the edge of the material, and the center-to-center distance between the holes shall be 2-3/4 inches plus or minus 1/32 inch. The perforator head shall be designed so that no obstruction will be encountered when inserting material to be perforated. The perforator head or enclosure, when not an integral part of the base, shall be securely attached to the base.

3.3.1.2 Base. The base shall conform to the material requirements specified in 3.1.1 and table I. The dimensions of the base parallel to the length of the adjustable extension guide shall be not more than 6 inches, and the dimensions perpendicular to the adjustable extension guide shall be not less than 5 inches and not more than 7-1/2 inches. The base shall be designed so that the perforator will maintain its stability and will not tilt, when tested as specified in 4.4.1.2 and 4.4.1.3. The center point between the punch mechanism shall be permanently marked on the base. The underside of the base shall be provided with not less than four protective shoes, or covering material, as specified in 3.1.11.

3.3.1.3 Handle. The handle shall conform to the material requirements stated in 3.1.4. The design and construction of the handle shall assure that there will be no permanent set or breakdown, when the perforator is tested as specified in 4.4.1.1. When actuated, the handle shall set the punch mechanism into motion.

3.3.1.4 Adjustable extension guide. The guide shall conform to the material requirements specified in 3.1.7. The guide shall be not less than 0.4375 inch wide. The guide of flat-strip design shall be not less than 0.050 inch thick, and the guide of roll-flanged edge design shall be not less than 0.040 inch thick. The guide shall have not less than 5-1/2 inches of useful length, when measured from the center of the perforator, and shall have a stop for centering material to be perforated. A scale of graduated measurements shall be stamped with metal die, etched, or otherwise incised into the guide, to provide means for centering material to be perforated. The guide shall be provided with a holding device, or shall be of such design to assure that the guide will be held in place at the desired point, when 5 pound pressure is applied (see 4.4.1.5).

3.3.1.5 Receptacle. The receptacle shall conform to the material requirements specified in 3.1.10. Stationary receptacle with cap shall be securely attached to the underside of the base. Removeable receptacle shall not become detached during ordinary usage.

3.4 Performance. There shall be no permanent set or breakdown to any part of the perforator that will affect its serviceability or performance, when tested as specified in 4.4.1.1. When actuated, the perforator shall simultaneously punch the required number of holes, and the tension of the spring(s) shall force the punch and handle to its original position, when handle is released (see 4.4.1.2 and 4.4.1.3). The punches shall not stick to the dies or plates, and perforations shall be entirely punched out and be free from torn or ragged edges, when tested as specified in 4.4.1.2 and 4.4.1.3. Perforation shall require not more than 160 pounds of force on the handle, when tested as specified in 4.4.1, 4.4.1.1, 4.4.1.2, and 4.4.1.3.

3.5 Hazard requirements. The perforators shall be designed to prevent injury to the users during the normal operation of the perforators.

3.6 Parts and components replacements. All removeable parts and components of the perforator of the same make and model shall be interchangeable.

3.7 Assembly and operation instruction. Instruction for assembly and operation shall be provided with each perforator, applicable to the type specified.

3.8 Finish. Unless otherwise specified, the exterior surface of the perforator, with the exception of machined and other operating parts, shall be finished with enamel or equivalent coating. Unless made of stainless steel, extension guide, adjustable paper guide, thumbscrews, and locking devices shall be cadmium, chromium or nickel plated.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:49Z
Check the source to verify that this is the current version before use.

3.9 Workmanship. The perforators shall be devoid of defects which adversely affect appearance, or which might impair serviceability or durability of the perforator. The perforators shall be devoid of burrs, sharp edges, or other defects which might constitute a hazard to the users.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size of lot. All perforators of the same type presented for inspection at one time shall be considered a lot for the purpose of examination and tests.

4.2.2 Sampling for examination and tests. Sampling for examination and tests shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual and dimensional examination. Random samples of perforators shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one perforator. The perforator shall be examined for defects listed in table II. The Inspection Level shall be S-3, and the Acceptable Quality Level (QPL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers offered for inspection at one time. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to closing operations. The Inspection Level shall be S-2, with an AQL of 4.0 defects per hundred units.

4.2.5 Sampling for tests. Random samples of perforators shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one perforator. The Inspection Level shall be S-2, and the AQL shall be 2.5 percent defective.

4.3 Examination.

4.3.1 Visual and dimensional examination. Samples taken in accordance with 4.2.3 shall be examined for defects listed in table II. Any perforator having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

TABLE II. Classification of defects

Examine	Defects
Type	Not as specified (see 1.2.1).
Material and Components	Not as specified (see 3.1 thru 3.1.11, as applicable).
Design and construction	
Type I	Not as specified (see 3.2 thru 3.2.1.6).
Type II	Not as specified (see 3.3 thru 3.3.1.5).
Assembly and operation instruction	Not as specified, or missing (see 3.7).
Finish	Not as specified (see 3.8).
Workmanship	Not in accordance with 3.9.

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table III, to determine that packaging, packing, and marking requirements conform to the requirements of section 5. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:49Z
Check the source to verify that this is the currentversion before use.

TABLE III. Examination of preparation for delivery

Examine	Defects
Containers	Not as specified.
Contents	Not as specified.
Markings	Omitted; incorrect; illegible improper size, locations, sequence or method of application.
Materials	Component missing or damaged.
Workmanship	Bulging or distortion of containers, Cushioning inadequate, improper or missing.

4.3.2.1 Examination of closure and reinforcement of containers. When shipping containers are required to comply with PPP-B-636, examination for defects in closure and reinforcement shall be in accordance with the appendix of that specification.

4.4 Tests.

4.4.1 Performance tests. Samples selected in accordance with 4.2.5 shall be subjected to the following test, as applicable. Any perforator failing one or more tests shall be considered defective. If the number of defective units in the sample exceeds the acceptance number for that sample, the entire lot represented by the sample shall be rejected. Perforators shall be oiled and then tested, as specified. Force shall be applied with even pressure and continued until material is perforated. The first five perforation of each perforation test shall be tested for the force needed for perforation. The force shall be measured by a platform scale, or equal (see 3.4).

4.4.1.1 Pressboard. Four sheets of pressboard, conforming to type II of UU-C-95, shall be perforated at one time. The perforator shall be operated 100 times, and each operation shall make new perforations. The test shall assure compliance with 3.4, with the exception that the handle may be used to return the punches to their original position. (See 3.2.1.3 and 3.3.1.3.)

4.4.1.2 Bond paper. Twenty sheets of bond paper, conforming to type III (24 pounds) of UU-P-121, shall be perforated at one time. The perforator shall be operated 25 times, and each operation shall make new perforations. The test shall assure compliance with 3.4.

4.4.1.3 Manifold paper. A single sheet of manifold paper, conforming to type V of UU-P-328, shall be perforated. The perforator shall be operated 25 times, and each operation shall make new perforation. The test shall assure compliance with 3.4.

4.4.1.4 Scale. A single sheet of bond paper (see 4.4.1.2) shall be perforated. The distance between the centers of the holes shall be measured to determine compliance with 3.2.1.4.

4.4.1.5 Extension guide. A force of 5 pounds shall be applied to the end of the guide in the horizontal direction to determine compliance with 3.2.1.5 and 3.3.1.4.

4.4.2 Metal hardness. For hardness testing on curved surfaces, remove necessary amount of metal at point of measurement.

4.4.2.1 Rockwell hardness and Rockwell Superficial hardness. The applicable hardness shall be tested in accordance with ASTM E 18, to determine compliance with 3.1.2, 3.1.3, and 3.1.5, as required.

4.4.2.2 Brinell hardness. The hardness, when applicable, shall be tested in accordance with ASTM E 10, to determine compliance with 3.1.5.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Assembled perforator or perforator heads as specified (see 6.2) shall be packaged as specified in 5.1.1.1 or 5.1.1.2.

5.1.1.1 Each assembled perforator with mechanism secured to prevent movement and operating instructions specified in section 3, shall be packaged in a box conforming to PPP-B-566 or PPP-B-676 variety water resistant.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:49Z
Check the source to verify that this is the currentversion before use.

5.1.1.2 Each perforator head shall be packaged in a box conforming to PPP-B-566 or PPP-B-676 variety water resistant or envelope commonly used for the purpose.

5.1.2 Level B. Assembled perforators or perforator heads as specified (see 6.2) shall be packaged as specified in 5.1.1 except that the box shall be variety non resistant.

5.1.3 Level C. Perforators or perforator heads as specified shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving agency.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Perforators packaged as specified in 5.1 shall be packed in a box conforming to PPP-B-636 class weather resistant. Each box shall be closed sealed and reinforced in accordance with the appendix of the box specification.

5.2.2 Level B. Twelve 3-hole perforators, twenty-four 2 hole perforators or thirty-six perforator heads shall be packed in a box conforming to PPP-B-636, class domestic.

5.2.3 Level C. Perforators or perforator heads in quantities as specified (see 6.2), packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with Uniform Freight Classification or National Motor Freight Classification as applicable.

5.3 Marking. In addition to any special markings required in the procurement documents, marking of the interior packages and exterior shipping containers shall be in accordance with Fed. Std. No. 123 for civil agencies or MIL-STD-129 for military agencies, as applicable (see 6.1).

6. NOTES

6.1 Intended use. The perforators covered by this specification are general office type perforators and are intended to punch two or more holes into paper.

6.2 Ordering data. Purchasers should select the preferred option permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Type of perforator required (see 1.2.1).
(c) Whether only perforator heads are required (see 1.2.1, 5.1.2 or 5.1.3).
(d) Whether other than 1/4 inch diameter punch is required. State the diameter of punch required (see 3.2.1.1 and 3.3.1.1).
(e) Inspection responsibility if other than specified herein; and administrative provisions for inspection records, when applicable (see 4.1).
(f) Level of packaging and packing required (see 5.1 and 5.2).
(g) Any special marking for shipment required (see 5.3).
(h) Quantities required (see 5.2.3).

NO OFFICIAL DOD INTEREST HAS BEEN REGISTERED

Preparing Activity:

GSA-FSS

User activity:

Army - GL

☆U. S. GOVERNMENT PRINTING OFFICE : 1972 O - 514-174 (239)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.