GG-S-161/7D
May 1, 1985
SUPERSEDING
GG-S-161/7C
May 3, 1977

FEDERAL SPECIFICATION SHEET

SCALES, PLOTTING

This specification was approved by the Assistant Administrator, office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring Scales, Plotting described herein shall consist of this document and the latest issue of GG-S-161.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers detail requirements for scales graduated in map ratios.

1.2 Classification.

1.2.1 Type designation number. Scales covered by this specification shall be identified by a type designation number (see 6.2) formed as indicated in GG-S-161. The type designation number is intended for cataloging and ordering purposes and not for printing on the scales. Sub-paragraphs 1.2.1.3 through 1.2.1.10 indicate the options available for the type VII and are further identified in GG-S-161.

1.2.1.1 Spec. No. GG-S-161.

1.2.1.2 Type of scales - -VII.

1.2.1.3 Shape of scales - -1, -2, -6, or -7.

1.2.1.4 Composition of scales - -A, -B, -C, -D, -E, or -F.

1.2.1.5 Grade of scales - -1 or -2.

1.2.1.6 Size of scales - -A, -B, or -F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.

1.2.1.7 Scale graduations - -1 or -2.

1.2.1.8 Numbering of scales - -A or -C.

1.2.1.9 Style of scales - -A, -B, -C, -D, or -E (see 3.2).

1.2.1.10 Type of sheath required - -1, -2, -3, -4, -5, or -6.

3. REQUIREMENTS

3.1 Description. Scales shall be in accordance with GG-S-161 and as specified herein.

3.2 Shapes and styles. The scales shall be shapes 1, 2, 6, or 7 as shown in figure 1 of GG-S-161, direct or double numbered, with scale graduations open or fully divided as specified in the following styles.

3.2.1 Style A. Style A scale shall be divided in feet on one edge and in yards on the other edge in the ratio of 1:25,000. The style A scale shall be furnished in 6-inch nominal lengths.

3.2.2 Style B. Style B scale shall be divided in meters on one edge and in yards on the other edge. Both edges shall be double numbered and graduated at 1:25,000 and 1:50,000. The style B scale shall be furnished in 10-inch nominal lengths.

3.2.3 Style C. Style C scale shall be divided in meters on both edges, graduated at 1:25,000 and 1:50,000. The style C scale shall be furnished in 30-centimeter nominal lengths.

3.2.4 Style D. Style D scale shall be divided in feet on one edge and in yards on the other edge, both graduated at 1:50,000. Style D scales shall be furnished in 12-inch nominal lengths.

3.2.5 Style E. Style E scales shall be open divided with four plotting and two drafting edges. All scales shall be numbered direct, with every 1000th unit of the plotting scales and every single unit of the drafting scales numbered. Plotting scales shall have 1000 units and drafting scales one unit to the left of the zero mark. Plotting scales shall have every 500th unit graduated. The first edge shall be graduated in yards at 1:25,000 with 7000 yards to the right of the zero. The two 500-yard intervals to the left of the zero shall be subdivided at 20-yard intervals with each 100 yards emphasized and every 500 yards numbered from right to left. The second edge shall be graduated in inches, divided to half inches with 11 inches to the right of the zero. The two half-inch intervals to the left of the zero shall be subdivided at 0.02-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.

inch intervals with each 0.1 emphasized. The third edge shall be graduated in meters at 1:50,000 with 14,000 to the right of the zero. The fourth edge shall be graduated in meters at 1:62,500 with 18,000 to the right of the zero. On both third and fourth edges, the two 500 intervals to the left of the zero shall be subdivided at 50 intervals with each 100 emphasized. The fifth edge shall be graduated in meters at 1:25,000 with 6000 to the right of the zero. The two intervals to the left of the zero shall be subdivided at 20 intervals with each 100 emphasized and 500 meters and 1000 meters numbered from right to left. The sixth edge shall be graduated in centimeters with 29 cm to the right of the zero. The centimeter to the left of the zero shall be subdivided into millimeters with each fifth millimeter emphasized. The graduations shall be placed so that as the scale is rolled over, the sequence shall be (1) yards, 1:25,000; (2) inches; (3) meters, 1:50,000. Meters 1:62,500 shall be on the same side as (1); centimeters as (2); and meters 1:25,000 as (3). Style E scale shall be furnished in 12-inch nominal lengths.

3.3 Marking. The scale ratio shall be marked as a representative fraction, for example "1:7920". In addition, the scale ratio may also be marked in words and figures, for example "8 in./mi." or 1 in./660 ft.".

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions shall be in accordance with GG-S-161.

5. PREPARATION FOR DELIVERY

5.1 Packaging shall be in accordance with GG-S-161.

6. NOTES. (The notes in GG-S-161 are applicable to this specification.)

6.1 Intended use. Plotting scales are used in plotting and drawing maps and charts.

6.2 Ordering data. Procurement documents should specify those desired options offered herein and should also specify the following:

a. Type designation number (see 1.2.1).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the currentversion before use.

MILITARY INTERESTS:

Custodians

Army - ME
Navy - YD
Air Force - 99

Review activities

Army - GL
Navy - MC
DLA - GS

User activity

Air Force - 82

CIVIL AGENCY COORDINATING ACTIVITIES:

FSS
NBS
OSS
SCS

PREPARING ACTIVITY:

Army - ME

Project 6675-0787

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.