GG-T-250A
June 14, 1974
SUPERSEDING
Fed. Spec. GG-T-250
April 18, 1961

FEDERAL SPECIFICATION

TESTER, ANTIFREEZE SOLUTIONS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a tester of the hydrometer-thermometer type, used to measure the specific gravity of ethylene glycol-water solutions commonly used as antifreeze in liquid cooled engines.

1.2 Classification. This specification covers one type of tester.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperborad.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 6630

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc. Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

American Society for Testing and Materials (ASTM):

D1124 - Hydrometer-Thermometer Field Tester For Engine Antifreezes.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 The tester. The tester described in this specification shall conform to ASTM D-1124, for the high boiling point type of antifreeze solutions.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, unless otherwise specified. For purposes of sampling for inspection, a lot shall consist of all testers submitted for inspection at one time.

4.3 Inspection.

4.3.1 Inspection of material and components. In accordance with 4.1, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified or, if none, in accordance with this specification. In the event of conflict, this specification shall govern.

4.3.2 Classification of defects. Paragraphs are cited from ASTM D-1124.

Major Defects (AQL 4.0).

101. Any component part missing (para. 1.2).
102. Defective glass or elastomer (para. 9 and para. 4).
103. Scales not as specified (para. 2.4 and 2.5).
104. Hydrometer syringe unit not as specified (para. 4).
105. Charts not as specified (para. 6).
106. Tester does not function.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:49Z
Check the source to verify that this is the currentversion before use.

Minor Defects (AQL 6.5).

201. Marking not as specified (para. 2.7).
202. Dimensions not as specified (paras. 2.3, 2.4, 3.2, and 7.3).
203. Faulty workmanship.

4.3.3 Inspection of preparation for delivery. The packaging, packing, and marking of the testers shall be examined to determine compliance with the requirements of section 5 of this specification. Examination of packaging requirements not covered by referenced specifications shall be performed in accordance with examination requirements of Military Specification MIL-P-116. Examination of packing and marking requirements not covered by referenced specifications shall be in accordance with Military Standard MIL-STD-105, using an AQL of 4.0 percent defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Levels A and B. The parts, charts, label, and instructions for assembly and use for the antifreeze solution tester shall be packaged in a box conforming to PPP-B-566 or PPP-B-676. The contents of the box shall be cushioned with suitable partitions, cushioning material, separators, or a combination thereof.

5.1.1.1 Intermediate packaging. Twelve (12) packaged testers shall be intermediately packaged in a box conforming to PPP-B-636, class domestic.

5.1.2 Level C. The tester shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving agency.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Testers, packaged as specified in 5.1, shall be packed in boxes conforming to PPP-B-636, class weather resistant. Containers shall be closed in accordance with the appendix to the box specification.

5.2.2 Level B. Forty-eight (48) packaged testers (4 intermediate packages) shall be packed in a box conforming to PPP-B-636, class domestic, grade not less than 275.

5.2.3 Level C. Testers in quantities as specified (see 6.2) packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination. Containers shall be in compliance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special markings required in the procurement documents, marking of the interior packages and exterior shipping containers shall be in accordance with Fed. Std. No. 123 for civil agencies or MIL-STD-129 for military agencies as applicable (see 6.1).

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Unit quantities required and package type.
(c) Level of packaging and packing required.
(d) Marking required.

MILITARY INTEREST

Army - MU
Navy - YD
Air Force 82

Preparing Activity

GSA - FSS

CIVIL AGENCY COORDINATION ACTIVITIES

GSA - FSS
DOT - NVP

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:49Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:49Z
Check the source to verify that this is the current version before use.