MILITARY SPECIFICATION

OVERCOAT, WOMAN'S, POLYESTER-WOOL, 13-OUNCE, BLUE 1549, WITH REMOVABLE LINER

This amendment forms a part of Military Specification MIL-0-83203A(USAF) dated 7 December 1972.

Pages 14, 15, and 16; table III; No. 8: Add:

"(q) As an option to No. 8(j) through 8(p), make the collar as follows:

(1) Insert 1/2-inch to 3/4-inch bias binding that is made of the rayon material specified in 3.1.2 between the undercollar and the interlining so that the bias binding will extend approximately 1/4 inch from the outer edge of the collar, and stitch through the three plies. Use top thread A, lower thread A, stitch type 304 or 306, 12-14 stitches per inch.

(2) Stitch the undercollar to the topcollar, using a 3/16-inch inch knife attachment, matching the notches and distributing fullness. The interlining edge shall be used as a guide for the finished stitch line and the shape of the collar. Use top thread A, lower thread A, stitch type 301, seam and stitch type SSa-1, and 12-14 stitches per inch.

(3) Turn the collar, and force out the edges. Baste the collar edge, with at least two rows of stitching, distributing the collar fullness evenly and rolling the joining seam to the underside. The first row of stitching shall be 1/4 inch from the edge. The other row of stitching shall be placed along the outside edge of the collar. The rayon bias binding shall not be exposed at the edge of the finished collar. Use commercial cotton thread and stitch type hand or machine."

Custodian:
Air Force - 11

Reviewer:
Air Force - 99

Preparing activity:
Air Force - 11

Project No. 8410-F396

FSC 8410

☆ U. S. GOVERNMENT PRINTING OFFICE: 1977 -703-020/3973

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:39Z
Check the source to verify that this is the current version before use.