MIL-W-60080(MU)
30 October 1964

MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, EMPTY, E6

1. SCOPE

1.1 This specification covers one type of empty warhead.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of.

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

FSC 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:08Z
Check the source to verify that this is the current version before use.

DRAWINGS

EDGEWOOD ARSENAL

DL123-1-42 - Warhead, Guided Missile, Empty, E6.
(All drawings referenced in this specification are listed on DL123-1-42.)

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL123-1-42 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the item shall conform to the specifications and drawings listed on Drawing DL123-1-42 and on subsidiary drawings.

3.2 Assembly. The warhead shall be assembled as shown on Drawing E123-1-42.

3.3 Leakage. The warhead shall not show a pressure drop of more than 1/2 pound per square inch gage (psig) when subjected to an internal air pressure of 15 ± 0.5 psig for a minimum period of 3 minutes when tested as specified in 4.4.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the currentversion before use.

3.4 Preproduction. When specified by the contract or order, a preproduction sample of warheads shall be produced in accordance with this specification for examination and test.

3.5 Serial number. Each warhead assembly shall be sequentially numbered.

3.6 Workmanship. The warhead shall be free from damage, such as dents and gouges, which could adversely affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.3 Inspection provisions.

4.3.1 Examination and test. Each warhead shall be examined and tested in accordance with the list of defects.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the currentversion before use.

4.3.2 List of defects.

4.3.2.1 Warhead, Guided Missile, Empty, E6 (Dwg E123-1-42).

1. Component missing
2. Component incorrectly assembled
3. Eccentricity excessive (Dwg D123-1-64)
4. Concentricity between forward housing flange and aft alignment pins incorrect
5. Perpendicularity between forward housing flange and aft alignment pins incorrect
6. Flatness incorrect (Dwg D123-1-64)
7. Leakage (4.4)
8. Workmanship (3.6)
9. Torque incorrect
10. Fastener head not flush or below surface of skin (0.002 max)
11. Quadrant bags not secured to cable tube assembly
12. Detonator cord grooves obstructed
13. Identification plate missing
14. Detonator block explosive carrier pellet cavity incorrect
15. Station 139 interface incorrect
16. Station 55 interface incorrect
17. Serial number missing

4.4 Leakage test. The warhead shall be subjected to the specified pressure through a shut-off device and a gage. The shut-off valve shall be closed and, after the required period of time, the gage shall be checked for the amount of drop in pressure.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. Cleaning and drying shall be in accordance with applicable provisions of MIL-P-116. Cleaning process C-1 and any of the drying procedures listed therein shall be used.

5.2 Preservation and packaging, level C. The empty warhead and its components shall be preserved and packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the current version before use.

5.3 Packing, level C. The empty warhead and its components, processed as specified in 5.1 and 5.2, shall be packed to insure carrier acceptance and safe delivery to the first destination for immediate use. Containers shall comply with Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This item is a component of a guided missile when loaded is designated as the E9 warhead.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Preproduction when required:

(1) Quantity required
(2) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(3) Name and address of test facility when testing is performed by the Government.
(4) Packing and shipping instruction when applicable.
(5) Time required for the Government to notify the supplier whether or not to proceed with production.

Custodian:

Army - MU

Preparing activity:

Army - MU (EA)

Project No. 1336-A122

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING OFFICER
PICATINNY ARSENAL
ATTN: SMUPA-DC 7
DOVER, NEW JERSEY

FOLD

PLATE NO. 12415 (BACK)

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-H004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:08Z
Check the source to verify that this is the current version before use.