
FED. SUP CLASS
4730




| DASH NUMBER | | TUBE OD | B STRAIGHT THREAD | C HEX FLAT | D DIAMETER | | M | M1 |
|---|---|---|---|---|---|---|---|---|
| BODY | ASSY | NOM | CLASS A OR B | NOM | BASIC | TOLERANCE | ±.030 | ±.060 |
| B2 | A2 | 1/8 | 5/16-24 UNF-2 | 7/16 | .062 | | .770 | .970 |
| B3 | A3 | 3/16 | 3/8 -24 UNF-2 | 1/2 | .125 | | .830 | 1.000 |
| B4 | A4 | 1/4 | 7/16-20 UNF-2 | 9/16 | .172 | ±.003 | .890 | 1.000 |
| B5 | A5 | 5/16 | 1/2 -20 UNF-2 | 5/8 | .234 | | .950 | 1.060 |
| B6 | A6 | 3/8 | 9/16-18 UNF-2 | 11/16 | .297 | | 1.060 | 1.250 |
| B8 | A8 | 1/2 | 3/4 -16 UNF-2 | 7/8 | .391 | ±.004 | 1.250 | 1.380 |
| B10 | A10 | 5/8 | 7/8 -14 UNF-2 | 1 | .484 | | 1.450 | 1.620 |
| B12 | A12 | 3/4 | 1-1/16-12 UN-2 | 1-1/4 | .609 | ±.005 | 1.660 | 1.750 |
| B14 | A14 | 7/8 | 1-3/16-12 UN-2 | 1-3/8 | .718 | | 1.730 | 1.780 |
| B16 | A16 | 1 | 1-5/16-12 UN-2 | 1-1/2 | .844 | +.007-.005 | 1.810 | 2.000 |
| B20 | A20 | 1-1/4 | 1-5/8 -12 UN-2 | 2 | 1.078 | +.008-.005 | 2.060 | 2.310 |
| B24 | A24 | 1-1/2 | 1-7/8 -12 UN-2 | 2-1/4 | 1.312 | | 2.330 | 2.590 |
| B32 | A32 | 2 | 2-1/2 -12 UN-2 | 2-7/8 | 1.781 | +.010-.005 | 3.060 | 3.380 |

*NOTES:*

1. MATERIAL: Steel, carbon in accordance with procurement specification.
   Steel, corrosion resisting in accordance with procurement specification.
2. PROTECTIVE COATING: Cadmium plated in accordance with procurement specification.
   Zinc plated in accordance with procurement specification.
   Phosphate coating in accordance with procurement specification.
   Passivation treatment in accordance with procurement specification.
3. DIMENSION AND TOLERANCE: Dimensions and tolerances not shown shall be in accordance with the SAE Standard for 37 Degree Flared Fittings (SAE J514).
4. THREADS: Threads shall be in accordance with Screw-Thread Standard for Federal Services, Handbook H28.
5. PART NUMBER: The MS part number consists of the MS number plus the dash number.
   A. For body only, cadmium plated, use the MS number, plus the body dash number. Example: MS51524B2.
   B. For complete assembly (with nuts and sleeves), cadmium plated, use the MS number, plus the assembly dash number. Example: MS51524A2.
   C. For zinc coating add (Z) to the dash number. Example: MS51524B2Z or MS51524A2Z.
   D. For phosphate coating add (P) to the dash number. Example: MS51524B2P or MS51524A2P.
   E. For corrosion-resisting steel add (S) to the dash number. Example: MS51524B2S or MS51524A2S.
6. For design feature purpose, this standard takes precedence over procurement documents referenced herein.
7. Reference documents shall be of the issue in effect on date of invitations for bid.
8. The illustration is for identification purpose only and is not intended to restrict designs and shapes not dimensioned.
9. (A) After 17 January 1979 bodies will be used for production only and SHALL NOT be stocked for maintenance. Existing stock of bodies should be used until depleted.

REVIEWER: CS-EL-ME
USER: AT-MC-YD

APPROVED 20 DEC 1971 REVISED (A) 17 JANUARY 1979

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

| | | |
|---|---|---|
| P.A. AR<br>Other Cust OS | TITLE: TEE, TUBE TO SWIVEL, SWIVEL ON BRANCH, 37° FLARED | MILITARY STANDARD<br>MS51524 |
| PROCUREMENT SPECIFICATION<br>MIL-F-18866 | SUPERSEDES: | SHEET 1 OF 1 |

DD FORM 672-1 (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:06Z
Check the source to verify that this is the current version before use.