FED. SUP CLASS
4030




TABLE I

DASH NUMBER	CHAIN SIZE	A REF	B MAX	B MIN	C MIN	PROOF LOAD (POUNDS)	APPROXIMATE WEIGHT (POUNDS)
1	1/4	2.25	.44	.35	.44	2,250	0.4
2	5/16	2.59	.47	.44	.53	3,400	0.5
3	3/8	2.88	.56	.47	.59	4,650	0.8
4	7/16	3.25	.52	.56	.62	6,250	1.3
5	1/2	3.69	.59	.62	.72	8,250	1.8
6	5/8	4.62	.78	.69	.84	12,500	2.8
7	3/4	5.84	.94	.78	.94	17,700	4.2

NOTES:

1. MATERIAL: Forged carbon steel, in accordance with procurement specification.
Ⓐ 2. PROTECTIVE COATING: Zinc coating (hot dip galvanized) in accordance with ASTM A153, with supplementary chromate treatment in accordance with MIL-C-17711.
3. DIMENSIONS: All dimensions are in inches unless otherwise specified.
4. PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS51827-1
5. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
6. Reference documents shall be of the issue in effect on date of invitations for bid.
7. The illustration is for identification purpose only and is not intended to restrict designs or shapes not dimensioned.

Ⓑ CANCELED AFTER 4 MAY 1988.

NO SUPERSEDING STANDARD.

APPROVED 26 MAY 1966 REVISED Ⓐ 21 MAR 1973 Ⓑ 4 MAY 1988

REVIEWER EL GL IS ME 82
USER AT AV MC OS YD SH

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. WC / Other Cust 82	TITLE: HOOK, GRAB, DIRECT EYE	MILITARY STANDARD MS51827
PROCUREMENT SPECIFICATION HR-C-271	SUPERSEDES SCAX3	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. (Project 4030-N018)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:09Z
Check the source to verify that this is the current version before use.