[Metric]
A-A-136B
December 4, 1995
Superseding
A-A-136A
April 2, 1991

COMMERCIAL ITEM DESCRIPTION
HOLDER, TELEPHONE RECEIVER

The General Services Administration has authorized the use of this commercial item description.

1. **SCOPE**: This commercial item description covers attachable shoulder telephone receiver holders intended to enable the user to balance the telephone receiver during calls, thereby freeing both hands.

2. **SALIENT CHARACTERISTICS:**

2.1 The holder shall be black.

2.2 The holder shall be made of commercially acceptable high impact plastic, a suitable corrosion resistant metal, or a combination of both. It shall be designed to fit standard telephone receivers.

2.3 The holder shall be constructed of a receiver holder and a shoulder cradle. The two pieces shall be joined by a screw or commercially appropriate fastening device. The device shall be receded in the padding.

2.4 The shoulder cradle shall be lined on the underside with a protective cushioning pad made of rubber, sponge or commercially appropriate material capable of meeting all requirements of this CID. The cushioning pad shall be no less than 0.125 inches thick.

2.5 The shoulder cradle shall be curved in accordance with normal commercial practice to provide a balance fit on the user's shoulder.

2.6 The holder shall be adjustable to allow maximum balance on the user's shoulder.

2.7 The holder shall be have a fastening device to provide a secure attachment to the telephone receiver. The fastening device shall be designed so as not to mar or damage the telephone or the holder.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

2.8 The shoulder cradle shall be no less than 13.97 cm (5-1/2") (length) by 2.54 cm (1") (width).

2.9 Each holder shall have a set of assembly instructions printed on the unit or included in, or on each package.

2.10 Workmanship:

The Receiver Holder and Shoulder Cradle (whether metal or plastic) shall be free of defects, including, but not limited to, burrs, niches, dents, rough or sharp edges, scratches, blisters, crinkling, imbedded foreign matter, discoloration or imperfections which will impair serviceability and affect the appearance or which might constitute a personal hazard to the user.

2.11 Corrosion Resistance:

All metal parts shall be resistant to corrosion. Individual parts shall be either corrosion resistent stainless or anodized, plated, painted, finished with baked enamel, subjected to a bluing process, or whatever is commercially appropriate for the specific function of the part. Contractor shall provide a manufacturer's chemical certification of corrosion resistance, upon request by the Government.

3. REGULATORY REQUIREMENTS:

The offeror is encouraged to use recovered materials in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Certification: The contractor shall certify that if polystyrene is used in the manufacture of this item, it shall contain a minimum of 25 percent Postconsumer Recovered Materials in accordance with the 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Material; Final rule. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4. QUALITY ASSURANCE PROVISIONS:

4.1 Contractor Certification. The contractor shall certify and maintain substantial evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4.2 Suppliers are encouraged to use quality control (QC) techniques that exhibits control over their processes (e.g. Statistical process Controls). These techniques shall ensure quality levels equal to, or greater than, those cited in the applicable technical document or herein. For those product characteristics which are controlled by such a method, requirements for end item inspection or test may be considered to have been met. End item inspection / testing may be used by the offeror, or the Government representative, as a means to determine the effectiveness of the inprocess quality controls. Inprocess controls shall not be substituted for end item performance testing, unless it can be demonstrated that there exists a direct correlation between the process and product performance, such that end item performance testing is obviated.

For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / shall be required. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society of Quality Control (ASQC) ANSI/ASQC Z1.4 1993, Sampling Procedures and Tables for Inspection by Attributes.

4.3 For Visual and Dimensional inspections the level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 Percent Defective. The sample unit shall be one holder. The supplier must provide objective evidence (test and inspection records) that the presented material meets the requirements of this Commercial Item Description.

5. Preservation, packing and marking shall be specified in the contract or Order.

6. NOTES

6.1 REFERENCED DOCUMENTS: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

6.1.1 Federal Regulations:
Federal Acquisition Regulations. Paragraph 23.403
Title 40 code of Federal Regulations Protection of Environment, Part 247.
Copies of the U.S. Code of Federal Regulations may be purchased with a VISA, Master Card or prepaid check through: Government Printing Office Washington, DC. Telephone (202)783-3238. When ordering, ask for Title 40, Parts 190-250, Stock Number: 869-013-146-0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

6.1.2 Application for copies of the ASTM test methods should be addressed to the American Society for Testing and Material; 1916 Race Street, Philadelphia, PA 19103.

6.1.3 Application for copies of ANSI/ASQC Procedures should be addressed to
ANSI/ASQC Z1.4-1993
American Society of Quality Control
P.O. Box 3005
611E Wisconsin Avenue
Milwaukee, WI 53201-4606

6.2 Ordering Information: Purchasers shall select the required options permitted herein, and include the following information in procurement documents:

A. Title, number, and date of this commercial item description.
B. Purchasers shall specify packaging, packing, and any special marking.
C. Purchasers shall specify identification marking, if other than required.

6.3 National Stock Number Listing:

7520-00-520-8847

MILITARY INTERESTS:
NONE

PREPARING ACTIVITY:
GSA-FSS

DoD has determined that no military activity has an official interest in this Commercial Item Description.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

whenever 4.4 Performance Characteristics Tests: Testing shall be performed on components w