INCH-POUND

A-A-3152A
July 30, 2002
SUPERSEDING
A-A-3152
January 8, 1998

COMMERCIAL ITEM DESCRIPTION

SCREWDRIVER, JEWELERS', SWIVEL KNOB

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This Commercial Item Description covers swivel knob jewelers' screwdrivers, both metal and anti-static plastic, with interchangeable or fixed blades, as individual screwdrivers, and or sets..

2. CLASSIFICATION.

2.1 Type 1 – Swivel knob, metal handle body, interchangeable blades.

2.2 Type 2 – Swivel knob, plastic, anti-static handle body, fixed blades.

2.3 Type 3 – Swivel knob, plastic, anti-static handle body, interchangeable blades.

3. SALIENT CHARACTERISTICS.

3.1 Design. Screwdrivers shall be similar to Figure I, II, or III in construction. The illustrations shown are for identification and not intended to preclude the purchase of screwdrivers which we otherwise in accordance with the requirements of this commercial item description.




Figure I. Type 1 – Swivel knob, metal handle body, interchangeable blades.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Hardware Super Store (6FEE), 1500 E. Bannister Rd. Bldg. #6, Kansas City, Missouri 64131.

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.



Figure II. Type 2 -Swivel knob, anti-static, plastic handle body, fixed blades.




Figure III. Type 3 -Swivel knob, anti-static, plastic handle body, interchangeable blades.

3.2 Material.

3.2.1 Screwdriver Bits. The screwdriver bits shall be made of high grade alloy steel hardened and tempered to comply with the specified physical and mechanical requirements.

3.2.2 Type 1 - Handle Screwdriver Body. The body shall be of steel or aluminum. The swivel knob shall be fabricated of metal or plastic. The chuck shall be made of steel.

3.2.3 Type 2 - Handle Screwdriver Body. The body and swivel knob shall be fabricated of plastic such as but not limited to cellulose acetate. When specified by the purchaser, the body and swivel knob shall be made of anti-static plastic.

3.2.4 Type 3 - Handle Screwdriver Body. The body and swivel knob shall be fabricated of plastic such as but not limited to cellulose acetate. When specified by the purchaser, the body and swivel knob shall be made of anti-static plastic. The chuck shall be made of steel.

3.3 Construction.

3.3.1 Screwdriver Bits. The screwdriver bits shall be hardened and tempered to comply with the specified physical and mechanical requirements. The cross-sectional shape of the blade shall be round. The blades shall be free from visible defects such as scale, seams, laps, and cracks.

3.3.1.1 Type 1 and Type 3 - Interchangeable Screwdriver Bits. The extreme shank end of each blade shall be flattened on two sides to seat firmly and shall be a good fit in the chuck jaw. The bit shank shall have a nominal diameter of 0.100 inch +/- 0.002 inches. The nominal bit lengths shall be 1.75 +/- 0.25 inch.

3.3.1.2 Flat Tip Screwdriver Bit. The blade tip(s) shall be of the type known commercially as cabinet tip, the straight sides being approximately parallel to the blade shank. Traditional jewel's screwdriver flat tip dimensions (not covered by ASME BI07.15-1993) shall be as shown in Table I Flat Tip Screwdriver Dimensions. Additional and/or larger flat tip sizes shall be in accordance with ASME BI07.15-1993.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

FLAT TIP DIMENSIONS

Width of Tip +/-.005 Inch	Thickness of Tip at End +0.003/-0.002 Inch
0.025	0.004
0.040	0.004
0.055	0.006
0.070	0.006
0.080	0.008
0.100	0.010

Table I. Flat Tip Screwdriver Dimension.

3.3.1.3 Phillips Cross Tip Screwdriver Bit. The blade tip(s) shall be of the type known commercially as Phillips tip and be manufactured in accordance with ASME B107.15-1993.

3.3.1.3 Hex and Spline Screwdriver Bit. The blade tip(s) shall be of the type known commercially as male hexagonal tip or male spline tip and be manufactured in accordance with ASME/ANSI B18.3 or ASME/ANSI B18.3.2 for sizes included with ASME/ANSI B18.3 or ASME/ANSI B18.3.2.

3.3.1.4 Other Tip Styles and Sizes. Other tip styles such as but not limited to Torx, Pozidrive, Square Recess, Clutch Head, Frearson, Torq-Set; and other tip sizes not includes in applicable above mentioned industrial standards shall be in accordance with acceptable industrial practice and be functionally and dimensionally compatible with the fasteners they are designed to remove and install. It is the intent of this CID to provide the purchaser a vehicle to procure traditional jeweler's swivel knob screwdrivers and swivel knob micro fixed blade screwdrivers with any commercially available tip style.

3.3.2 Screwdriver Body.

3.3.2.1 Type 1, Swivel Knob, Metal Handle Body, Interchangeable Blades. The body shall be cylindrical in shape, and neatly knurled to provide a comfortable handgrip. The handle shall have a minimum nominal diameter of 1/4 inch and shall have a minimum length of 2-3/4 inches. One end of the body shall have a chuck which will securely hold interchangeable blades. The other end shall have a swivel-type knob. The swivel knob shall be not less than 1/2 inch across flats.

3.3.2.2 Type 2, Swivel Knob, Plastic, Anti-Static, Handle Body, Fixed Blades. The body shall be shaped to provide a comfortable handgrip. The handle shall have a minimum nominal diameter of 1/4 inch and shall have a minimum length of 2-1/2 inches. One end of the body shall have a blades securely attached. The other end shall have a swivel-type knob. The swivel knob shall be not less than 1/2 inch across flats or in diameter.

3.3.2.3 Type 3, Swivel Knob, Plastic, Anti-Static, Handle Body, Interchangeable Blades. The body shall be shaped to provide a comfortable hand grip. The handle shall have a minimum nominal diameter of 1/4 inch and shall have a minimum length of 2-1/2 inches. One end of the body shall have a chuck which will securely hold interchangeable blades. The other end shall have a swivel-type knob. The swivel knob shall be not less than 1/2 inch across flats or in diameter.

3.4 Finish.

3.4.1 Screwdriver Bits. The screwdriver bits shall have a smooth, bright polish finish that will produce a 63 micro-inch roughness height rating, or better. When tested in accordance with ASME B46.1, the roughness height rating shall be as specified on all exposed portions other that the tip vicinity. The blades shall be treated in a manner to prevent rust or corrosion. Plating, if any, shall be adherent. There shall be no evidence of plating peeling, or chipping. Cadmium plating will not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

acceptable.

3.4.2 Screwdriver Body Assembly. All parts subject to corrosion shall be protected by nickel plating or other suitable and equally effective means, except cadmium plating will not be acceptable.

3.5 Blade Hardness. The blade hardness shall be 48 to 62 on the Rockwell C scale. When tested in accordance with ASTM E-18, the hardness will be measured as close to the tip as possible and shall be as specified.

3.6 Sets. The components of sets shall conform to the specified requirements for the individual items. Sets shall be provided in an indexed case or pouch unless otherwise specified by the purchaser.

3.7 Identification Marking. The jewelers' screwdriver shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

4. REGULATORY REQUIREMENTS

4.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pounds units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. PRODUCT CONFORMANCE

5.1 Product Conformance. The product provided shall meet the salient characteristics of the Commercial Item Description, conform to the producer's own drawing, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marked. The government reserves the right to require proof of such conformance.

6. PACKAGING. Preservation, packaging and marking shall be as specified in the contract or order.

7. NOTES. This section contains information of a general or explanatory nature that is not mandatory.

7.1 Source of Documents.

Federal Acquisition Regulation (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

American Society for Testing Materials (ASTM), 100 Barr Harbor Drive; West Conshohocken, PA 19428- 2959.

American Society of Mechanical Engineers (ASME), 3 Park Avenue; New York, NY 10016.

American Society for Quality Control (ANSI/ASQC Z1.4): P.O. Box 3005; 611 East Wisconsin Avenue, Milwaukee, WI 53201-4606.

GSA Specification Section (3FP-E), Suite 8100, 470 L 'Enfant Plaza, SW; Washington, DC 20407.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

7.2 National Stock Numbers (NSN's). The following list of NSN's corresponds to the types, classes, and sizes specified in this CID. This list may not be indicative of all possible NSN's associated with this CID.

Type	Tip Size	NSN Screwdriver With 1 each Bit	NSN Bit Only Nominal Length 1.75 +/- 0.25 Inch
1	0.025	5120-00-180-0705	5120-00-293-2055
1	0.040	5120-00-180-0706	5120-00-293-2050
1	0.055	5120-00-180-0727	5120-00-293-2051
1	0.070	5120-00-180-0728	5120-00-293-2052
1	0.080	5120-00-180-0729	5120-00-180-0887
1	0.100	5120-00-180-0730	5120-00-293-2056

Type	Handle, Screwdriver Jewelers' Without Bit
1	5120-01-060-9243

Components of Set 5120-00-288-8739 6 Screwdrivers With Bits	Components of Set 5120-01-119-2570 1 Handle, 6 Bits	Components of 1 Handle, 2 Bits Sizes 0.70 & 0.100	Screwdriver With Spring Actuated Blade - 0.055
5120-00-180-0705	5120-01-060-9243	5120-00-446-2860	5120-00-585-7878
5120-00-180-0706	5120-00-293-2055		
5120-00-180-0727	5120-00-293-2050		
5120-00-180-0728	5120-00-293-2051		
5120-00-180-0729	5120-00-293-2052		
5120-00-180-0730	5120-00-180-0887		
	5120-00-293-2056		

7.3 Ordering data. Purchasers should select the preferred options permitted herein and shall include the following information in procurement documents.

(a) Title, number, and date of this Commercial Item Description.
(b) The appropriate NSN.
(c) The type, tip style, and size of each individual screwdriver.
(d) The type, tip style, and size of each screwdriver within each set.
(e) Individual blades or handles as required.
(f) If anti-static plastic handles are required (Type 2 and Type 3 only).
(g) Packaging requirements.

For example, the following typical lot sampling requirements would be specified in the contract:

7.4 Key words. Screwdriver, Jewelers', Swivel Knob.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.

A-A-3152A

MILITARY INTERESTS:

NOTE: DOD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:30Z
Check the source to verify that this is the current version before use.