MIL-B-45993(AL)
21 February 1984
SUPERSEDING
T&E PD-94A
10 April 1979

MILITARY SPECIFICATION

BEAD BREAKER, PNEUMATIC TIRE, PORTABLE

AIR OR AIR OVER HYDRAULIC OPERATED

This specification is approved for use by the US Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1 SCOPE

1.1 Scope. This specification covers an air or air over hydraulic operated portable hand held tire bead breaker for the wheel/tire assemblies of military vehicles and all commercial vehicles with the size range specified herein.

2 APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-LEE-S, Rock Island, IL 61299 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4910

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-T-60	- Tape: Packaging, Waterproof

MILITARY

MIL-P-116	- Preservation - Packaging, Methods of
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-C-4109	- Coupling Halves, Low Pressure, Air Hose, Quick-Disconnect
MIL-C-5501	- Caps and Plugs, Protective, Dust and Moisture Seal
MIL-H-13531	- Hose, Rubber and Hose Assembly, Rubber (Hydraulic Flexible)
MIL-F-17111	- Fluid, Power Transmission

STANDARDS

FEDERAL

FED-STD-H28	- Screw Thread Standards for Federal Services

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-130	- Identification Marking of US Military Property

2.1.2 Other Government document, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

D7353294	- Standard Military Wheels
D7353762	- Standard Military Wheels
D7353765	- Standard Military Wheels
D7355430	- Standard Military Wheels
D7355436	- Standard Military Wheels
D7355439	- Standard Military Wheels
D7387807	- Standard Military Wheels
D7388452	- Standard Military Wheels
D7388820	- Standard Military Wheels
D7389618	- Standard Military Wheels
D7389621	- Standard Military Wheels

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

JACK INSTITUTE

JI-100 - Hydraulic Jack Fluid

(Application for copies should be addressed to the Jack Institute, Inc., 1326 Freeport Road, Pittsburgh, PA 15238).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE HANDBOOK

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., Two Pennsylvania Plaza, New York, NY 10001.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951-82 Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3 REQUIREMENTS

3.1 First article. When specified (see 6.2), the supplier shall furnish three complete bead breakers for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification. In event of significant design changes during the course of production, an additional production item shall be furnished for first article inspection for each such change prior to shipment of the changed item.

3.2 Design. The bead breaker shall be designated to separate a tire bead from the wheel rim. It shall be capable of being operated by one person. It shall break beads of all tube and tubeless type tires from flat-base and drop center automotive rims within a tire size range of 7.00 by 16 through 14.00 by 24 (see Table I). The bead breaker shall consist of a hand held rim clamping and bead breaking assembly operated by air, or a hand held air over hydraulic pump assembly. Additional tools, adapters, or devices shall not be required for fastening or positioning on wheel to perform the bead breaking operation. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

bead breaker shall perform all requirements herein without malfunction, breakage, damage or deformation of any component, leakage, or damage to the tire or rim. Total weight of the bead breaker, with pump and hose assembly, shall not exceed 50 lbs.

NOTE: Damage to the tire bead and sidewalls constitutes internal and external structure damage and gouging, tearing, cutting or slitting of the tire structure or carcus. Damage to the rim flange and bead seat band constitutes permanent deformation of the metal beyond its initial manufactured state. Superficial scratches or surface dents that do not change or modify the initial configuration of the rim/wheel assembly shall not be considered to be deforming in nature.

3.2.1 Maintainability. Design and configuration of the bead breaker and the adjustment features shall assure that maintenance of operational capability and accuracy will be reduced to the simplest procedures and require a minimum of skills and common maintenance equipment. Instructions for disassembly, repair, assembly, and adjustment will be clear, concise, and definitive in application.

3.3 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the bead breaker presenting safety hazards which can be guarded without substantial interference to operation of the bead breaker. All guards shall be removable to provide access to guarded parts.

3.4 Construction. The bead breaker shall be complete so that when connected to an air supply it can be used for the operations specified herein.

3.4.1 Parts and materials. All parts and materials used in fabrication may be virgin, recycled or reclaimed materials free of defects and imperfections that might affect safety, performance, serviceability, or appearance of the finished product. Contact between dissimilar metals, especially aluminum or magnesium in contact with steel, copper or brass, shall be avoided wherever possible.

3.4.2 Interchangeability. All parts shall be manufactured to such standards as will permit replacement and adjustment without modification of parts or machine.

3.4.3 Castings and forgings. All castings and forgings shall be free of defects and mismatching. No process shall be used for reclaiming any defective parts.

3.4.4 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. These operations shall not be employed as a repair measure for defective parts.

3.4.5 Fastening devices. All screws, pins, bolts and similar parts shall be installed in such a manner as to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently deformed.

3.4.6 Threads. Screw threads shall be in the inch system and shall conform to FED-STD-H28.

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:36Z
Check the source to verify that this is the current version before use.

3.5 Components and product characteristics.

3.5.1 Rim clamping and bead breaker assembly. The bead breaker assembly shall consist of a mechanism to perform the action of clamping the bead breaker assembly onto the rim and simultaneously applying a progressive clamping and wedging force between the tire bead and the rim flange. The component(s) which effect breaking of the tire bead from the rim shall maintain metal to metal contact with the rim flange as it follows the rim contour down the rim bead seat. No repositioning of the bead breaker assembly shall be required once the rim clamping, wedging action has begun. The component(s) which effect breaking of the tire bead from the rim, shall not slip from the tire bead to the tire sidewall during the bead breaking operation. While the progressive clamping is sustained (or increased) the bead breaking component shall further depress the tire bead along the rim bead seat to break the tire bead free. When actuating pressure is released by the operator, the bead breaker component(s) shall automatically return to their retracted position. The assembly may be repositioned and the bead breaking operation reperformed around the tire and rim assembly for total separation of the tire bead from the rim. As a minimum, the bead breaker shall be capable of breaking the tire beads from the rims/wheels specified in paragraph 3.2 and Table I. As a minimum, the assembly shall have a rim width clamping range from 3/4 inch to 3 1/2 inch and a pressure foot travel of 3 1/2 inches.

3.5.2 Air actuated bead breaker. The air actuated bead breaker shall comply with the stated performance requirements specified in 3.5.1. It shall be actuated by an air (only) supply from 95 to 105 pounds per square inch.

3.5.3 Air over hydraulic bead breaker.

3.5.3.1 Air over hydraulic pump assembly. The bead breaker shall be actuated by an air driven hydraulic pump activated by a foot treadle. The air over hydraulic pump assembly shall be capable of developing sufficient pressure for operation of the rim clamping and bead breaker assembly as specified (see 3.5.1). The air supply pressure for operation of pump assembly shall be within the range of 95 to 105 pounds per square inch. The pump shall be provided with a built-in safety overload valve and a control valve to allow instant release or pumping action. The reservoir shall have ample capacity for the total displacement of the bead breaker. A metal embossed warning plate stating "CAUTION: DO NOT USE HYDRAULIC BRAKE FLUID. USE ONLY LIGHTWEIGHT PETROLEUM BASE HYDRAULIC FLUID" shall be attached near the filler plug of the pump reservoir. The hydraulic reservoir of each bead breaker supplied shall be filled to the manufacturer's recommended operating level with hydraulic fluid conforming to MIL-F-17111 or Jack Institute JI-100.

3.5.3.2 Hydraulic hose assembly. The bead breaker hose assembly between the pump and bead breaker assemblies shall be not less than 72 inches long. Hose shall comply with requirements of Standard SAE J517-100R2A or MIL-H-13531, Type II, Class B. Each end of the hose shall be furnished with a wire spring guard.

3.5.3.3 Hydraulic quick disconnect coupling. There shall be a quick disconnect coupling between the air over hydraulic pump assembly hose and the bead breaker assembly. It shall be of the double end shutoff type with 360 degrees swivel action and dust caps.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

3.5.4 Air line quick disconnect couplings. There shall be two quick disconnect couplings provided. They shall be the Type I, Style 2 and the Type II, Style 1 of MIL-C-4109. The Type II, Style 1 shall be attached to the bead breaker air line port.

TABLE I. Standard military design wheels.

Tire Application	Military Dwg. No. of Military Design	Budd Co. Part No. of Military Design	Budd Co. Part No. of Commercial Counterpart
12.00-20 Dual 14 Ply	D7353294	1/ R66380-8	2/ R45520-2
14.00-20 Dual 12, 18 & 20 Ply	D7353762	66550-8	3/
14.00-20 Single 12, 18 & 20 Ply	D7353765	66560-8	2/ R92060
9.00-15, 10.00-15 Dual, 12 & 14 Ply	D7355430	66630-8	2/ R74910-3
9.00-16 Dual 8 Ply	D7355436	66730-1	2/ R48750-1
14.00-24 Dual 18 & 20 Ply	D7355439	66620-8	2/ R47820-2
7.00-16 Single 6 Ply	D7387807	3/	3/
9.00-16 Single 8 Ply	D7388452	1/ R48750-1	2/ R48750-1
10.00-20, 11.00-20 Dual 12 Ply 11.00-20 Single	D7388820	1/ R65950-8	2/ R45520-2
11.00-20 Single 12.50-20 Single 12 Ply	D7389618	1/ R66280-8	2/ R66640-3
9.00-20 Dual 8, 10-12 Ply	D7389621	1/ B65890-8	2/ R66640-3
9.50R-16.5D 8 Ply	None	Chrysler Co. Part No. 4/	4026506

Source: https://assist.dla.mil -- Downloaded: 202640-22T04:36Z
Check the source to verify that this is the current version before use.

NOTES:
1/ Indicates Budd Co. or their distributors.
2/ Budd Co. commercial counterpart wheels which may be used for design and test purposes when the military type is not available.
3/ Information not available.
4/ Available from Chrysler Co. only.

3.6 Painting. Unless otherwise specified (see 6.2), painting and finishing of the bead breaker shall be in accordance with the supplier's standard practice.

3.7 Identification marking. The bead breaker shall be marked for identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2), shall include the National Stock Number.

3.8 Workmanship. The bead breaker, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, scale and sharp edges; marking of parts and assemblies; thoroughness of welding, brazing, painting, and riveting; alignment of parts and tightness of assembly screws and bolts.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. First article inspection shall be applied to the preproduction model or initial production item and to the first item produced subsequent to a significant design change in accordance with 3.1. Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.3 and the tests in 4.4 and 4.5. Failure of the first article to pass examination inspection or the the tests shall be cause for rejection of the unit.

4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to production items being offered for acceptance under the contract. Quality conformance inspection shall consist of a. through c. as follows. Failure of an item to pass an examination or test shall be cause for rejection of the unit.

a. Examination (see 4.3).
b. Performance tests (see 4.4).
c. Packaging inspection (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

4.2.2.1 Sampling. Sampling shall be in accordance with MIL-STD-105 and the following:

EXAMINATION/TEST	LEVEL	AQL
Examination (see 4.3)	II	1.0
Performance tests (see 4.4) (Does not apply if alternate test procedure is used)	S-4	1.5
Packaging inspection (see 4.6)	S-4	4.0

4.3 Examination. The bead breaker shall be examined to determine compliance with section 3 herein and the contract using the following checklist as a guide.

EXAMINATION CHECK LIST

CHARACTERISTICS	REQUIREMENT PARAGRAPH
Design (incl weight limit)	3.2
Maintainability	3.2.1
Safety and health requirement	3.3
Construction	3.4
Parts and materials	3.4.1
Interchangeability	3.4.2
Castings and forgings	3.4.3
Welding, brazing, or soldering	3.4.4
Fastening devices	3.4.5
Threads	3.4.6
Components and product characteristics	3.5
Rim clamping and bead breaker assembly	3.5.1
Bead Breaker	3.5.2 or 3.5.3
Pump assembly	3.5.3.1
Hose assembly	3.5.3.2
Hydraulic coupling	3.5.3.3
Air line coupling	3.5.4
Painting	3.6
Identification marking	3.7
Workmanship	3.8

4.4 Performance tests.

4.4.1 Performance test. Each bead breaker under test shall be operated in accordance with the manufacturers instructions to break the beads on both sides of tire sizes 14.00 x 24, 20 ply and 7:00 x 16, 6 ply. Each test bead breaker shall be used on both of these tire and rim assembly sizes. All tires used in testing shall be obtained from vehicles that have been in service in order that conditions will be encountered similar to those found under actual field conditions. Air supply pressure shall be as prescribed in 3.5.2 and 3.5.3. Inability of the bead breaker to break the tire bead free from the wheel rim or evidence of any hydraulic fluid leakage or bead breaker malfunction or damage during operation shall be cause for rejection. The tire shall be removed and examined for damage to the beads and sidewalls, and the rim flange and bead seat band shall be examined for deformation and gouging. The tire shall be mounted and inflated in accordance with the tire manufacturer's instructions and examined for leaks due to damage or deformation caused by the bead breaker (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

NOTE: ALTERNATE PERFORMANCE TEST PROCEDURE:

4.4.2 Alternate performance test. The following may be implemented as an alternate to the test requirements of 4 4.1 above:

a. A contractor developed test simulator may be used to duplicate the motion and forces imposed on the bead breaker. The simulator forces must be equal to the forces encountered in breaking actual tires from their rims. The 3 1/2" pressure foot travel must also be duplicated. Drawings and operational characteristics of the simulator shall be approved by the Government before the simulator may be used for final acceptance inspection.

b. Contour gages shall be provided to check the shape of the pressure foot that contacts the tire to separate the tire from the rim. Contour gages shall also be provided for critical bead breaker body component dimensions that interface with the tire and wheel assembly. The dimensions involved, gage material, method of applying gages, and accept/reject criteria shall be approved by the Government before the gages may be used for final acceptance inspection.

c. The test procedure shall be as follows:

(1) Each bead breaker shall be subjected to a 3 cycle function test on the simulator.

(2) Each bead breaker shall have its critical body component dimensions and pressure foot (feet) 100 percent inspected using the contour gages.

(3) Four bead breakers from a lot size of 500 or one month's production, whichever is smaller, will be function tested on a wheel and tire combination specified in Table I (one complete wheel and tire assembly per bead breaker).

d. Failure to meet the alternate performance test shall require the contractor to:

(1) Conduct a failure analysis study, performing a dimensional, physical, and visual examination, as required, of the component(s) or condition(s) suspected to be the cause of failure.

(2) Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect in future production.

(3) Provide satisfactory objective evidence of the results of the failure analysis and corrective actions to the Government representative prior to submitting the reconditioned bead breakers for retest.

4.5 Rim clamping and bead breaker assembly test. The bead breaker shall be tested as in 4.4 to determine compliance with 3.5.1, including capability throughout the range of specified tire and wheel sizes, including each tire size listed in Table I. Inability of the bead breaker to break the bead free from the wheel rim and to perform the function and procedure described in 3.5.1 shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

4.6 Packaging inspection. Preservation, packing, and marking of the bead breaker shall be inspected to determine compliance with section 5.

5 PACKAGING

5.1 Preservation. Preservation shall be level A or B or industrial, as specified. Level B preservation shall be the same as level A (see 6.2).

5.1.1 Level A and B preservation.

5.1.1.1 Cleaning and drying. Components of the bead breaker shall be cleaned and dried in accordance with the applicable procedures of MIL-P-116.

5.1.1.2 Preservative application. All exposed, critical ferrous metal surfaces of the bead breaker shall be coated with type P-2 preservative. Non-critical, unpainted, ferrous metal surfaces shall be coated with a preservative compound conforming to type P-1. When applicable, the interior surface of the air motor shall be preserved with type P-10, grade 30 preservative oil. Preservatives specified and the procedures for application shall conform to MIL-P-116.

5.1.1.3 Unit protection. The method of unit protection for the bead breaker shall conform to method I to MIL-P-116. Surfaces coated with type P-2 preservative oil shall be covered with barrier material conforming to MIL-B-121, grade A. The material shall be secured in place with tape conforming to PPP-T-60, type optional. Plastic cap-plugs conforming to MIL-C-5501 shall be placed over the metal threads of the air and hydraulic fittings. The bead breaker assembly along with the hydraulic hose (see 5.1.1.3.1) and the technical data (see 5.1.1.3.2) shall be packaged in a close-fitting fiberboard box conforming to PPP-B-636, grade V3c. Sufficient blocking, as specified in MIL-P-116, shall be applied to immobilize the contents of the box. The box closure shall be in accordance with the appendix to the container specification.

5.1.1.3.1 Hose assembly. The hose assembly shall be coiled to a minimum safe diameter and secured with cotton tape or twine to prevent uncoiling. The hose shall be packaged in accordance with method IC-3 of MIL-P-116.

5.1.1.3.2 Technical data. Publications issued with the bead breaker shall be packaged in accordance with method IC-1 of MIL-P-116.

5.1.2 Industrial preservation. The bead breaker shall be cleaned, preserved and packaged in accordance with the criteria and guidelines of ASTM D3951-82 (see 6.2).

5.2 Packing. Packing shall be level A or B, or industrial, as specified (see 6.2).

5.2.1 Level A packing. Four each bead breakers shall be packed in a snug-fitting shipping container conforming to PPP-B-601, overseas type. The box closure shall be in accordance with the appendix to the container specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Packing requirements shall be the same as for level A (see 5.2.1), except, the shipping container shall conform to PPP-B-601, domestic type.

5.2.3 Industrial packing. Industrial packing of the bead breaker shall conform to ASTM D3951-82.

5.3 Marking.

5.3.1 Military marking. Bead breakers packaged and packed in accordance with level A or level B requirements (see 5.1.1, 5.2.1, and 5.2.2) shall be marked in accordance with MIL-STD-129.

5.3.2 Industrial marking. Bead breakers packaged and packed in accordance with industrial requirements (see 5.1.2 and 5.2.3) shall be marked in accordance with ASTM D3951-82.

6 NOTES

6.1 Intended use. The bead breakers covered by this specification are portable bead breakers for use in field shops to facilitate tire removal from military vehicles and commercial light and heavy trucks. It is intended for use to break beads of tube and tubeless type tires from flat-base and drop center passenger car and truck/bus rims within the tire size range of 7.00 by 16 through 14.00 by 24.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. First article, when required (see 3.1).
c. Name plate, if different (see 3.7).
d. First article inspection, if different (see 4.2.1).
e. Degree of preservation and packaging, and degree of packing required (see 5.1, 5.1.2 and 5.2).

Custodian:
Army - AL

User interest:
Army - ME

Preparing activity:
Army - AL

Project No. 4910-A561

☆ U.S. GOVERNMENT PRINTING OFFICE: 1984—705—040/A1530

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

US ARMAMENT MUNITIONS and CHEMICAL COMMAND[
Attn: DRSMC-LEE-S
Rock Island IL 61299

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T04:36Z
Check the source to verify that this is the currentversion before use.