MILITARY SPECIFICATION

HOWITZER, MEDIUM, TOWED, 155MM: M198

This amendment forms a part of Military Specification MIL-H-45984B (AR), dated 22 October 1984, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.3.3.5, Rod pull curves, change: "Range 1: Peak rod pull shall occur within the first 20 miliseconds for long recoil, and 60 miliseconds for short recoil." to: "Range 1: Peak rod pull shall occur within the first 20 milliseconds for long recoil."

Change: "Range 2: Within 280 miliseconds (max.) for long recoil or 180 miliseconds (max.) for short recoil, the continuous rod pull shall not exceed the peak rod pull of Range 1." To: "Range 2: For long recoil, the continuous rod pull curve shall not exceed the peak rod pull of Range 1. For short recoil (900mils and above) the maximum rod pull shall not exceed the peak rod pull in Range 1 by more than 6000 lbs."

PAGE 8

Figure 1: For short recoil sketch only, delete: "Note 1".

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1025-A143)

FSC 1025

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:34Z
Check the source to verify that this is the current version before use.