NOT MEASUREMENT SENSITIVE

MIL-PRF-46002C
AMENDMENT 1
20 December 2000

PERFORMANCE SPECIFICATION

PRESERVATIVE OIL, CONTACT AND VOLATILE CORROSION-INHIBITED

This amendment forms a part of MIL-PRF-46002C, dated 14 July 2000, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

* 3.5.1.1: Delete and substitute:

"3.5.1.1 Solid sediment. The oil shall generate not more than 0.05 milliliters (mL) mean total volume of sediment (see 4.2.4.1.1)."

PAGE 12

* 4.2.4.1.1: Delete and substitute:

"4.2.4.1.1 Solid sediment. To determine conformance to 3.5.1.1, the oil shall be tested IAW ASTM D91, and shall generate not more than 0.05 mL mean total volume of sediment."

Custodians:
Army - AT
Navy - OS
Air Force - 68

Preparing Activity:
Army - AT

(Project 9150-1256)

Review Activities:
Army - MD, AL, AR, SM
Air Force - 11
DLA - GS

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:37Z
Check the source to verify that this is the current version before use.