MILITARY SPECIFICATION

UNDERCUTTER, AMATURE MICA, ELECTRICALLY OPERATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1 SCOPE

1.1 Scope. This specification covers a light duty, bench mounted, electrically-operated, rotary cutter type armature mica undercutter, used for undercutting the mica insulation between commutator bars on motors and-generators.

2 APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

W-C-596 - Connector, Plug, Receptacle Cable Outlet, Electrical Power
W-C-596/13 - Connector, Plug, Electrical, General Purpose, Hospital Grade Grounding, 2 Pole, 3 Wire, 15 Amperes, 125 volts, 50/60 Hertz

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing by the end of this document or by letter.

AMSC N/A FSC 4940
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-889 - Dissimilar Metals

2.1.2 Other Government documents. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety Health Standard (29 CFR 1910)

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nogovernment document which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

NEMA MG-1 - Motors and Generators

(Application for copies and NEMA publications should be addressed to the National Electrical Manufacturers Association, Sales Office, 2101 L Street, N. W., Washington, DC 20037.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA-70 - The National Electrical Code

(Application for copies of NFPA publications should be addressed to the NFPA Publications Sales Division, Batterymarch Park, Quincy, MA 22269.)

UNDERWRITERS LABORATORIES, INC. (UL)

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

UL 20- General-Use Snap Switches
UL 45 - Portable Electric Tools

(Application for copies of UL publications should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062, 1285 Walt Whitman Road, Melville, Long Island, New York 11746, or 1655 Scott Boulevard, Santa Clara, California 95050.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3 REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2.1).

3.2 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3 Design. Armature mica undercutter furnished shall be of the manufacturer's latest design. The design shall be such as to provide safe operation. All parts of the undercutter shall be new, designed and constructed to the requirements listed here in. All parts subject to wear, breakage, and distortion shall be readily accessible for adjustment repair.

3.4 Construction. The undercutter shall be complete so that when installed in its intended application and connected to the applicable source of power, it can be used for any operation for which it was designed. The undercutter shall be constructed of parts which are new, without defects and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without distortion.

3.4.1 Casting and forgings. All castings and forgings shall be free from defects, scale, and mismatching. No process such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.4.2 Welding, brazing, and soldering. Welding, brazing and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

3.4.3 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for adjustment and preventing loss of tightness. All parts subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently deformed.

3.4.4 Threads. Threads shall be conformed to FED-STD-H28 and the applicable Detailed Standards referenced therein.

3.5 Performance characteristics.

3.5.1 Capacity. Undercutter shall be suitable for undercutting mica on commutators up to at least 6 inches in diameter and on armatures up to at least 7 inches in diameter. Distance between centers shall be adjustable up to at least 18 inches.

3.5.2 Depth of cut. The depth of cut shall-be regulated by an adjustable stop, the ranges of which shall be such as to accommodate commutators up to 6 inches in diameter. The 0.25 inch diameter saw shall cut to a depth of at least 0.025 inch.

3.6 Components. The undercutter shall consist essentially of electrical components, frame, armature holding supports, stop, stop collars, and motor carriage.

3.7 Motor. The motor shall be of the universal type, continuous duty, suitable for operation on both 115 volts direct current and 115 volt, 60 hertz, single phase alternating current. The motor shall have a rating of at least 1/12 horsepower and shall conform to the requirements of UL 45. The spindle shall be of steel, ground and mounted on ball or roller bearings, and case hardened to 63-65 Rockwell C hardness. The spindle shall be either belt-driven from the drive motor or an integral part of the driven motor. The spindle arbor shall be 0.125 inch diameter and case hardened 63-65 Rockwell C hardness and shall be suitable for mounting cutters specified in 3.13.

3.8 Frame. The frame shall be of' structural steel, or-metal castings, with finished and polished cross members on which the motor carriage and armature supports shall slide freely without binding or chatter, and readily clamp in position. End sections of the frame shall be provided with mounting holes at each end for mounting to a workbench.

3.9 Armature holding support. The armature holding support shall be of suitable cast or fabricated metal mounted to the cross member support by means of a thumb screw clamp arrangement for rapid adjustment-and for adequate clearance between the supports for the centered armature shafts.

3.10 Armature support adjustment. The armature shall be provided with V blocks to support unentered armatures up to at least 7 inches in diameter and with 60 degree steel center points with means provided for thumb adjustments of points.

3.11 Spindle stops. Adjustable stops shall be provided to control saw travel.

3.12 Spindle motor carriage. The spindle motor carriage shall support the motor in horizontal position. Carriage supports shall be provided to allow the motor and spindle to traverse the required length of cut, while maintaining the motor in a horizontal position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

3.13 Cutters. The contractor shall furnish four sets of cutters. Each set of cutters shall consist of five different widths of 0.015, 0.020, 0.025, 0.030, and 0.035 inch each in three different diameters of 0.250, 0.3125, and 0.375 inch (four sets total, 60 cutters). All cutters shall fit a 0.125 inch diameter arbor. Cutters shall be of the saw type for cutting U-shape slots and shall conform to the requirements specified in 3.4. Cutters shall be tungsten carbide or high speed steel, heat-treated to 63-65 Rockwell C hardness.

3.14 Interchangeability. All parts of the end item shall be manufactured to definite standards and tolerances. Parts subject to possible future replacement shall be assigned a manufacturer's part number. When industry or government standards are applicable, replaceable parts shall conform to the standards. All possible future replacement, repair, and spare parts shall provide the same or better form, fit, function, and performance as the respective parts provided initially in the end item. When industry or government standards are applicable, al replaceable parts shall conform to the standards.

3.15 Electrical equipment.

3.15.1 Switch. Switch shall be of quick break design and shall have a locking device for holding in "on" position. Switch shall be readily accessible, and self-contained. Switch shall comply with UL 20.

3.15.2 Cable and plug. The electrical power supply cable shall be not less than 10 feet in length and shall terminate with a three-prong grounding plug in accordance with W-C-596 and W-C-596/13. The electric power supply cable shall include sheathing/covering in accordance with the National Electric Code (NEC), NFPA-70, and OSHA 2206, subpart S-Electrical. The electrical power supply cable shall have a voltage/potential and ampere/current carrying capacity exceeding that required by the electric motor of the undercutter in accordance with NFPA-70.

3.16 Safety devices. Safety devices shall be provided to protect the operator from undercutter elements which present safety hazards. Safety devices shall not interfere with the operation of the undercutter or with the operator's performance.

3.16.1 Occupational safety standards. The product shall comply with the subparts of OSHA 2206 that are applicable to the machine itself.

3.17 Height limitations. The weight without cable, plug connector, and accessories shall not exceed 30 pounds.

3.18 Protective finish. The protective finish shall be paint. All surfaces to be painted shall, immediately prior to painting, be cleaned, dried, and free of all foreign matter. The protective paint coating shall be no less than 0.002 inch thickness. The adhesion of the paint shall prevent any peeling of paint when removing fiber glass tape applied over two intersecting cuts in the paint, the cuts being not less than 2 inches in length and through the paint thickness to the base metal. The surface hardness of the paint shall be in accordance with the industrial practice of checking with pencil lead and shall be within the range of H to HB lead. Where no protective finish can be utilized (such as bedways, machine guidance surfaces, etc.) the natural finish of the material or the finish obtained from heat treatment is permissible provided the surfaces are free from scale or corrosion and preservative treated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

3.19 Surfaces. Surfaces of all castings, forgings, molded parts, stamping, and welded parts shall be cleaned and free of sand, dirt, fins, sprues, scale, flux, flash, and other harmful or extraneous materials. External surfaces shall be smooth and ail edges shall be rounded or beveled.

3.20 Lubrication. All bearings (except sealed, permanently lubricated type), mating gears and all other moving parts shall be provided means to assure adequate lubrication. All oil holes, grease fittings, and filler caps shall be so located as to be readily accessible. The supplier shall include and install all lubricants, fluids, greases, and other compounds in accordance with the best commercial practices of the undercutter industry.

3.21 Identification plate. A corrosion-resistant metallic plate shall be securely attached to the undercutter. Characters and numerals shall be permanently and legibly engraved, etched, embossed, or stamped in bold face on a contrasting background. The plate shall be secured to the machine with permanent fasteners such as screws, bolts, and rivets. The plate shall be secured with permanent fasteners at each of the four corners. The plate shall include the following information.

Nomenclature
National Stock Number (NSN)
Manufacturer's Name
Manufacturer's Model Number
Manufacturer's Serial Number (if applicable)
Contract Number

3.22 Accessories. In addition to the 'accessories specified herein, each undercutter tool shall be furnished with such maintenance tools, accessories, and extra parts as normally furnished commercially.

3.23 Workmanship. Workmanship of the undercutter, accessories, and ancillary items shall be of a quality equal to that of the best commercial practices of the undercutter manufacturing industry.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of-any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. When required, first article inspection shall be applied to the preproduction model or initial production item (see 3.1). First article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to production items offered for acceptance under the contract. Quality conformance inspection shall consist of (a) through (e) below. Failure of any-item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Performance test (see 4.6.2).
(c) Hardness test (see 4.6.3).
(d) Paint test (see 4.6.4).
(e) Packaging inspection (see 4.7).

4.4.1 Sampling. Sampling for quality conformance inspection shall be performed in accordance with MIL-STD-105 using inspection levels and acceptable quality levels (AQL). A sample lot shall consist of a quantity produced in one month or 150 undercutter, whichever is less.

Inspection or Test	Inspection Level	AQL
Product examination (4.5)	II	1.0
performance test (4.6.2)	II	1.0
Hardness tests (4.6.3)	II l	1.0
Paint test (4.6.4)	'11	1.0
Packaging inspection (4.7)	S-4	4.0

4.5 Product examination. Visually, manually, and dimensionally examine the undercutter to determine conformance with the requirements of 3.2 through 3.4.4, 3.6, 3.8 through 3.17, and 3.19 through 3.23. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from identified defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. Dimensional examination shall include verification that the undercutter meets all dimensions and characteristics specified. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the undercutter has passed the visual, manual, and dimensional verifications prescribed for it by the contractor's inspection system shall be cause for rejection.

4.6 Tests. Measuring instruments used in performing the following tests shall be more accurate by a factor of ten than the specified limit, and shall be traceable to the National Bureau of Standards. Failure of the undercutter to pass any of the test requirements shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

4.6.1 Electric motor test. Prior to approval of the first shipment the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the motor used on the undercutter has been tested and meets the requirements of UL 45 and, except as otherwise specified herein, shall be in accordance with NEMA MG-1. The motor shall have a rating of at least 1/12 horsepower and shall operate on both 115 volts direct current and 115 volts 60 hertz single phase alternating current. Failure to meet the requirements of UL 45 or applicable requirementts of NEMA MG-1, or failure to operate at the required voltages shall be cause for rejection.

4.6.2 Performance test. The undercutter shall undercut the mica on an armature to the maximum depth using a 0.375 inch diameter, 0.035 inch width cutter. Binding of the carriage or collars, chattering of the cutter, or overheating of the motor during the test shall be cause for rejection.

4.6.3 Hardness test. Rockwell C hardness tests shall be performed on the components listed below, or on test samples processed concurrently with the components. Failure of a component or sample to meet the required hardness number shall be cause for rejection. A Certificate of Conformance (COC) may be accepted for a component in lieu of the test, provided the COC is signed by an officer of the original equipment manufacturer of that component.

Component	Rockwell C No.	Ref Para
Spindle	63-65	3.7
Spindle arbor	63-65	3.7
Cutters (all)	63-65	3.13

4.6.4 Painting test. The surface of a sample part shall be used to conduct the painting test. The sample part shall be of identical material and have the same surface finish as one of the parts in the finished undercoating spray outfit. The sample part shall be painted at the same time as the undercoating spray outfit using the same paint and the same painting process. The protective paint coating shall be not less than 0.002 inch in thickness. The paint adhesion shall be adequate to the extent that no paint shall be peeled by application and removal of fiberglass tape over two intersecting cuts exposing the base metal for a distance of not less than 2 inches. Depress a sharpened H and HB hardness wooden lead pencil vertically onto the surface of the painted sample part until the lead crushes or breaks. The H hardness pencil lead shall leave no indentation in the painting surface. Failure of this painting test including hardness shall be cause for rejection.

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5 PACKAGING (see 6.2.1)

5.1 Miliatary preservation and packing. When specified in the contract, requirements for level A preservation, and levels A or B packing shall be in accordance with MIL-M-18058.

5.2 Marking. When military levels of preservation and packing are specified, marking shall be in accordance with the retirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

5.3 Industrial preservation, packing, and marking. When specified in the contract, preservation, packing, and marking shall be in accordance with ASTM D 3951 . Bar coding is also required.

5.3.1 Additional industrial requirements. In addition to the requirements of ASTM D 3951, all unprotected ferrous metal parts and all accessories shall be cleaned, preserved, and wrapped with greaseproof wrap. Accessories shall be packed, blocked and cushioned in fiberboard container(s). All motor openings shall be sealed with waterproof tape or entire motor shall be wrapped with waterproof barrier material and taped in place. Shaft shall be preserved and wrapped with greaseproof wrap. Any critical surfaces shall be protected from damage in transit. Technical data shall be placed in a plastic bag (stapled or sealed closed) and enclosed in accessory container. Movable parts of the machine shall be secured by mechanical devices incorporated into the machine for that purpose. They must also be augmented with appropriate wood blocking, metal strapping, etc., to assure immobilization. Levers, cranks, handles, etc., shall be secured in position with annealed wire or steel strapping and protected from damage. All items shall be protected from marring.

5.4 Military and industrial packing for lubrication systems. The lubrication systems shall be temporarily capped or plugged to prevent loss of lubricants during shipment. Tags, warning that all temporary caps of plugs must be removed before start-up or use of the undercutter shall be attached to all temporary caps or plugs. These warnings shall also be included in the instruction manual.

6 NOTES

6.1 Intended use. Undercutting mica between commutator bars of electric motors and generators. Undercutter is a stationary, bench mounted machine. Motor is high speed, 115 volt universal type. Undercutter is light duty for undercutting horizontal commutators in repair shop service.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, name, and date of this specification.
(b) First article, when specified (see 3.1).
(c) Preservation, packing and marking as required (see Section 5, Packaging).

6.2.2 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.3 Subject term (key word) listing.

AMSC number
Accessories
Acquisition requirements
Armature holding support
Armature support adjustment
Cable and plugs
Castings and forgings
Classification of inspections
Construction

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

Contract data requirements
Cutter
Design
Distribution statement
Electric motor test
Electrical equipment
Fastening devices
Federal
First article
First article inspection
Government documents
Hardness test
Identification plate
Industrial prevention, packing, and marking
Inspection or test
Intended use
Interchangeablity
Lubrication
Marking
Military and industrial packing for lubrication systems
Military preservation and packing
Military specification
Ordering data
Packaging
Packaging inspection
Painting test
Performance characteristics
Performance test
Product examination
Project number
Protective finish
Quality Assurance Provisions
Quality conformance inspection
Responsibility for compliance
Responsibility for inspection
Safety devices
Scope
Specifications
standards
stop collars
Surface
Tests
Threads
Undercutter
Weight limitations
Welding, brazing and soldering
Workmanship

Custodian:
Army-AL
Air Force - 99

Preparing Activity:
Army - AL

Review Activities:
Army - SM
Air Force - 82

(Project Number: 4940-A509)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armement Research and Development Command
ATTN: DRDAR-TST-S
Dover, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:36Z
Check the source to verify that this is the currentversion before use.