MILITARY SPECIFICATION
WELDING SHOP, TRAILER MOUNTED

This specification is approved for use by the US Army Armament, Munitions, and Chemical Command (Engineering Support Directorate, Tool and Equipment Engineering Division, Standardization, Specifications and Packaging Branch), Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense

1 Scope

1.1 This specification covers a Trailer Mounted Welding Shop, Army Part Number 11022000, 350 Ampere Direct Current (DC), Constant Current/Constant Voltage (CC/CV) with all components necessary for Shielded Metal Arc Welding (SMAW) ,Gas Metal Arc Welding (GMAW), including shorting arc process, (DC) Gas Tungsten Arc Welding (GTAW), Flux Cored Arc Welding (FCAW), Air Carbon Arc Cutting and Gouging (AAC), Oxyacetylene Welding (OAW) and Oxygen Cutting (OC).

2 APPLICABLE DOCUMENTS

2.1 Government Documents

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications , standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-V-173	-Varnish, Moisture and Fungus Resistant (For Treatment of Communications, Electronics and Associated Equipment)
MIL-P-10524/9	-Plate, Tags and Bands, Aircraft Loading Data Plate
MIL-T-0013880	-Torches, Oxyacetylene, Welding and Cutting
MIL-W-45562	-Welding and Soldering Equipment, Supplies and Accessories, Packaging of

.Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-LEE-S, Rock Island, IL 61299 by using a self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3431

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

MIL-W-45992 - Welding Machine, Arc, Direct Current (DC), Constant Current (CC), Constant Voltage (CV), 350 Ampere, Diesel Engine Driven (DED)
MIL-C-46168 - Coating, Aliphatic Polyurethane, Chemical Agent Resistant

STANDARDS

FEDERAL

FED-STD-H28 - Screw Threads Standards For Federal Service

MILITARY

MIL-STD-130 - Identification Marking of Military Property
MS-53030 - Chassis, Trailer, Generator, 2-1/2 Ton, 2-Wheel
MS-90495 - Plate, Identification, Blank, Mechanical Equipment

2.1.2 Other government documents, drawings and publications. The following other government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

ARMY

11021481 - Welding Machine Cover
11021251 - Finish Methods
11022000 - Welding Shop, Trailer Mounted
11022560 - Gas Cylinder Cover
11022570 - Gas Cylinder Cover
11022810 - Pattern Camouflage Painting

LIST OF COMPONENTS

ARMY

3431-95-CL-A04 - List of Components

(Copies of specifications, standards, handbooks, drawings and publications required by the contractor in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D3951-82 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL ELECTRICAL MANUFACTURER'S ASSOCIATION

NEMA EW-1 - Electric Arc Welding Standards

(Application for copies should be addressed to the National Electrical Manufacturer's Association, 2101 L Street NW, Washington, DC 20037.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

AMERICAN WELDING SOCIETY

AWS A5.18 - Specification for Carbon Steel Filler Metals for Gas Shielded Arc Welding

(Applications for copies should be addressed to the American Welding Society, 550 N.W. Le Jeune Road, P.O. Box 351040, Miami, FL 33135.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3 REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish one or more complete welding shop(s) for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The trailer mounted welding shop shall be in accordance with Army Drawing 11022000 and as specified herein. The shop shall include all tools and equipment specified in the list of components 3431-95-CL-A04. Welding terms and definitions shall be in accordance with NEMA Standard EW-1 as referenced herein and on the applicable drawing.

3.3 Construction. The welding shop shall be free from any characteristics or defects which may render the shop unsuitable or inefficient for the purpose intended. The shop and its equipment shall be so constructed as to be capable of performing the operations specified herein.

3.3.1 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity, and intent of the materials originally selected or specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is or rebuilt from scrap or other used equipment.

3.3.2 Castings and forgings. Castings shall be free of visible blowholes, porosity, hardspots, shrinkage defects, cracks, or other defects. Forgings shall be free of visible scale, inclusions, cold shuts, mismatching, or other defects. In no event shall such processes as welding, peening, plugging, or filling with cold solders or metallic pastes be used on castings or forgings.

3.3.3 Welding, brazing and soldering. Welding, brazing and soldering shall be employed only where those operations are included in fabrication of the original design. These operations shall not be employed as repair measures for defective parts.

3.3.4 Fastening devices. All parts subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed. All bolt and rivet holes shall be accurately punched or drilled and free of burrs. All nuts, bolts, screws and retaining fasteners shall be installed in a manner to prevent loss of tightness. Those subject to removal or adjustment shall not be swaged, peened or staked or otherwise

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

permanently deformed.

3.3.5 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.6 Threads. All threaded parts of the welding shop and its components shall conform to FED-STD-H28 and applicable "Detailed Standards" section referenced therein.

3.3.7 Cleaning, treating and painting. Surfaces to be painted shall be cleaned and dried to insure they are free of oil, grease, welding slag and spatter, loose mil scale, water, dirt, corrosion products or any other interfering substances. After cleaning and before any corrosion product or other coating interfering material can be deposited, the surface shall be prepared or treated to insure adhesion of the coating system. Finish methods shall be as specified on the individual drawing and drawing 11021251. The total dry film thickness shall not be less than 2.5 mils over the entire surface. The primer and paint shall be in accordance with MIL-C-46168 infrared absorbent and chemical agent resistant paint. The color of the camouflage coating paint shall be as specified on the applicable drawing. The camouflage pattern shall be in accordance with Drawing Number 11022810.

3.3.8 Fungus and moisture resistance. The electrical circuitry shall be protected from fungus growth and moisture by an overall fungus treatment in accordance with MIL-V-173 with the exception that:

a. Components of circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.

b. Components or circuit elements whose functions will be adversely affected by the coating shall not be treated.

3.3.9 Identification marking. The welding shop shall be marked for identification in accordance with MIL-STD-130 and shall conform with the applicable drawings and shall include the National Stock Number. The markings shall be applied to plates conforming to MIL-P-15024/9 and MS-90495.

3.3.10 Storage box locks. The equipment storage box shall be furnished with a lock and two identical keys. The keys and lock shall be different for a series of no less than 30 units. The key series and lock shall repeat on each series of locks.

3.4 Performance and product characteristics.

3.4.1 Physical data.

3.4.1.1 Weight. The combined wet weight of the shop body and components shall not exceed 5,200 pounds (not including the trailer chassis).

3.4.1.2 Lunette loading (wet weight). With all components in place on the shop body and shop body mounted on the trailer chassis, the vertical loading of the lunette eye shall not be greater than 635 pounds nor less than 350 pounds.

3.4.1.3 Dimensions. With the shop body mounted on the trailer chassis, the width shall not exceed 8 feet, the length (including the trailer chassis) shall not exceed 14.9 feet, and the height (including the trailer chassis) shall not exceed 8.6 feet.

3.4.2 Transportability. Intended operation and function of shop components shall not be degraded as a result of transportation (i.e. cracked welds, permanent deformation, damaged equipment, etc.).

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:35Z
Check the source to verify that this is the current version before use.

3.4.2.1 Rough handling. The shop set and trailer shall be such that rough handling will not cause distortion. The trailer mounted welding shop shall withstand stresses without damage to or displacement of any component when exposed to shock and vibration, such as occurring in rail transportation with humping at 10 miles per hour.

3.4.2.2 Roadability. The shop set with trailer and fully loaded shall be capable of being towed at speeds up to 50 mph on improved roads, up to 35 mph on unpaved roads and up to five mph on rough terrain.

3.4.3 Environmental conditions.

3.4.3.1 Low temperature. The welding shop shall be capable of starting and operating down to a minimum temperature of -25 degrees F. The welding shop shall not be adversely affected by storage down to a minimum temperature of -28 degrees F.

3.4.3.2 High temperature. The welding shop shall be capable of starting and operating up to a maximum temperature of +120 degrees F. The welding shop shall not be adversely affected by storage up to a maximum temperature of +160 degrees F, with the exception that gas cylinders shall be removed from the welding shop and stored at temperatures of no more than +120 degrees F. In addition, the welding shop shall not be adversely affected by a relative humidity between 80 and 100 percent during high temperature operation and storage.

3.4.4 Welding performance. The welding shop shall be capable of performing the following processes without malfunction when the power source is operated within the ranges as specified in NEMA-EW1 for the rating of the machine.

Shielded Metal Arc Welding	- SMAW
Gas Metal Arc Welding, including shorting arc process	- GMAW
Flux Cored Arc Welding	- FCAW
(DC) Gas Tungsten Arc Welding	- GTAW
Air Carbon Arc Cutting and Gouging	- AAC

In addition, the welding shop shall be capable of performing the following processes in conformance with the requirements of MIL-T-0013880.

Oxyacetylene Welding	- OAW
Oxygen Cutting	- OC

3.5 Welding machine cover. Each welding shop shall be provided with a removable cover for the welding machine in accordance with Drawing Number 11021481.

3.6 Gas cylinder covers. Each welding shop shall be provided with removable covers for the gas cylinders in accordance with Drawing Number 11022560 for the right side (facing the welding machine control panel) and 11022570 for the left side gas cylinder.

3.7 Identical items. All welding shops of this classification furnished under any one contract shall be physically, functionally, and mechanically identical. This requirement includes parts, assemblies and components. Any deviation must have the prior written approval of the contracting officer.

3.8 Government furnished property. The shop body shall be mounted on a M200A1 trailer chassis in accordance with MS-53030. Unless otherwise specified (see 6.2), one Chassis, Trailer, Generator,2-1/2 Ton,Wheel,Military Design, M200A1 per shop set shall be furnished by the government.

3.9 Welding machine. Each welding shop shall include a welding machine conforming to MIL-W-45992.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

3.10 Workmanship. Standards of workmanship shall be such as to assure equipment of a neat appearance, having the stability and efficient operating characteristics as found in commercial equipment of the type specified herein.

4 QUALITY ASSURANCE

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).

b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. When specified (see 6.2), first article inspection shall be performed on the welding shop, trailer mounted. This inspection shall include the examinations and tests specified in Table I.

4.2.2 Quality conformance inspection. Quality conformance inspection shall be applied to production units being offered for acceptance under the contract. The sampling for test and examination shall be in accordance with Table I. The contractor shall provide to the government representative objective evidence that the examination requirements have been met. Failure of a welding machine to meet the sample inspection tests shall be cause for the government to suspend acceptance until:

a. The contractor has completed a failure analysis.

b. The applicable production processes and procedures to prevent recurrence of the same defect in future production are evaluated and corrected.

c. The welding machines awaiting submittal for government acceptance, (including components and subassemblies at in-process or final assembly) are examined to insure that the material containing the same defect(s) is purged from the inventory and not presented to the government for acceptance.

d. Objective evidence of the results of the failure analysis and corrective actions are provided to the government representative prior to submitting the reconditioned welding machine for retest.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

Table I. Tests and examination.

FIRST ARTICLE	QUALITY CONFORMANCE INSPECTION		TEST AND EXAMINATION	TEST PARA.	REQUIREMENT PARA.
	SAMPLING (1 OUT OF EA. 40)	100 PERCENT INSPECTION (EA. UNIT SHALL BE INSPECTED)			
X	-	-	Design (Drawing 11022000	4.3	3.2
X	-	X	Tools and Equipment	4.3	3.2
X	-	X	Construction	4.4	3.3
X	-	X	Casting and Forgings	4.4	3.3.2
X	-	X	Welding, Brazing and Soldering	4.4	3.3.3
X	-	X	Fastening Devices	4.4	3.3.4
X	-	X	Materials	4.4	3.3.5
-	-	X	Threads	4.4	3.3.6
X	-	X	Cleaning, Treating and Painting	4.4	3.3.7
X	-	X	Fungus and Moisture Resistance	4.4	3.3.8
X	-	X	Identification Marking	4.4	3.3.9
X	-	X	Storage Box Locks	4.4	3.3.10
X	-	-	Weight	4.5.1	3.4.1.1
X	-	-	Lunette Loading (wet weight)	4.5.2	3.4.1.2
X	X	-	Dimensions	4.5.3	3.4.1.3
X	-	-	Portability and rough handling	4.6.1	3.4.2.1
X	-	-	Roadability	4.6.2	3.4.2.2
X	-	-	Low Temperature	4.7.1	3.4.3.1
X	-	-	High Temperature	4.7.2	3.4.3.2
X	X	-	Welding Performance	4.8	3.4.4
X	-	X	Welding Machine Cover	4.9	3.5
X	-	X	Gas Cylinder Cover	4.10	3.6
X	-	X	Identical Items	4.11	3.7
X	-	-	Welding Machine	4.12	3.9
X	-	X	Workmanship	4.13	3.10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

4.3 Design. Visual examination shall be performed to ascertain compliance with Drawing 11022000 (see 3.2).

4.4 Construction. The inspection of the welding shop shall include visual and manual examination to determine conformance with the requirements of 3.3 through 3.3.10. Visual examination shall include verification of proper cleaning; presence of specified protective coatings; completeness of manufacture and assembly; adequacy of marking; and repetition of key series. Manual examinations shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at any practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the welding shop and its components have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection.

4.5 Physical data.

4.5.1 Weight. The complete welding shop shall be weighed as per 3.4.1.1 using a scale. Weight shall be as specified in 3.4.1.1.

4.5.2 Lunette loading (wet weight). Using a scale, the lunette loading shall be as specified in 3.4.1.2.

4.5.3 Dimensions. Using a steel tape, the dimensions shall be as specified in 3.4.1.3.

4.6 Transportability. (Tests to be conducted in the following order: 4.6.1 followed by 4.6.2.)

4.6.1 Rough handling. The weld shop when packaged as specified in paragraph 3.4.2.1 shall be subjected to a rail impact (hump) test. The test shall be conducted using three standard railroad cars, one of which will be a flat-bed car. The item to be tested will be loaded and properly blocked and attached to the flat-bed car using hold-downs provided. The other two cars will be coupled together and the brakes on both cars will be set in the emergency condition. The test car (flat-bed with the item to be tested) shall be impacted into the two buffer cars at a speed of 10 mph. After the test, the unit shall be inspected visually for damage.

4.6.2 Roadability tests. To determine compliance with 3.4.2.2, the welding shop with trailer and fully loaded shall be towed:

a. On a paved road at speeds up to 50 mph for a distance of 5 miles.

b. On an unpaved road at speeds up to 35 mph for a distance of 3 miles.

c. On off-road terrain at speeds up to 5 mph for a distance of 3 miles.

After each of the above tests, the welding shop, all its components, and trailer shall be visually examined for any deleterious effects. In addition, after the off-road terrain test, the welding machine (MIL-W-45992) shall be operated and visually inspected to determine that it produces welding power, auxiliary power and compressed air and that all instruments and gauges function properly. The welding performance tests (see 4.8) shall be performed upon completion of this test.

4.7 Environmental conditions. A warmup time of at least 5 minutes shall be allowed before environmental testing begins (see 4.7.1 and 4.7.2). Maximum power testing shall be performed for 5 continuous minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

4.7.1 Low temperature. To assure compliance with 3.4.3.1, the complete welding shop shall be submitted to storage at a temperature of -28 degrees F for a period of 24 hours. At the end of this period, the temperature shall rise to -25 degrees F and after stabilization, the welding shop shall be started and the output of both the auxiliary power generator and the welding generator shall be checked for minimum and maximum output per NEMA EW-1 Class I(100), using a resistance load bank having a power factor of 0.99 or higher.

4.7.2 High temperature. To assure compliance with 3.4.3.2, the complete welding shop shall be submitted to storage at a temperature of +160 degrees F and induced relative humidity of 80 to 100 percent for a period of 24 hours. At the end of this period, the temperature shall be reduced to +120 degrees F and 80 to 100 percent relative humidity. After a 24 hour stabilization period, the welding shop shall be started and the output of both the auxiliary power generator and the welding generator shall be checked for minimum and maximum output per NEMA EW-1 Class I(100) using a resistance load bank having a power factor of 0.99 or higher.

CAUTION: Remove all gas cylinders from the welding shop prior to the high temperature storage tests. The Compressed Gas Association publication G-1 limits storage of gases to a maximum of 120 degrees F.

4.8 Welding performance. To assure compliance with 3.4.4, the following tests shall be performed using the associated accessory items cited in the List of Components 3431-95-CL-A04, as required. All welding operations shall be performed by a trained operator. Welds on test plates shall be visually examined for acceptable quality. Failure of the welding shop to perform any of the following cited tests shall be cause for rejection (see 4.2.2).

4.8.1 Welding tests in the CC mode. Welding tests in the CC mode shall be as follows:

a. Using the cables specified in the welding shop (50 ft. lengths), welding operations shall be performed using the SMAW process with 5/32 inch diameter E-6010 electrodes on mild steel plates, 2 pieces approximately 2 inches by 10 inches by 1/4 inch in a horizontal fillet position, tee joint. Welds shall be 10 inches long.

b. Using the above cables, welding operations shall be performed using the SMAW process with 7/32 inch diameter E-7018 electrodes on mild steel plates, 2 pieces approximately 4 inches by 1-1/2 inches by 3/8 inches in a horizontal fillet position, tee joint. Welds shall be 4 inches.

c. Using the cables, hose and air compressor specified in the welding shop, cutting and gouging shall be performed (AAC process) using 5/32 inch diameter copper coated carbon electrode and test plates of mild steel (2 pieces) approximately 4 inches by 10 inches by 1/2 inch, cutting one piece across the 4 inch width and gouging the other 10 inch length.

d. Using the gas shielding tungsten electrode welding set (TIG torch), hose, cables and regulator specified in the welding shop, with Argon gas, 1/16 inch diameter 2 percent thoriated tungsten, perform a horizontal fillet lap joint weld using 2 pieces of 2 inch by 10 inch by 16 gauge stainless steel. Using 1/8 inch diameter 2 percent thoriated tungsten, perform a horizontal fillet joint weld using 2 pieces of 2 inch by 10 inch by 1/8 inch stainless steel. Welds shall be 10 inches long.

4.8.2 Welding tests in the CV mode. Welding tests in the CV mode shall be as follows:

a. Using the welding set, gas shielded, consumable electrode, the welding cables, gas hose and the regulator/flowmeter specified in the welding shop, connected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

a cylinder of carbon dioxide gas, perform a horizontal fillet tee joint weld using .035 diameter per AWS 5.18 classification ER-70S-3 wire on test plates of 2 pieces of 2 inch by 10 inch by 1/8 inch mild steel. Welds shall be 10 inches long.

b. Using the welding set and accessories specified above, perform a horizontal fillet tee joint weld using 1/16 inch diameter, flux cored wire (Hobart 802 or equal) on test plates of 2 pieces of 4 inch by 10 inch by 3/8 inch mild steel. Welds shall be 10 inches long.

c. Using the welding set and accessories specified above, connected to a cylinder of Argon gas, perform a horizontal fillet lap joint weld using .035 diameter aluminum welding wire ER-4043 on test plates consisting of 2 pieces of 2 inch by 10 inch by 1/8 inch, 1100 series aluminum.

d. Using the welding set and accessories specified above, connected to a cylinder of Argon gas, perform a fillet lap joint weld using 3/64 inch diameter aluminum welding wire ER-4043 on test plates consisting of 2 pieces of 2 inch by 10 inch by 1/4 inch, 1100 series aluminum. Welds shall be 10 inches long.

4.8.3 Oxyacetylene tests. A certificate of conformance shall be issued to ascertain compliance with 3.4.4 and the quality assurance provisions of MIL-T-0013880.

4.9 Welding machine cover. Visual inspection for compliance with 3.5 shall be performed with a certificate of conformance issued to ascertain that the cover meets the requirements of 3.5 and component drawing requirements.

4.10 Gas cylinder covers. Visual inspection for compliance with 3.6 shall be performed with a certification of conformance issued to ascertain that the covers meet the requirements of 3.6 and component drawing requirements.

4.11 Identical items. A certificate of conformance shall be issued to ascertain compliance with paragraph 3.7.

4.12 Welding machine. Visual inspection for compliance with 3.9 shall be performed.

4.13 Workmanship. Workmanship shall be visually inspected for compliance with 3.10.

4.14 Packaging inspection. The trailer mounted welding shop shall be inspected before and after packaging to determine compliance with the preservation, packaging, packing and marking requirements specified in section 5 and the contract (see 6.2).

5 PACKAGING

5.1 Military preservation, packaging, packing and marking. Unless otherwise specified (see 6.2), preservation, packaging, packing and marking shall be in accordance with applicable requirements of MIL-W-45562. Level of preservation, packaging and packing shall be as specified in the contract.

5.2 Industrial preservation-packaging, packing and marking. Unless otherwise specified (see 6.2), preservation-packaging, packing and marking shall conform to the requirements of ASTM D3951-82.

6 NOTES

6.1 Intended use. The equipment covered by this specification is intended to be used as a Welding Shop, Trailer Mounted.

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:35Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

a. Title, number and date of this specification.

b. First article, when required (see 3.2).

c. Government furnished property, if required (see 3.8).

d. First Article, when required (see 4.2.1).

e. Level of preservation and packaging (see 5.1 and 5.2).

6.2.1 Contract data requirements. Required technical data, such as operators manuals, parts lists, wiring diagrams, and other instructions for operation and maintenance as identified on a numbered DD Form 1664 should be specified on a DD Form 1423 incorporated into the contract.

6.3 First article. When a first article is required, it shall be tested and approved under the appropriate provision of 7-104.55 of the Defense Acquisition Regulation. The first article should be preproduction sample, or a standard production item from the contractor's current inventory. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examination, test and approval of the first article.

Custodian:
Army - AL

Preparing Activity:
Army - AL

Project Number 3431-A155

Source: https://assist.dla.mil -- Downloaded: 202610-22T04:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament, Munitions and Chemical Command
Attn: DRSMC-LEE-S
Rock Island, IL 61299

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T04:35Z
Check the source to verify that this is the current version before use.