NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-15733/58B
AMENDMENT 3
6 May 1994
SUPERSEDING
AMENDMENT 2
31 May 1990

PERFORMANCE SPECIFICATION SHEET

FILTERS AND CAPACITORS, RADIO FREQUENCY INTERFERENCE, HERMETICALLY SEALED, STYLE FL63

This amendment forms a part of MIL-F-15733/58B, dated 24 January 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Seal, delete in its entirety and substitute:

"Seal: Method 112, test condition A or D, MIL-STD-202."

PAGE 4

Insertion loss, delete in its entirety and substitute:

"Insertion loss: At 25°C and temperature extremes; in accordance with MIL-F-15733 and table III."

PAGE 5

TABLE I, add dimensions for new part number as follows:

Dash no.	A		B		C		D	
	Min	Max	Min	Max	Min	Max	Min	Max
0004	—	.545 (13.84)	—	.385 (9.78)	.302 (7.67)	.322 (8.18)	.140 (3.56)	.175 (4.45)

Dash no.	E		F	G		H		J
	Min	Max	Typ	Min	Max	Min	Max	
0004	.140 (3.56)	.160 (4.06)	.097 (2.46)	.190 (4.83)	.210 (5.33)	.045 (1.14)	.075 (1.91)	.250-28 UNF-2A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:26Z
Check the source to verify that this is the current version before use.

TABLE II, add hardware dimensions for new part number as follows:

"

Dash no.	Hex nut					Lockwasher	
	A		B		C	D	
	Min	Max	Min	Max	Thread	Min	Max
0004	.307 (7.80)	.317 (8.05)	.088 (2.24)	.098 (2.49)	.250-28 UNF-2B	.395 (10.03)	.410 (10.41)

"

TABLE III, add characteristics for new part number as follows:

"

Dash no.	Circuit configuration	Maximum rated current (amperes)	Maximum rated voltage dc		Voltage drop (volts dc, max)
			+85°C to -55°C	+125°C	
0004	L1	10.0	80	50	.08

"

Dash no.	Minimum full load insertion loss (dB) in accordance with MIL-STD-220 over full temperature range -55°C to +125°C.															
004	30 kHz	50 kHz	100 kHz	150 kHz	200 kHz	300 kHz	500 kHz	1.0 MHz	2.0 MHz	5.0 MHz	10.0 MHz	20.0 MHz	50.0 MHz	100 MHz	1.0 GHz	10 GHz
	15	---	23	28	32	33	39	44	50	57	60	---	---	---	70	---

"

FIGURE 2, delete "Dash numbers 0001 and 0002" and substitute "Dash numbers 0001, 0002, and 0004".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:26Z
Check the source to verify that this is the current version before use.

* TABLE V, delete and substitute:

"TABLE V. Group A inspection. 1/

Test or inspection	Sampling procedure
Thermal shock	100%
Voltage conditioning	100%
Dielectric withstanding voltage	100%
Insulation resistance (+25°C)	100%
Voltage drop	100%
Seal test	100%
Insertion loss (check test)	100%
Radiographic inspection 2/	100%
Visual and mechanical inspection	See MIL-F-15733, group A inspection
Capacitance to ground	

1/ This table replaces table X of MIL-F-15733.
2/ Applicable to dash number 0002 only."

Cataloging information, last sentence; delete and substitute "Dash numbers 0001, 0002, and 0004 shall be cataloged under FSC 5915 as radio frequency interference filters."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AT, AV, ME, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

Preparing activity:
DLA - ES

(Project 59GP-0132)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:26Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:26Z
Check the source to verify that this is the current version before use.