

FED SUP CLASS
4730



SHORT NUT



LONG NUT

| DASH NO. | | TUBE O.D. | B STRAIGHT THREAD | C HEX FLAT NOM | D DIA | | L OVERALL LENGTH | $L_1$ OVERALL LENGTH | T HEIGHT OF FLAT |
|---|---|---|---|---|---|---|---|---|---|
| SHORT NUT | LONG NUT | | | | MIN | MAX | | | |
| -1 | -1L | 1/8 | .312-24UNF-2B | 3/8 | 0.130 | 0.135 | 0.50 | 0.75 | 0.22 |
| -2 | -2L | 3/16 | .375-24UNF-2B | 7/16 | 0.192 | 0.197 | 0.62 | 0.81 | 0.28 |
| -3 | -3L | 1/4 | .438-20UNF-2B | 9/16 | 0.255 | 0.260 | 0.75 | 0.94 | 0.38 |
| -4 | -4L | 5/16 | .500-20UNF-2B | 5/8 | 0.317 | 0.322 | 0.88 | 1.12 | 0.44 |
| -5 | -5L | 3/8 | .625-18UNF-2B | 3/4 | 0.380 | 0.385 | 1.00 | 1.31 | 0.50 |
| -6 | -6L | 7/16 | .688-16UN-2B | 13/16 | 0.442 | 0.447 | 1.06 | 1.50 | 0.56 |
| -7 | -7L | 1/2 | .750-16UNF-2B | 7/8 | 0.505 | 0.510 | 1.12 | 1.62 | 0.62 |
| -8 | -8L | 5/8 | .875-14UNF-2B | 1-1/16 | 0.630 | 0.635 | 1.31 | 1.88 | 0.75 |
| -9 | -9L | 3/4 | 1.062-14UNS-2B | 1-1/4 | 0.755 | 0.760 | 1.50 | 2.19 | 0.88 |
| -10 | -10L | 7/8 | 1.250-12UNF-2B | 1-1/2 | 0.880 | 0.885 | 1.62 | 2.31 | 1.00 |
| -11 | -11L | 1 | 1.375-12UNF-2B | 1-5/8 | 1.005 | 1.010 | 1.81 | 2.50 | 1.00 |

Material: Brass in accordance with QQ-B-626, alloy 360, temper half hard or SAE UNS C36000, half hard.

Protective coating: None.

Dimensions and Tolerances: Dimensions and tolerances not shown shall be in accordance with the SAE Standard for 45° Flared Type Tube Fittings (SAE J512). Unless otherwise specified all dimensions are in inches.

Threads: Threads shall be in accordance with FED-STD-H28.

Part number: The MS part number consists of the MS number plus the dash number.
Example: MS39166-1 for the short nut.
MS39166-1L for the long nut.

NOTES:

1. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
2. Referenced documents shall be of the issue in effect on date of invitations for bids, or request for proposal, except that referenced adopted industry documents shall give the date of the issue adopted.
3. The illustration is for identification and is not intended to restrict designs and shapes not dimensioned.

(E) CANCELLED - FOR PROCUREMENT USE

SAE J512-80

| P A ME Other Coat | INTERNATIONAL INTEREST | TITLE NUT, TUBE COUPLING, SHORT AND LONG 45° FLARED TYPE, AUTOMOTIVE | MILITARY STANDARD MS39166 |
|---|---|---|---|
| PROCUREMENT SPECIFICATION MIL-F-1224 | SUPERSEDES MS39167 AND ORDNANCE ENGINEERING STANDARD CNAX5 IN PART | | SHEET 1 OF 1 |

DD FORM 672-1 (COORDINATED) 4730-0340

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

APPROVED 3 APR 62 REVISED (A) 27 FEB 67 (B) 22 OCT 68 (C) 26 SEP 75 (D) 15 JUN 82 (E) 10 MAR 87

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Review activities: Army - AT, MI, MA - CR

User activities: Army - GL, Navy - OS

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:47Z
Check the source to verify that this is the current version before use.