INCH POUND
MS75088C
16 February 1995
SUPERSEDING
MS75088B
4 September 1985


MILITARY SPECIFICATION SHEET

COILS, RADIO FREQUENCY, MOLDED, FIXED, MICRO-MINIATURE, MAGNETICALLY SHIELDED (IRON CORE-IRON SLEEVE) TYPES LT10K203 TO LT10K216, INCLUSIVE

Inactive for new design after 4 September 1985.
For new design, use MIL-C-39010/2.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-15305.



Ltr	Dimensions are in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
ØA	.152 (3.86)	.172 (4.37)
B	.390 (9.91)	.430 (10.92)
C	1.250 (31.75)	1.626 (41.30)
ØD	.023 (0.58)	.027 (0.69)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 1. Dimensions and configuration.

Ⓒ denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Style: LT10.
Grade: 1.
Class. A.

(C) Weight: 0.0353 ounce maximum.

Operating temperature range: -55°C to +105°C.

Ambient temperature 90°C

Temperature rise: 15°C.

Terminal pull: 5 pounds.

Altitude: 70,000 feet.

Shock, specified pulse: MIL-STD-202, method 213, test condition I, is applicable.

Dielectric withstanding voltage (sea level): MIL-STD-202, method 301, test voltage of 1,000 V rms for a minimum of 60 seconds

Barometric pressure (reduced): MIL-STD-202, method 105, test condition C, test voltage of 200 V rms for a minimum of 60 seconds

Percent coupling 3 percent maximum.

Electrical characteristics See tables I and II

Inductance: See table I.

Q values: See table I.

Self-resonant frequency: See table I.

DC resistance: See table I.

(C) Part or Identifying Number (PIN): MS75088-(dash number from table I).

TABLE I. Electrical characteristics (initial) and dash numbers.

Dash no. 1/	Type designation 2/	Superseded MS PIN	Inductance (µH)	Q (min)	Test frequency (MHz)	SRF min (MHz)	DC resistance (ohms)	Rated dc current (mA)
-1	LT10K203	MS90537-13	1.00 ±10%	44	25	140	.07	1,070
-2	LT10K204	MS90537-14	1.20 ±10%	44	7.9	130	.10	895
-3	LT10K205	MS90537-15	1.50 ±10%	44	7.9	115	.12	815
-4	LT10K206	MS90537-16	1.80 ±10%	44	7.9	105	.14	775
-5	LT10K207	MS90537-17	2.20 ±10%	44	7 9	100	.19	650
-6	LT10K208	MS90537-18	2.70 ±10%	44	7.9	92	.28	535
-7	LT10K209	MS90537-19	3.30 ±10%	44	7.9	85	.35	480
-8	LT10K210	MS90537-20	3.90 ±10%	44	7.9	75	.40	450
-9	LT10K211	MS90537-21	4.70 ±10%	44	7.9	70	.55	380
-10	LT10K212	MS90537-22	5.60 ±10%	44	7.9	65	.72	335
-11	LT10K213	MS90537-23	6.80 ±10%	50	7.9	55	1.02	280
-12	LT10K214	MS90537-24	8.20 ±10%	50	7.9	50	1.32	250
-13	LT10K215	MS90537-25	10.0 ±10%	50	7.9	46	1.62	220
-14	LT10K216	MS90537-26	12.0 ±10%	55	2.5	44	2.00	200

1/ The dash number added to MS military standard number constitutes the MS PIN; for example MS75088-1

2/ The coils specified herein are substitutes for the inactivated coils on MS90537, providing the small decrease in physical dimensions are not a factor. The decrease in maximum operating temperature from 125°C to 105°C does not downgrade these coils but assures satisfactory operation at 105°C for a minimum of 2,000 hours of life, rather than a shorter period of operation at 125°C.

Source: https://assist.dla.mil -- Downloaded: 202640-23T20:28Z
Check the source to verify that this is the current version before use.

TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from initial measurement		Allowable percent from specified minimum value in electrical characteristics (initial) table	
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±5	---	---	-10
Group III	±5	±(3% +.001 ohm)	-8	-10
Group IV	±5	±(2% +.001 ohm)	-5	-10
Quality conformance inspection group C				
Subgroup I	±5	---	---	-10
Subgroup II	±5	±(2% +.001 ohm)	-5	-10
Subgroup III	±5	±(3% + 001 ohm)	-8	-10

(C) 1/ Test fixture allowance of + 01 µH shall be added to all change in inductance limits ±(_ percent +.01 µH).

Application notes:

1. These coils are intended to be supported by their leads.
2. Solderable/weldable lead wire AWG 24.

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, ME, MI
Navy - AS, MC, OS, SH
Air Force - 17, 19
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5950-0865)

Source: https://assist.dla.mil -- Downloaded: 202610-23T20:28Z
Check the source to verify that this is the current version before use.