
MS9743

FED SUP CLASS 5306



PART NO.	L	K	APPROX WEIGHT LB/100
MS9743-04	.500	.088-.108	2.14
MS9743-05	.562	.088-.108	2.25
MS9743-06	.625	.088-.108	2.36
MS9743-07	.688	.088-.108	2.47
MS9743-08	.750	.088-.108	2.58
MS9743-09	.812	.088-.108	2.70
MS9743-10	.875	.088-.108	2.81
MS9743-11	.938	.088-.108	2.92
MS9743-12	1.000	.088-.125	3.03
MS9743-13	1.062	.128-.188	3.14
MS9743-14	1.125	.190-.250	3.25
MS9743-15	1.188	.252-.312	3.36
MS9743-16	1.250	.315-.375	3.47
MS9743-17	1.312	.378-.438	3.58
MS9743-18	1.375	.440-.500	3.70
MS9743-19	1.438	.502-.562	3.81
MS9743-20	1.500	.565-.625	3.92
MS9743-21	1.562	.628-.688	4.03

PART NO.	L	K	APPROX WEIGHT LB/100
MS9743-22	1.625	.690- .750	4.14
MS9743-23	1.688	.752- .812	4.26
MS9743-24	1.750	.815- .875	4.37
MS9743-25	1.812	.878- .938	4.48
MS9743-26	1.875	.940-1.000	4.59
MS9743-27	2.000	1.065-1.125	4.81
MS9743-28	2.125	1.190-1.250	5.04
MS9743-29	2.250	1.315-1.375	5.26
MS9743-30	2.375	1.440-1.500	5.48
MS9743-31	2.500	1.565-1.625	5.70
MS9743-32	2.625	1.690-1.750	5.93
MS9743-33	2.750	1.815-1.875	6.15
MS9743-34	2.875	1.940-2.000	6.37
MS9743-35	3.000	2.065-2.125	6.60
MS9743-36	3.125	2.190-2.250	6.82
MS9743-37	3.250	2.315-2.375	7.04
MS9743-38	3.375	2.440-2.500	7.26
MS9743-39	3.500	2.565-2.625	7.49

PART NO.	L	K	APPROX WEIGHT LB/100
MS9743-40	3.625	2.690-2.750	7.71
MS9743-41	3.750	2.815-2.875	7.93
MS9743-42	3.875	2.940-3.000	8.16
MS9743-43	4.000	3.065-3.125	8.38
MS9743-44	4.125	3.190-3.250	8.60
MS9743-45	4.250	3.315-3.375	8.83
MS9743-46	4.375	3.440-3.500	9.05
MS9743-47	4.500	3.565-3.625	9.27
MS9743-48	4.625	3.690-3.750	9.50
MS9743-49	4.750	3.815-3.875	9.72
MS9743-50	4.875	3.940-4.000	9.94
MS9743-51	5.000	4.065-4.125	10.16
MS9743-52	5.125	4.190-4.250	10.39
MS9743-53	5.250	4.315-4.375	10.61
MS9743-54	5.375	4.440-4.500	10.82
MS9743-55	5.500	4.565-4.625	11.05
MS9743-56	5.625	4.690-4.750	11.27
MS9743-57	5.750	4.815-4.875	11.49
MS9743-58	5.875	4.940-5.000	11.72
MS9743-59	6.000	5.065-5.125	11.94

1. SHANK SHALL BE STRAIGHT WITHIN .003 PER INCH OF BOLT LENGTH.
2. THE RUNOUT OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3. THE RUNOUT OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND DOUBLE HEXAGON OD SHALL BE WITHIN .008 FIR.
4. INCOMPLETE THREADS NOT TO ENTER FILLET.
5. MATERIAL: CRES AMS 5643.
6. HARDNESS: ROCKWELL C32-38.
7. MANUFACTURING SPECIFICATION: AMS 7474.
8. FLUORESCENT PENETRANT INSPECTION PER AMS 2645.
9. SURFACE TEXTURE: USAS B46.1-1962. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES EXCEPT UPSET HEAD.
10. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
11. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.
12. DO NOT USE UNASSIGNED PART NUMBERS.

Ⓑ REINSTATED 31 OCT 84

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIV.

APPROVED 3 MAY 69 REVISED Ⓐ 21 DEC 83 Ⓑ 31 OCT 84

Review activities: Ⓑ AIR FORCE - 82 DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A.	AS	TITLE	MILITARY STANDARD
Other Cust Ⓑ	AV 99	BOLT, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, PD SHANK, CRES AMS 5643, .3125-24 UNJF-3A	MS9743
PROCUREMENT SPECIFICATION		SUPERSEDES:	PAGE 1 OF 1

DD FORM 1 SEP 87 672-1 PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE. 5306-0873

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:24Z
Check the source to verify that this is the current version before use.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1989-241-518/A-5352