MILITARY SPECIFICATION

LAUNCHER, GUIDED MISSILE, LAU-7 SERIES

This amendment forms a part of Military Specification MIL-L-22620D, dated 3 February 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

In upper right hand corner, delete "MIL-L-22620D(AS)" and substitute: "MIL-L-22620D."

Under title, delete the preamble in its entirety and substitute: "This specification is approved for use by all Departments and Agencies of the Department of Defense."

PAGE 2

*

2.1, under Military, delete "MIL-P-81001 Power Supply, PP-2581/A" and substitute: "MIL-P-85576 Power Supply PP-2581A/A."

2.1, after MIL-R-81202, delete title in its entirety and substitute: "Receiver Assembly, Nitrogen, for LAU-7 Series Launchers."

2.1, under Naval Air Systems Command, delete "DL58A164H791" and its title and substitute: "DL58A164H891 Data List, Guided Missile Launcher, LAU-7/A-5 (Navy type)."

2.1, under Naval Air Systems Command, delete "DL60A89D114" and its title and substitute: "DL60A89D600 Data List, PP-2581A/A Power Supply."

2.1, under Naval Air Systems Command, add "58A164D710 Drawing, Dummy Power Supply."

PAGE 4

*

3.7.3, delete sentence in its entirety and substitute: "The power supply, PP-2581A/A, shall be in accordance with MIL-P-85576."

FSC 1055

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:07Z
Check the source to verify that this is the current version before use.

PAGE 6

4.3f, under "AIM-9J 170 Pounds" add "AIM-9L 191 Pounds."

4.3f under, "AIM-9H 198 Pounds" add "AIM-9L 188 Pounds."

4.3g, line 4, delete "MIL-P-81001" and substitute: "MIL-P-85576."

4.3g, line 5, delete "PP-2581/A" and substitute: "PP-2581A/A."

PAGE 7

Figure 1, first line, delete "(AIM-9E, 9J)" and substitute: "(AIM-9E, 9J and 9L)."

Figure 2, first line, delete "(AIM-9D, 9G, 9H)" and substitute: ("AIM-9D, 9G, 9H and 9L)."

PAGE 8

TABLE II, test H, change spelling from "Mchanical" to "Mechanical."

4.6.2.1, line 5, delete "A minimum of four (4) samples shall be taken" and substitute: "A minimum of four launchers shall be taken from each lot."

PAGE 12

4.6.3.1h, delete "Fairings" and substitute: "Fairings and Fin Retainers."

PAGE 14

Figure 4, top and bottom, delete "0.092 ± .020" and substitute: "0.920 ± .020."

PAGE 17

4.6.5.2.1, Type I launcher, delete sentence in its entirety and substitute: "The electrical circuit continuity shall be in accordance with drawing 58A164D810 and MIL-P-85576."

4.6.5.2.2, Type II launcher, second line, delete "PP-2581/A" and substitute: "PP-2581A/A."

4.6.5.3.1, line 3, delete "0.300 ± 0.002" and substitute: "0.280 ± 0.001."

4.6.5.3.1, line 5, delete "0.280 ± 0.002" and subbstitute: "0.250 ± 0.001."

4.6.5.4a, second line, add "To verify the diode function (across solenoid terminals) of Type I launchers, the de-energizing voltage spike shall not exceed 40 VDC."

4.6.5.6.1, line 2, delete "58A164D571" and substitute: "58A164D810."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:07Z
Check the source to verify that this is the current version before use.

PAGE 18

4.6.5.6.1, under NOTE, delete "58A164D571" and substitute: "58A164D810."

4.6.6.1a, line 2, add "The detent wrench/safety pin shall not be removable with the detent solenoid energized."

PAGE 19

4.6.7.1, line 2, add "During quality conformance inspection of lots, the umbilical hook support assembly shall not cause any undue binding, interference, etc., when loading or down loading the test missile."

4.6.7.2, delete title, "Fairings" and substitute "Fairings and fin retainers."

4.6.7.2, line 2, add "During quality conformance inspection of lots, the fin retainer assemblies shall adequately retain the forward fins of the missiles listed in 4.3"

4.6.7.5, line 2, delete "MIL-P-81001" and substitute: "MIL-P-85576."

PAGE 21

4.6.8.2, lines 1 and 2, delete first sentence in its entirety and substitute: "The launcher shall be placed within a chamber whose ambient temperature is room temperature; the ambient temperature shall then be reduced to -54°C (-65°F) and held for a minimum of four hours."

4.6.8.2, line 5, delete "four hour period" and substitute: "leakage test."

4.6.8.5, line 2, delete "510" and substitute: "510.2."

PAGE 22

4.6.8.7, line 2, delete "509" and substitute: "509.2."

4.6.8.8, line 2, delete "500" and substitute: "500.2."

PAGE 25

4.6.8.10.4, line 1, delete "and inadvertent release."

4.6.8.11, line 2, delete "507" and substitute: "507.2."

PAGE 29

Below 6.6, add activity symbols as shown:

"Custodians:
Navy - AS
Air Force - 99
Review activity:
Air Force - 84"

"Preparing activity
Navy - AS"

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:07Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Navy - AS
Air Force - 99

Review activity:
Air Force - 84

Preparing activity:
Navy - AS
(Project No. 1055-0072)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:07Z
Check the source to verify that this is the current version before use.