MIL-R-22573(WEP)
AMENDMENT-2
1 APRIL 1964
SUPERSEDING
AMENDMENT-1
15 NOVEMBER 1963

MILITARY SPECIFICATION

RADAR BEACON AN/APN-132(*)

This amendment forms a part of Military Specification MIL-R-22573 (WEP) dated 1 August 1960 and has been approved by the Bureau of Naval Weapons, Department of the Navy.

Page 4, Paragraph 3.2.11.2: Delete and substitute "3.2.11.2 Shock - The equipment shall operate satisfactorily when subjected to shocks of 15 G's (11 millisecond duration) on each of the 3 major axes. The equipment shall remain intact when subjected to a shock of 50 G's (11 millisecond duration) on each axis."

Page 4, Paragraph 3.3.2.2: Delete and substitute "3.2.2.2 Transmitter - The transmitter frequency shall be adjustable to any frequency from 9310 to 9400 mc, by the installation of one of three magnetrons. Each magnetron shall be adjustable over a range of 30 mc."

Page 5, Paragraph 3.3.3.1: Delete and substitute "3.3.3.1 Interrogation Signal - The equipment shall receive radar interrogation signals. The interrogation signal may be either single or paired pulses having a pulse duration of 0.5 ± 0.1 microsecond. The rise time of the interrogation will be 0.1 microsecond or less and the fall time 0.2 microsecond or less. The spacing between the paired pulses is adjustable, at the radar, from 1.5 to 6 microseconds in 0.1 microsecond increments."

Page 5, Paragraph 3.3.4.2: Delete and substitute "3.3.4.2 Double Pulse Interrogation - The Radar Beacon shall respond to any one of five spacings of double pulse interrogation as follows:

(a) 1.9 ± 0.02 microseconds - Mode 1

(b) 2.8 ± 0.02 microseconds - Mode 2

(c) 3.7 ± 0.02 microseconds - Mode 3

(d) 4.6 ± 0.02 microseconds - Mode 4

(e) 5.5 ± 0.02 microseconds - Mode 5

FSC 5841

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:58Z
Check the source to verify that this is the current version before use.

Individual pulse characteristics are:

(a) Pulse width - 0.5 ± 0.1 microseconds

(b) Pulse rise time - 0.1 microseconds or less

(c) Pulse fall time - 0.2 microseconds or less."

Page 5, Paragraph 3.3.4.2.1: Delete and substitute "3.3.4.2.1 Double Pulse Reject Limits:

(1) When the radar beacon is set for acceptance of a double pulse interrogation whole nominal spacing is 1.9 microseconds, interrogations having a pulse spacing less than 1.4 microseconds or greater than 2.4 microseconds shall not cause a beacon response to be generated.

*(2) When the radar beacon is set for acceptance of a double pulse interrogation whose nominal spacing is 2.8 microseconds, interrogations having a pulse spacing less than 2.4 or greater than 3.3 microseconds shall not cause a beacon response to be generated.

(3) When the radar beacon is set for acceptance of a double pulse interrogation whose nominal spacing is 3.7 microseconds, interrogations having a pulse spacing less than 3.3 microseconds or greater than 4.2 microseconds shall not cause a beacon response to be generated.

(4) When the radar beacon is set for acceptance of double pulse interrogation whose nominal spacing is 4.6 microseconds, interrogations having a pulse spacing less than 4.2 microseconds or greater than 5.1 microseconds shall not cause a beacon response to be generated.

(5) When the radar beacon is set for acceptance of a double pulse interrogation whose nominal spacing is 5.5 microseconds, interrogations having a pulse spacing less than 5.1 microseconds or greater than 6.2 microseconds shall not cause a beacon response to be generated."

Page 5, Paragraph 3.3.4.3: Delete and substitute "3.3.4.3 Interrogation Control - The mode of interrogation to which the beacon shall respond (single pulse mode or one of five separate double pulse modes), shall be remotely and/or locally (receiver and transmitter box) controlled. When used with the control as specified in 3.4.2 and appropriate interconnecting cable, the mode of interrogation to which the beacon will respond shall be remotely controlled."

Page 7, Paragraph 3.4.1.5 (5); Delete and substitute "(5) Double pulse mode control:

(a) Selection of any of five double pulse modes of decoding operation when alternate control unit and appropriate interconnecting cable are employed. (See 3.3.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T12:58Z
Check the source to verify that this is the current version before use.

(b) When the control unit (See 3.4.2) and appropriate interconnecting cables are employed this control shall have no effect."

Page 7, Paragraph 3.4.1.6: Delete and substitute "3.4.1.6 Electrical Connections - Connections to external circuits shall be provided by standard receptacles in accordance with MIL-E-5400 as follows:

Reference Designation	Receptacle Type	Function
J 1	18 pin male connector Bendix Type PT07H14-18P (or approved equivalent)	Power and control functions for RT-513/APX-132
J 2	Waveguide flange UCl 135/U Modified with threaded holes (8-32) in place of 0.169 dia. clearance holes (4 places) (or approved equivalent)	Transmitter output
J 3	Waveguide flange UCl 135/U Modified threaded holes (8-32) in place of 0.169 dia. clearance holes (4 places) (or approved equivalent)	Receiver input
P2001	18 pin male connector Bendix Type PT07E-14-18P (or approved equivalent)	Power and control functions from C-3908/APX-132."

Page 8, Paragraph 3.4.2.5: Delete "MIL-E-3400" and substitute "MIL-E-5400".

Page 8: Add "3.4.3.1 Weight - The weight of the mounting shall not exceed 4.75 pounds."

Page 16, Paragraph 6.6.6: Add "not including pulse droop."

An asterisk preceding a paragraph number denotes a change to be made to the specification which did not appear in the previous amendment.

Source: https://assist.dla.mil -- Downloaded: 20260-19T12:58Z
Check the source to verify that this is the current version before use.