MILITARY SPECIFICATION

PRESSURE RELIEF DEVICES, OVERPRESSURIZATION PREVENTION WHEEL/TIRE, AIRCRAFT

This specification is approved for use by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete 2.1 and substitute:

2.1 Government documents.

Add: 2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of the specification to the extend specified herein.

Under Specifications Federal, change to read:

PPP-B-636 Boxes, Shipping, Fiberboard

Add this statement to the bottom of page 1.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Naval Air Engineering Center, Systems Engineering and Standardization Department (Code 93), Lakehurst, NJ 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

PAGE 2

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for Specification sheets), the text of this specification shall take precedence.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.

PAGE 3

3.4.1, line 4: Delete "5000 psig" and substitute "3000 psig".

PAGE 4

3.4.6, change to read: "Length. The devices shall not exceed 1.75 inches in overall length, including inflation stem, but not including threaded mounting end fitting."

PAGE 5

3.5.1, change to read: "High pressure. The device shall not structurally fail when an internal pressure of 4500 psig is applied pneumatically or hydraulically from the inflation end as specified in the burst pressure test of 4.6.5."

PAGE 8

4.3.2, line 3: Delete "(AIR-530321C)" and substitute "(AIR-530)".

PAGE 9

4.5.4, line 4: Delete one extra "shall".
4.6.3, line 2: Delete "5000 psig" and sustitute "3000 psig".

PAGE 10

4.6.4.2, line 3: Delete "5000 psig" and substitute "3000 psig".

4.6.5, change to read: "Burst pressure. A device shall be plugged on the outlet end and a pneumatic or hydraulic pressure of 4500 psig introduced into the inlet end, held for two seconds, then released. The device shall not structurally fail during the test."

PAGE 13

4.6.16, line 4: Delete "5000 psig" and substitute "3000 psig".
4.6.16, line 6: Delete "shal" and substitute "shall".

PAGE 15

6.3, line 10: Delete "(AIR-530321C)" and substitute "(AIR-530)".

Preparing Activity:
Navy - AS
(Project No. 1630-N336)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:29Z
Check the source to verify that this is the current version before use.